Vehicle: [Fleet] 2026 Chevrolet Silverado MD (CC56043) 2WD Crew Cab WT (✔ Complete)

Standard Equipment

Mechanical	
	GVWR, 16,500 lbs. (7484 kg) (Silverado 4500 HD Crew Cab 2WD models require one of the following combinations: (1) (FTA) 7k front axle and (FK6) 7k front suspension and (FN1) 10k rear axle or (GL4) 11k rear axle and (GR3) 11k rear suspension or (G40) 12K Rear air suspension. (2) (FTA) 7k front axle and (FK6) 7k front suspension and (HD1) 15k rear axle or (J27) 15.5k rear axle and one of the following rear suspensions: (GR4) 13.5k rear suspension, (FU7) 15.5k rear suspension, (GP1) 13.5K rear air suspension, (GP8) 15.5k rear air suspension, (91B) 13.5k LiquidSpring prep single volume rear suspension, (91C) 13.5k LiquidSpring prep stacked volume rear suspension, (91D) 15.5k LiquidSpring prep single volume rear suspension or (91E) 15.5k LiquidSpring prep stacked volume rear suspension.) (STD)
	Emissions, 50 state certification
	Emissions, USA 50 State certified
	Engine, Duramax 6.6L Turbo-Diesel V8, B20-Diesel compatible 350 hp @ 2500 rpm, 750 lb.-ft. torque @ 1400 rpm (STD)
	Highway Service Transmission, Automatic close-ratio 6 SPD with double overdrive, Allison, A1700HS ratios: 3.10 1ST, 1.80 2ND, 1.40 3RD, 1.00 4TH, 0.70 5TH, 0.61 6TH Highway Series, 19.5K GVW & 26K GCW Max., requires PTX and park pawl. Available with GVWs less than or equal to 19.5K (Requires (C7Y) 14,001 lbs. GVWR, (C5B) 15,000 lbs. GVWR, (C7P) 16,000 lbs. GVWR, (C7R) 16,500 lbs. GVWR, (GZX) 17,500 lbs. GVWR, (GZJ) 18,000 lbs. GVWR or (GZG) 19,500 lbs. GVWR. Requires (R6G) 26,000 lb. GCWR (11,793 kg).) (STD)
	Rear axle, 4.10 ratio Max road speed: 79 MPH
	Wheelbase, 175" (444.5 cm), 60" CA (Requires (F0C) 49" axle to end of frame. Not available with (G40) 12,000 lbs., (GP1) 13,500 lbs. or (GP8) 15,500 lbs. rear air suspension, (N12) straight exhaust system that terminates ahead of rear wheels, or (NPK) right side exit exhaust ahead of rear wheels.) (STD)
	Front axle, 7,000 lbs, Dana Spicer D800-N, "I"-beam, non-driving (Requires (FK6) 7,000 lb. (3,175 kg) front suspension.)
	Front suspension, 7,000 lbs. (3,175 kg) multi-leaf, includes shock absorbers (STD)
	Rear axle, 11,000 lb. (4,999 kg)
	Rear suspension, 11,000 lbs. (4,990 kg) multi-leaf, vari-rate (Not available with air suspension.) (STD)
	Neutral-at-Stop Automatic transmission shifts to neutral when the service brake is depressed while the vehicle is at a complete stop, and remains in neutral until the service brake is released
	Transmission shift control calibration, fuel sense Performance
	Rear wheel drive
	Batteries, heavy-duty dual 1100 cold-cranking amps includes battery box mounted to left side under cab
	Alternator, 150 amps
	Trailering provisions, trailering wire harness only, trailer combined (Stop/Tail/Turn) connection socket and harness mounted at rear of frame.
	Trailer brake controller, integrated
	Incomplete vehicle

Vehicle: [Fleet] 2026 Chevrolet Silverado MD (CC56043) 2WD Crew Cab WT (✓ Complete)

Mechanical	
	Axle to End of Frame, 49" (Requires wheelbase (EM1) 199" or (FNV) 175". Not available with (G40), (GP1) or (GP8) rear air suspension.)
	Axle, Open rear axle, non-locking rear
	Axle lubricant, rear, synthetic oil EmGard FE -75W-90
	Steering, power (Bosch S2 8014 Plus)
	Brakes, hydraulic, heavy duty Bosch/Meritor/Wabco system with 4-channel (ABS) (Includes (J69) driveline park brake.)
	Fuel tank, rear only, 40 gallon mounted between frame side rails and behind rear axle
	Fuel, diesel B20
	Capped Fuel Fill
	Exhaust system, right side exit, behind rear wheels (Requires (FNV) 175" wheelbase.)
	Exhaust brake
Exterior	
	Wheels, 19.5" x 6.75", steel, Black painted, 8-holes, hub piloted (STD)
	Tires, front 225/70R19.5G highway blackwall Pirelli Max Axle Load: 7,940 lbs. (Requires (YEY) Tires, rear 225/70R19.5G highway blackwall Pirelli, Max Axle Load: 15,000 lbs. or (YEZ) Tires, rear 225/70R19.5G traction blackwall Pirelli, Max Axle Load: 15,000 lbs.) (STD)
	Tires, rear 225/70R19.5G highway blackwall Pirelli Max Axle Load: 15,000 lbs. (Requires (XEY) Tires front 225/70R19.5G Highway blackwall Pirelli.) (STD)
	Spare tire delete (STD)
	Wheel, spare delete
	Bumper, front, Black
	Assist steps
	Front fender extension, painted body color
	Grille, base, molded in color, Black
	Grille guard screen, insect protection (mounted behind grille)
	Headlamps, halogen projector-beam
	Lamps, cargo area, cab mounted with switch on center switch bank
	Lamps, Smoked Amber roof marker
	Lamps, rear, stop/turn/backup (1-piece assembly) with license plate light
	Mirrors, outside high-visibility vertical camper-style, Black with manual folding and extension and lower convex spotter glass
	Glass, solar absorbing, tinted

Vehicle: [Fleet] 2026 Chevrolet Silverado MD (CC56043) 2WD Crew Cab WT (✓ Complete)

Exterior	
	Antenna, fixed mast
	Door handles, Black
Entertainment	
	Audio system, 4.2" diagonal color display, AM/FM stereo with USB port and auxiliary jack (Requires (AE7) front 40/20/40 split-bench seat. Not available with (UE1) OnStar services capable.) (STD)
	SiriusXM, delete
	6-speaker audio system
Interior	
	Seats, front 40/20/40 split-bench, 3-passenger driver and front passenger recline with outboard head restraints and center fold-down armrest with storage. Vinyl has fixed lumbar and cloth has manually adjustable driver lumbar. (Not available with (H0U) Jet Black Interior.) (STD)
	Interior trim, Jet Black/Dark Ash (Required and only available with (H2Q/H2R) Dark Ash seats with Jet Black interior accents.)
	Seat trim, Vinyl
	Seat, rear 60/40 folding bench (folds up), 3-passenger (includes child seat top tether anchor)
	Seat Belt, Black
	Floor covering, Graphite-colored rubberized-vinyl
	Steering wheel, urethane
	Steering column, manual Tilt-Wheel
	Instrumentation, 6-gauge cluster featuring speedometer, fuel level, engine temperature, tachometer, voltage and oil pressure
	Speedometer, miles/kilometers
	Driver Information Center, 3.5" diagonal monochromatic display provides warning messages and basic vehicle information
	Upfitter switch kit provides up to 4-30 amp circuits to facilitate installation of aftermarket electrical accessories located on the instrument panel
	Windows, power with driver express up and down and express down on all other windows
	Door locks, power
	Cruise control, steering wheel-mounted
	Air conditioning, single-zone
	Mirror, inside rearview manual day/night
	Visors, driver and front passenger, vinyl
	Assist handle, front passenger and driver on A-pillars

Vehicle: [Fleet] 2026 Chevrolet Silverado MD (CC56043) 2WD Crew Cab WT (✓ Complete)

Safety-Mechanical	
	Brake, parking, driveline park brake system
	StabiliTrak, Electronic Stability Control System with Traction Control includes Electronic Trailer Sway Control and Hill Start Assist
	Traction control
Safety-Exterior	
	Daytime Running Lamps, with automatic exterior lamp control
Safety-Interior	
	Airbags, Single-stage frontal airbags for driver and front outboard passenger; Seat-mounted side-impact airbags for driver and front outboard passenger; Head-curtain airbags for front and rear outboard seating positions; (Always use seat belts and child restraints. Children are safer when properly secured in a rear seat in the appropriate child restraint. See the Owner's Manual for more information.)
	Airbag deactivation switch, frontal passenger-side (Included and only available with (AY0) airbags.)
	OnStar, delete
	Rear Vision Camera, display integrated into Radio (Shipped loose in cab for upfitter installation.)
	Horn, Trumpet Style, single-note