Vehicle: [Fleet] 2027 Chevrolet 4500 HD LCF Diesel (CT31003) 2WD Reg Cab 109" (✓ Complete)

Standard Equipment

Mechanical	
	Emissions, Federal certification. Does NOT meet California emissions requirements - TRUCKS CANNOT BE SOLD OR REGISTERED IN CALIFORNIA.
	Engine, Diesel 5.2L 4 cylinder 215 hp [160.3 kW] @2500 rpm, 452 lb-ft of torque [612.8 Nm] @ 1850-2750 rpm (Governed). 16 valve, four cycle, chain-driven dual overhead camshaft valve train, a cast iron cylinder block, and a cast aluminum cylinder head. Turbocharged, inter-cooled, water cooled EGR, direct injection, electronically controlled common rail fuel system and engine cruise control. Oil level check switch and light. Engine warning system with audible warning for low oil pressure, high coolant temperature, and a protection system that will reduce fueling if excessive coolant temperature is detected (STD)
	Transmission, 6-speed automatic Aisin A465 transmission with fifth and sixth gear overdrive with lock up in 2nd, 3rd, 4th, 5th and 6th, PTO capability automatic torque converter lockup in stationary PTO mode. (STD)
	Rear axle, 4.56 ratio
	Air cleaner, heavy-duty, 11" diameter dry paper single element. Air cleaner canister standard with air restriction gauge. Back of cab location.
	Drivetrain, rear-wheel drive
	Battery, dual 750 cold-cranking amps, 12 volt, maintenance free
	Alternator, 140 amps
	Frame, ladder-type channel frame. Full C section straight frame 33.5" (85.1 cm) wide.
	Incomplete vehicle certification
	Wheelbase, 109" (276.9 cm)
	GVWR, 14,500 lbs. (6577 kg)
	Front suspension, 6,830 lbs. (3098 kg) tapered leaf, semi-elliptical steel alloy. Includes shock absorbers and stabilizer bar.
	Rear Suspension, 9,880 lbs. (4481kg), tapered leaf spring with shock absorbers (Standard on 4500 HD only.)
	Front axle, 6,830 lbs. (3098 kg), reverse Elliot "I"-beam includes integral hydraulic power steering with an 18.8-20.9:1 gear ratio (Standard on 4500 HD and 4500 XD only.)
	Rear axle, 11,020 lbs. (4998 kg), full-floating with oil lubricated rear wheel-bearings
	Vehicle Application Truck
	Brakes, 4-wheel antilock, front and rear disc with traction control and stability control
	Exhaust brake
	Exhaust, single horizontal outlet
	Fuel tank, 30 Gallon, (113L), stainless steel includes 2 auxiliary fuel ports
Exterior	
	Wheels, 16" x 6, K. steel (STD)

Vehicle: [Fleet] 2027 Chevrolet 4500 HD LCF Diesel (CT31003) 2WD Reg Cab 109" (✓ Complete)

Exterior	
	Tires, front, 215/85R16 E, all-season (STD)
	Tires, rear, 215/85R16 E all-season (STD)
	Grille, Black
	Assist steps
	Glass, tinted
	LED Headlamps includes integrated LED turn signal indicators
	Headlamp washer system
	Mirror, outside left-hand and right hand dual cab-mounted with integral convex mirror
	Windshield wiper, pulse, wet arm
Entertainment	
	Audio System, AM/FM stereo with auxiliary jack, USB port and Bluetooth (STD)
	Audio system feature, 2 speakers
Interior	
	Seat, front high back bucket driver and passenger tricoat cloth covered reclining high back driver seat with single two occupant fold down passenger seat (STD)
	Seat trim, Cloth
	Cup holders
	Floor mats
	Steering wheel, urethane
	Steering wheel, tilt and telescopic
	Driver Information Center, (DIC) (monitors vital functions including diesel exhaust fluid levels (DEF), particulate matter emissions level in the diesel particulate filter (DPF), diesel particulate filter regeneration, service reminders for engine oil, transmission oil, differential oil, power steering fluid, engine oil filter, and fuel filters. Also provides fuel economy reporting by average, instant, and trip.)
	Air conditioning, single-zone electronic, integral in-dash mounted
	Windows, power
	Door locks, power
	Remote Keyless Entry
	Cruise control, electronic, automatic
	Windshield washer bottle access on passenger side dash when passenger-side door is open
	Storage, door pockets
	Lighting, interior dome