Vehicle: [Fleet] 2027 Chevrolet 7500 XD LCF Diesel (CT87603) 2WD Reg Cab 236" (✓ Complete)

Standard Equipment

Mechanical	
	Engine, Cummins B6.7L turbocharged 6-cylinder diesel engine, delivering 260 hp and and 660 lb-ft of torque (STD)
	Transmission Allison 2500RDS 6-speed automatic. Includes PTO Gear, with access only on driver's side of transmission. (Standard and only available on 7500 XD model.) (STD)
	Rear axle, 5.57 ratio (Standard on 7500 XD model and available on 6500 XD with (XUH) and (YUH) 11R22.5G tires.)
	GVWR, 33,000 lbs. (14,969 kg) (Standard and only available on 7500 XD model.) (STD)
	Air cleaner, heavy-duty, 11" diameter dry paper single element. Air cleaner canister standard with air restriction gauge. Back of cab location.
	Drivetrain, rear-wheel drive
	Battery, dual 750 cold-cranking amps, 12 volt, maintenance free with threaded post
	Alternator, 160 amps
	Frame, ladder-type channel frame. Full C section straight frame 33.5" (85.1 cm) wide. Yield strength 80,000 psi, section modulus 12.69 cu.in. and RBM 1,015,000 lb-ft/in per rail.
	Incomplete vehicle certification
	Wheelbase, 236" (599.4 cm)
	Front suspension, 12,000 lbs. (5450 kg) tapered leaf semi-elliptical steel alloy. Includes shock absorbers with stabilizer bar
	Rear Suspension, 21,000 lbs. (9525 kg), semi-elliptical steel alloy bolted multi-leaf and shock absorbers
	Front axle, 12,000 lbs. (5,450 kg), Dana E-1254-W
	Rear axle, 21,000 lbs. (9525 kg) full-floating single-speed with oil lubricated rear wheel-bearings, Dana Spicer S21-140 (Standard and only available on 7500 XD model.)
	Vehicle Application Truck
	Brakes, dual circuit full air drum brakes with 4 channel anti-lock brake system
	Exhaust brake
	Fuel Tank, 100 Gallon, (378L), rectangular aluminum fuel tank mounted on left hand frame rail. Fuel water separator with indicator light.
	Exhaust, single horizontal outlet
Exterior	
	Wheels, 22.5 x 8.25 steel, painted white (STD)
	Tires, front, 11R22.5G standard profile LRR (low rolling resistance) tubeless steel belted radial. Front Highway tread. (Standard on 7500 XD model, available on 6500 XD model. Requires (074) 5.57 rear axle ratio and (YUH) 11R22.5G rear tires. Front GAWR will be increased from 11,000 lbs. to 12,000 lbs.)

Vehicle: [Fleet] 2027 Chevrolet 7500 XD LCF Diesel (CT87603) 2WD Reg Cab 236" (✓ Complete)

Exterior	
	Tires, Rear, 11R22.5G standard profile LRR (low rolling resistance) tubeless steel belted radial. Rear Highway traction tread. (Standard on 7500 XD model, available on 6500 XD model. Requires (074) 5.57 rear axle ratio and (XUH) 11R22.5G front tires.)
	Grille, color-keyed bar and grille surround
	Glass, tinted
	Grille, Silver
	Mirror, outside left hand and right hand dual cab mounted exterior with convex mirrors for 96" wide body
	LED Headlamps
Entertainment	
	Audio System, AM/FM stereo with auxiliary jack, USB port and Bluetooth (STD)
	Audio system feature, 2 speakers
Interior	
	Seat, high back driver only air suspension system and fixed passenger seat (STD)
	Seat trim, Cloth
	Cup holders
	Floor mats
	Steering wheel, urethane
	Steering column, Tilt-Wheel and telescoping steering column
	Driver Information Center, Multi-Information Display (MID) monitors vital functions including diesel exhaust fluid levels (DEF), particulate matter emissions level in the diesel particulate filter (DPF), diesel particulate filter regeneration, service reminders for engine oil, transmission oil, differential oil, power steering fluid, engine oil filter, and fuel filters. Also provides fuel economy reporting by average, instant, and trip.
	Windows, power
	Door locks, power
	Cruise control, electronic, automatic
	Windshield washer bottle access, underhood
	Air conditioning, single-zone manual, integral in-dash mounted
	Storage, door pockets
	Lighting, interior dome
	Storage, seatback pockets
Safety-Mechanical	
	Park brake, air-controlled, spring-type

Vehicle: [Fleet] 2027 Chevrolet 7500 XD LCF Diesel (CT87603) 2WD Reg Cab 236" (✓ Complete)

Safety-Exterior

	Daytime Running Lamps