

# Hino Standard Features

## Bid Invitation #HT06-16

The following descriptions are the standard features, as pulled from the Hino dealer quotation database. Offeror shall price these complete trucks in their entirety, on Form-D, reflecting the entire complement of the base vehicle specification's standard features listed herein, as well as all normal dealer make-ready and factory-to-dealer destination charges. Except as ordered by an H-GAC member (e.g. axle upgrade, longer wheelbase, et cetera), the base units described herein and priced on Form-D shall not require any additional compulsory components, fees, or services to render them complete, functional, and legal cab-chassis. All Form-D line items shall be priced inclusive of air conditioning.

---

### H-GAC Product Code: E1

#### 155 COE, SRA

Model 2016 Hino 155

Transmission Aisin A465 - 6 speed automatic transmission

Wheelbase 137.8

#### **Standard Options**

##### **Qty Order Code Description**

##### **1 ENGINE**

Engine - HINO J05E-TP Turbo charged and intercooled, diesel 4 cycle, 4 cylinder, In-line water-cooled; Max Output 210hp @ 2500rpm; Max Torque 440lb.ft. @ 1500rpm; 5L displacement, EPA10 Emissions Certified.

1 OIL Oil Capacity - 9.9 quarts

1 EXHBRAKE Exhaust brake, electric-pneumatic with valve in exhaust pipe.

1 FUELFILTCOE Fuel Filter - Pre Filter Heated Water Separator

1 ALT 12 volt 130 amp brushless alternator

1 BATTERY Two 12 volt parallel connection, 1244 CCA.

1 STARTER 12 volt 3.35 kW Denso starter

1 RADIO Radio - AM/FM with single CD

1 AIRCOND Air conditioned

##### **1 DISPLAY**

Meter Cluster - Information display: Instant and trip fuel consumption, Diesel Particulate Reduction System performance/status, maintenance intervals, engine and vehicle diagnostics.

1 PWDL-COE Power Windows and Door Locks

1 GAUGES Gauges - Speedometer mph (km/h), odometer, fuel/DEF gauges, coolant temp gauge, engine tachometer

1 FTGRILLCOE Grille - Chrome plated

1 HORNCOE Horn - Electric Horn

1 HEAT/DEF Heater/Defroster - 18,596 BTU/h

1 LAMPS Lighting - Stop/tail lights, marker and identification lamps (roof), back-up lamps

##### **1 MISC**

Cab Features - Standard: Cruise control, tilt and telescopic steering. Overhead compartments, door pockets, cup holders, side mirrors (1 flat, 1 convex) on each side

##### **1 SEATS**

Seats - Fabric covered reclining high back driver's seat.

Fabric passenger foldaway center seat and right fabric passenger seat.

##### **1 INDICATORS**

Warning Indicators - Oil pressure, brake fluid, battery charge, high beam, turn signal, parking brake, engine control system and ABS.

1 OBD On-Board Diagnostics

1 FREIGHT Equalized Freight Charge

1 COOLSYS Cooling Capacity - 5.90 gallon cooling system capacity

##### **1 WARRANTY\_05**

Warranty - Basic Vehicle - 36 months unlimited mileage

(exception batteries and expendables), Extended Engine and Vehicle - 60 months or 175,000 miles (includes injectors, fuel supply pump, turbo, transmission, and rear axle); Emissions - 60 months or 100,000 mile warranty;  
1 HWATCH\_05

Hino Watch Roadside Assistance - 3-year unlimited roadside assistance including lockout, \*out of fuel/DEF, battery jumpstart, information, and warranty towing (2 year coverage). \*Fluids are customer pay responsibility. Tire Service - assist customer in arranging for roadside tire service if requested

1 FUELTK Fuel Tank - 30 gallon rear center mount

1 GVWR GVWR - Gross Vehicle Weight Rating - 14,500 lbs.

1 BMP Bumper - painted, match to cab

1 BRAKES

Brakes - Hydraulic system with disc brakes, hydraulic assist with dual circuit. Brakes: 11.3" diameter x 3.31" x 0.51" thickness.

1 FRAME

Frame straight section ladder type, 33" width, yield strength 56,900 PSI, resistance bending moment 706,800 in./lbs. (two side no reinforcement).

1 WHEELS Wheels - Steel painted wheels 17.5X6K-127 6-stud disc.

1 FSTAB-COE Front Stabilizer Bar

1 BKBUZZ Backup Buzzer

1 TIRES Front tires - Bridgestone 215/75R 17.5 Rib Pattern; Rear

Tires - Bridgestone 215/75R 17.5 All Season.

1 AXLES

Front Axle - Reversed Elliot "I" beam. Front axle capacity is 5,950lbs.

Rear Axle - Full-floating, single reduction. Rear axle capacity is 13,660

1 SPRINGS

Front Spring: Tapered leaf springs with shock absorbers, 5,950lb. rating.

Rear Spring: Tapered leaf springs with shock absorbers and auxillary helper leaf spring, 9,877 lb. rating.

1 AXLESTD Rear Axle Ratio - Standard 4.63 with Aisin A465 six speed automatic

---

**H-GAC Product Code: E2**  
**195 COE, SRA**

Model 2016 Hino 195  
Transmission Aisin A465 - 6 speed automatic transmission  
Wheelbase 114.2

**Standard Options**

**Qty Order Code Description**

**1 ENGINE**

Engine - HINO J05E-TP Turbo charged and intercooled, diesel 4 cycle, 4 cylinder, In-line water-cooled; Max Output 210hp @ 2500rpm; Max Torque 440lb.ft. @ 1500rpm; 5L displacement, EPA10 Emissions Certified.

1 OIL Oil Capacity - 9.9 quarts

**1 EXHBRAKE**

Exhaust brake, electric-pneumatic with valve in exhaust pipe.

1 FUELFILTCOE Fuel Filter - Pre Filter Heated Water Separator

1 ALT 12 volt 130 amp brushless alternator

1 BATTERY Two 12 volt parallel connection, 1244 CCA.

1 STARTER 12 volt 3.35 kW Denso starter

1 RADIO Radio - AM/FM with single CD

1 AIRCOND Air conditioned

**1 DISPLAY**

Meter Cluster - Information display: Instant and trip fuel consumption, Diesel Particulate Reduction System performance/status, maintenance intervals, engine and vehicle diagnostics.

1 PWDL-COE Power Windows and Door Locks

**1 GAUGES**

Gauges - Speedometer mph (km/h), odometer, fuel/DEF gauges, coolant temp gauge, engine tachometer

1 FTGRILLCOE Grille - Chrome plated

1 HORNCOE Horn - Electric Horn

1 HEAT/DEF Heater/Defroster - 18,596 BTU/h

**1 LAMPS**

Lighting - Stop/tail lights, marker and identification lamps (roof), back-up lamps

**1 MISC**

Cab Features - Standard: Cruise control, tilt and telescopic steering. Overhead compartments, door pockets, cup holders, side mirrors (1 flat, 1 convex) on each side

**1 SEATS**

Seats - Fabric covered reclining high back driver's seat. Fabric passenger foldaway center seat and right fabric passenger seat.

**1 INDICATORS**

Warning Indicators - Oil pressure, brake fluid, battery charge, high beam, turn signal, parking brake, engine control system and ABS.

1 OBD On-Board Diagnostics

1 FREIGHT Equalized Freight Charge

1 COOLSYS Cooling Capacity - 5.90 gallon cooling system capacity

**1 WARRANTY\_05**

Warranty - Basic Vehicle - 36 months unlimited mileage (exception batteries and expendables), Extended Engine and Vehicle - 60 months or 175,000 miles (includes injectors, fuel supply pump, turbo, transmission, and rear axle); Emissions - 60 months or 100,000 mile warranty;

**1 HWATCH\_05**

Hino Watch Roadside Assistance - 3-year unlimited roadside assistance including lockout, \*out of fuel/DEF, battery jumpstart, information, and warranty towing (2 year coverage). \*Fluids are customer pay responsibility. Tire Service - assist customer in arranging for roadside tire service if requested

1 FUELTKN Fuel Tank - 30 gallon rear center mount

1 GVWR GVWR - Gross Vehicle Weight Rating - 19,500 lbs.  
1 BMP Bumper - painted, match to cab  
1 BRAKES  
Brakes - Hydraulic system with disc brakes, hydraulic assist with dual circuit. Brakes: 13.72" diameter x 4.37" x 0.51" thickness.  
1 FRAME  
Frame straight section ladder type, 33" width, yield strength 56,900 PSI, resistance bending moment 706,800 in./lbs. (two side no reinforcement).  
1 WHEELS Wheels - Steel painted wheels 19.5X6K-127 6-stud disc.  
1 FSTAB-COE Front Stabilizer Bar  
1 BKBZZ Backup Buzzer  
\$0.00  
1 TIRES  
Front tires - Bridgestone 225/70R 19.5 Rib Pattern; Rear Tires - Bridgestone 225/70R 19.5 All Season.  
1 AXLES  
Front Axle - Reversed Elliot "I" beam. Front axle capacity is 7,275lbs.  
1 SPRINGS  
Front Spring: Tapered leaf springs with shock absorbers, 7,275lb. rating.  
Rear Spring: Tapered leaf springs with shock absorbers and auxillary helper leaf spring, 13,669 lb. rating.  
1 AXLESTD  
Rear Axle Ratio - Standard 5.57 with Aisin A465 six speed automatic

---

**H-GAC Product Code: E3**  
**238 CONV. CAB, SRA**

Model 2016 Hino 238

Transmission Auto - Allison 2200RDS w/Syn Fluids (PTO)

Wheelbase 152.0

**Standard Options**

**Qty Order Code Description**

**1 ENGINE**

Engine - HINOJ08E-VC Turbo charged and intercooled with glow plugs, 6 cylinder, In-line water-cooled; Max Output 220hp @2500rpm; Max Torque 520lb.ft. @ 1500rpm; 7.68L displacement, EPA10 Emissions Certified.

1 OIL Oil Capacity - 16.15 quarts

**1 EXHBRAKE**

Exhaust Brake - Driver controlled w/steering column Stalk Switch

**1 FUELFILT**

Fuel Filter - Davco 243 Diesel Pro Heated fuel/water separator. (Diesel Pro 243)

1 ALT Alternator – Delco 12 volt 130 amp Brush Type

1 BATTERY Battery - Two 12 volt parallel connection, 600 CCA x 2

1 STARTER Starter – Denso 12 volt 4.8 kW / 6.4 HP rating

1 RADIO Radio - AM/FM with single CD, two speakers.

**1 AIRCOND**

Air Conditioning - Denso Cab AC System designed specifically for Hino - Refrigerant 134A

**1 DISPLAY**

Meter Cluster - Information display: Instant and trip fuel consumption, Diesel Particulate Reduction System performance/status, maintenance intervals, engine and vehicle diagnostics.

**1 GAUGES**

Gauges - Speedometer mph (km/h), odometer, fuel/DEF gauges, coolant temp gauge, engine tachometer, air pressure gauge.

1 FTGRILL Grille - Chrome plated

1 HORN Horn - Electric Dual Horn

1 HEAT/DEF Heater/Defroster - 18,357 BTU/h

**1 LAMPS**

Lighting - Marker lamps, stop/tail lights, back-up lights, side-flasher lights.

**1 MISC**

Cab Features - Standard: Cruise control, power steering with tilt and telescopic steering column, cup holders, cigarette lighter, coat hook, bag hook, two overhead compartments, two door pockets, sun visors, side mirrors (1 flat, 1 convex) each side.

**1 SEATS**

Seats - Vinyl driver seat adjustable reclining, with AIR suspension and two person passenger bench seat. Three point seatbelt for driver and outer passenger, two point seatbelt for center position.

**Standard Options**

**Qty Order Code Description**

**1 INDICATORS**

Warning Indicators - Oil pressure, brake pressure, coolant level, battery charge, high beam, turn signal, parking brake, engine control system and ABS.

1

1 FREIGHT Equalized Freight Charge

1 COOLSYS Cooling Capacity - 6.6 gallon cooling capacity

**1 WARRANTY\_05**

Warranty - Basic Vehicle-24 months unlimited mileage; Engine-36 months unlimited mileage; Engine-60 month Extended Coverage, 250,000 miles (includes injectors, fuel supply pump and turbo); Emission-60 months 100,000

miles; Frame Rails & Cross Members-48 months unlimited mileage; Cab-48 months unlimited mileage; ABS-24-36 months 300,000 miles.

1 HWATCH\_05

Hino Watch Roadside Assistance - 3-year unlimited roadside assistance including lockout, \*out of fuel/DEF, battery jumpstart, information, and warranty towing (2 year coverage). \*Fluids are customer pay responsibility. Tire Service - assist customer in arranging for roadside tire service if requested

1 FUELTK

Fuel Tank - Aluminum 50 gallon capacity. Clean CA position. (drivers side mounted)

1 GVWR GVWR - Gross Vehicle Weight Rating - 23,000 lbs.

1 AIRTANK Air Tank - 34 liter tank (9 gallon capacity)

1 BRAKES

Brakes - Hydraulic dual circuit with Antilock Brake System (ABS). Front Brakes: 15.375" diameter x 18.96" x 0.74" thickness: Rear Brakes: 15.375" x 18.96" x 0.74". Drum diameter 10" Meritor.

1 AIRDRYER Air Dryer - Nabtesco heated air dryer.

1 FRAME

Frame - Straight C Channel frame, ladder type, powder coated, 34" wide, yield strength 80,000 PSI, resistance bending moment (RBM) 1,031,900 in./lbs. (one side no reinforcement).

1 WHEELS

Wheels - Accuride powder coated 22.5" x 8.25" 10-stud disc.

1 TIRES

Front tires - Bridgestone 10R22.5 R268 Rib pattern; Rear tires - Bridgestone 10R22.5 M726EL Lug pattern.

1 AXLES

Front Axle - Meritor MFS8, 8,000 lb. capacity, Reverse Elliot "I" beam with oil lubricated hubs.

Rear Axle - Meritor RS17-145, 17,500 lb. capacity full-floating single reduction hypoid gearing.

1 SPRINGS

Front Spring: Tapered leaf springs with shock absorbers, 8,000 lb. rating; Rear Spring: Semi-elliptical main, 19,000 lb. rating.

1 AXLESTD Rear Axle Ratio - Standard 5.29

---

**H-GAC Product Code: E4**  
**258LP CONV. CAB, SRA**

Model 2016 Hino 258LP

Transmission Auto - Allison 2200RDS w/Syn Fluids (PTO)

Wheelbase 152.0

**Standard Options**

**Qty Order Code Description**

**1 ENGINE**

Engine - HINOJ08E-VC Turbo charged and intercooled with glow plugs, 6 cylinder, In-line water-cooled; Max Output 220hp @2500rpm; Max Torque 520lb.ft. @ 1500rpm; 7.68L displacement, EPA10 Emissions Certified.

1 OIL Oil Capacity - 16.15 quarts

**1 EXHBRAKE**

Exhaust Brake - Driver controlled w/steering column Stalk Switch

**1 FUELFILT**

Fuel Filter - Davco 243 Diesel Pro Heated fuel/water separator. (Diesel Pro 243)

1 ALT Alternator - Delco 12 volt 130 amp Brush Type

1 BATTERY Battery - Two 12 volt parallel connection, 600 CCA x 2

1 STARTER Starter - Denso 12 volt 4.8 kW / 6.4 HP rating

1 RADIO Radio - AM/FM with single CD, two speakers.

**1 AIRCOND**

Air Conditioning - Denso Cab AC System designed specifically for Hino - Refrigerant 134A

**1 DISPLAY**

Meter Cluster - Information display: Instant and trip fuel consumption, Diesel Particulate Reduction System performance/status, maintenance intervals, engine and vehicle diagnostics.

**1 GAUGES**

Gauges - Speedometer mph (km/h), odometer, fuel/DEF gauges, coolant temp gauge, engine tachometer, air pressure gauge.

1 FTGRILL Grille - Chrome plated

1 HORN Horn - Electric Dual Horn

1 HEAT/DEF Heater/Defroster - 18,357 BTU/h

**1 LAMPS**

Lighting - Marker lamps, stop/tail lights, back-up lights, side-flasher lights.

**1 MISC**

Cab Features - Standard: Cruise control, power steering with tilt and telescopic steering column, cup holders, cigarette lighter, coat hook, bag hook, two overhead compartments, two door pockets, sun visors, side mirrors (1 flat, 1 convex) each side.

**1 SEATS**

Seats - Vinyl driver seat adjustable reclining, with AIR suspension and two person passenger bench seat. Three point seatbelt for driver and outer passenger, two point seatbelt for center position.

**Standard Options**

**Qty Order Code Description**

**1 INDICATORS**

Warning Indicators - Oil pressure, brake pressure, coolant level, battery charge, high beam, turn signal, parking brake, engine control system and ABS.

1

1 FREIGHT Equalized Freight Charge

1 COOLSYS Cooling Capacity - 6.6 gallon cooling capacity

**1 WARRANTY\_05**

Warranty - Basic Vehicle-24 months unlimited mileage; Engine-36 months unlimited mileage; Engine-60 month Extended Coverage, 250,000 miles (includes injectors, fuel supply pump and turbo); Emission-60 months 100,000

miles; Frame Rails & Cross Members-48 months unlimited mileage; Cab-48 months unlimited mileage; ABS-24-36 months 300,000 miles.

1 HWATCH\_05

Hino Watch Roadside Assistance - 3-year unlimited roadside assistance including lockout, \*out of fuel/DEF, battery jumpstart, information, and warranty towing (2 year coverage). \*Fluids are customer pay responsibility. Tire Service - assist customer in arranging for roadside tire service if requested

1 FUELTK

Fuel Tank - Aluminum 50 gallon capacity. Clean CA position. (drivers side mounted)

1 GVWR GVWR - Gross Vehicle Weight Rating - 25,500 lbs.

1 AIRTANK Air Tank - 34 liter tank (9 gallon capacity)

1 BRAKES

Brakes - Hydraulic dual circuit with Antilock Brake System (ABS). Front Brakes: 15.375" diameter x 18.96" x 0.74" thickness: Rear Brakes: 15.375" x 18.96" x 0.74". Drum diameter 12" Meritor.

1 AIRDRYER Air Dryer - Nabtesco heated air dryer.

1 FRAME

Frame - Straight C Channel frame, ladder type, powder coated, 34" wide, yield strength 80,000 PSI, resistance bending moment (RBM) 1,031,900 in./lbs. (one side no reinforcement).

1 WHEELS Wheels - Accuride powder coated 19.5" x 6.75" 8-stud disc.

1 TIRES

Front tires - Bridgestone 245/70R19.5 R250F Rib pattern;

Rear tires - Bridgestone 245/70R19.5 M729F Lug pattern.

1 AXLES

Front Axle - Meritor MFS8, 8,000 lb. capacity, Reverse Elliot "I" beam with oil lubricated hubs.

Rear Axle - Meritor RS17-145, 17,500 lb. capacity full-floating single reduction hypoid gearing.

1 SPRINGS

Front Spring: Tapered leaf springs with shock absorbers, 8,000 lb. rating; Rear Spring: Semi-elliptical main, 19,000 lb. rating.

1 AXLESTD Rear Axle Ratio - Standard 4.11

---



**H-GAC Product Code: E5**  
**258ALP CONV. CAB, SRA**

Model 2016 Hino 258ALP

Transmission Auto - Allison 2500RDS w/Syn Fluids (PTO)

Wheelbase 152.0

**Standard Options**

**Qty Order Code Description**

**1 ENGINE**

Engine - HINO J08E-VB Turbo charged and intercooled with glow plugs, 6 cylinder, In-line water-cooled; Max Output 260hp @2500rpm; Max Torque 660lb.ft. @ 1500rpm; 7.68L displacement, EPA10 Emissions Certified.

1 OIL Oil Capacity - 16.15 quarts

**1 EXHBRAKE**

Exhaust Brake - Driver controlled w/steering column Stalk Switch

**1 FUELFILT**

Fuel Filter - Davco 243 Diesel Pro Heated fuel/water separator. (Diesel Pro 243)

1 ALT Alternator – Delco 12 volt 130 amp Brush Type

1 BATTERY Battery - Two 12 volt parallel connection, 600 CCA x 2

1 STARTER Starter – Denso 12 volt 4.8 kW / 6.4 HP rating

1 RADIO Radio - AM/FM with single CD, two speakers.

**1 AIRCOND**

Air Conditioning - Denso Cab AC System designed specifically for Hino - Refrigerant 134A

**1 DISPLAY**

Meter Cluster - Information display: Instant and trip fuel consumption, Diesel Particulate Reduction System performance/status, maintenance intervals, engine and vehicle diagnostics.

**1 GAUGES**

Gauges - Speedometer mph (km/h), odometer, fuel/DEF gauges, coolant temp gauge, engine tachometer, air pressure gauge.

1 FTGRILL Grille - Chrome plated

1 HORN Horn - Electric Dual Horn

1 HEAT/DEF Heater/Defroster - 18,357 BTU/h

**1 LAMPS**

Lighting - Marker lamps, stop/tail lights, back-up lights, side-flasher lights.

**1 MISC**

Cab Features - Standard: Cruise control, power steering with tilt and telescopic steering column, cup holders, cigarette lighter, coat hook, bag hook, two overhead compartments, two door pockets, sun visors, side mirrors (1 flat, 1 convex) each side.

**1 SEATS**

Seats - Vinyl driver seat adjustable reclining, with AIR suspension and two person passenger bench seat. Three point seatbelt for driver and outer passenger, two point seatbelt for center position.

**Standard Options**

**Qty Order Code Description**

**1 INDICATORS**

Warning Indicators - Oil pressure, brake pressure, coolant level, battery charge, high beam, turn signal, parking brake, engine control system and ABS.

1 EMISS10 Surcharge - EPA10 Emissions.

1 FREIGHT Equalized Freight Charge

1 COOLSYS Cooling Capacity - 6.6 gallon cooling capacity

**1 WARRANTY\_05**

Warranty - Basic Vehicle-24 months unlimited mileage; Engine-36 months unlimited mileage; Engine-60 month Extended Coverage, 250,000 miles (includes injectors, fuel supply pump and turbo); Emission-60 months 100,000

miles; Frame Rails & Cross Members-48 months unlimited mileage; Cab-48 months unlimited mileage; ABS-24-36 months 300,000 miles.

1 HWATCH\_05

Hino Watch Roadside Assistance - 3-year unlimited roadside assistance including lockout, \*out of fuel/DEF, battery jumpstart, information, and warranty towing (2 year coverage). \*Fluids are customer pay responsibility. Tire Service - assist customer in arranging for roadside tire service if requested

1 FUELTK

Fuel Tank - Aluminum 50 gallon capacity. Clean CA position. (drivers side mounted)

1 GVWR GVWR - Gross Vehicle Weight Rating - 25,500 lbs.

1 AIRTANK Air Tank - Two 34 liter tanks (68L total),(15cfm@1250rpm)

1 BRAKES

Brakes - Full air dual circuit "S" cam type, leading and trailing shoes with automatic adjustment and Antilock Brake System (ABS). Front Brakes: 15.0" diameter x 4.0" x 0.73" thickness: Rear Brakes: 16.5" x 7.0" x 0.85".

1 AIRDRYER

Air Dryer - Bendix –AD-IS (Air Dryer Integrated Solution) heated air dryer.

1 FRAME

Frame - Straight C Channel frame, ladder type, powder coated, 34" wide, yield strength 80,000 PSI, resistance bending moment (RBM) 1,031,900 in./lbs. (one side no reinforcement).

1 WHEELS Wheels - Accuride powder coated 19.5" x 7.5" 10-stud disc.

1 TIRES

Front tires - Bridgestone 245/70R19.5 R250F Rib pattern;

Rear tires - Bridgestone 245/70R19.5 M729F Lug pattern.

1 AXLES

Front Axle - Meritor MFS10, 10,000 lb. capacity, Reverse Elliot "I" beam oil lubricated hubs.

Rear Axle - Meritor RS19-145, 19,000 lb. capacity, full-floating single reduction single speed hypoid gearing.

1 SPRINGS

Front Spring: Tapered leaf springs with shock absorbers, 8,000 lb. rating; Rear Spring: Semi-elliptical main, 17,500 lb. rating.

1 AXLESTD Rear Axle Ratio - Standard 4.11

---

**H-GAC Product Code: E6**  
**268 CONV. CAB, SRA**

Model 2016 Hino 268

Transmission Auto - Allison 2200RDS w/Syn Fluids (PTO)

Wheelbase 152.0

**Standard Options**

**Qty Order Code Description**

**1 ENGINE**

Engine - HINOJ08E-VC Turbo charged and intercooled with glow plugs, 6 cylinder, In-line water-cooled; Max Output 220hp @2500rpm; Max Torque 520lb.ft. @ 1500rpm; 7.68L displacement, EPA10 Emissions Certified.

1 OIL Oil Capacity - 16.15 quarts

**1 EXHBRAKE**

Exhaust Brake - Driver controlled w/steering column Stalk Switch

**1 FUELFILT**

Fuel Filter - Davco 243 Diesel Pro Heated fuel/water separator. (Diesel Pro 243)

1 ALT Alternator - Delco 12 volt 130 amp Brush Type

1 BATTERY Battery - Two 12 volt parallel connection, 600 CCA x 2

1 STARTER Starter - Denso 12 volt 4.8 kW / 6.4 HP rating

1 RADIO Radio - AM/FM with single CD, two speakers.

**1 AIRCOND**

Air Conditioning - Denso Cab AC System designed specifically for Hino - Refrigerant 134A

**1 DISPLAY**

Meter Cluster - Information display: Instant and trip fuel consumption, Diesel Particulate Reduction System performance/status, maintenance intervals, engine and vehicle diagnostics.

**1 GAUGES**

Gauges - Speedometer mph (km/h), odometer, fuel/DEF gauges, coolant temp gauge, engine tachometer, air pressure gauge.

1 FTGRILL Grille - Chrome plated

1 HORN Horn - Electric Dual Horn

1 HEAT/DEF Heater/Defroster - 18,357 BTU/h

**1 LAMPS**

Lighting - Marker lamps, stop/tail lights, back-up lights, side-flasher lights.

**1 MISC**

Cab Features - Standard: Cruise control, power steering with tilt and telescopic steering column, cup holders, cigarette lighter, coat hook, bag hook, two overhead compartments, two door pockets, sun visors, side mirrors (1 flat, 1 convex) each side.

**1 SEATS**

Seats - Vinyl driver seat adjustable reclining, with AIR suspension and two person passenger bench seat. Three point seatbelt for driver and outer passenger, two point seatbelt for center position.

**Standard Options**

**Qty Order Code Description**

**1 INDICATORS**

Warning Indicators - Oil pressure, brake pressure, coolant level, battery charge, high beam, turn signal, parking brake, engine control system and ABS.

1 FREIGHT Equalized Freight Charge

1 COOLSYS Cooling Capacity - 6.08 gallon cooling system capacity

**1 WARRANTY\_05**

Warranty - Basic Vehicle-24 months unlimited mileage; Engine-36 months unlimited mileage; Engine-60 month Extended Coverage, 250,000 miles (includes injectors, fuel supply pump and turbo); Emission-60 months 100,000 miles; Frame Rails & Cross Members-48 months unlimited

mileage; Cab-48 months unlimited mileage; ABS-24-36 months 300,000 miles.

1 HWATCH\_05

Hino Watch Roadside Assistance - 3-year unlimited roadside assistance including lockout, \*out of fuel/DEF, battery jumpstart, information, and warranty towing (2 year coverage). \*Fluids are customer pay responsibility. Tire Service - assist customer in arranging for roadside tire service if requested

1 FUELTK

Fuel Tank - Aluminum 50 gallon capacity. Clean CA position. (drivers side mounted)

1 GVWR GVWR - Gross Vehicle Weight Rating - 25,950 lbs.

1 AIRTANK Air Tank - 34 liter tank (9 gallon capacity)

1 BRAKES

Brakes - Hydraulic dual circuit with Antilock Brake System (ABS). Front Brakes: 15.375" diameter x 18.96" x 0.74" thickness: Rear Brakes: 15.375" x 18.96" x 0.74". Drum diameter 12" Meritor for automatic transmission, 9" Bosch for manual transmission.

1 AIRDRYER Air Dryer - Nabtesco heated air dryer.

1 FRAME

Frame - Straight C Channel frame, ladder type, powder coated, 34" wide, yield strength 80,000 PSI, resistance bending moment (RBM) 1,031,900 in./lbs. (one side no reinforcement).

1 WHEELS

Wheels - Accuride powder coated 22.5" x 8.25" 10-stud disc.

1 TIRES

Front tires - Bridgestone 11R 22.5 R268 Rib pattern; Rear tires - Bridgestone 11R 22.5 M726EL Lug pattern.

1 AXLES

Front Axle - Meritor MFS10, 10,000 lb. capacity, Reverse Elliot "I" beam oil lubricated hubs.

Rear Axle - Meritor RS19-145, 19,000 lb. capacity, full-floating single reduction single speed hypoid gearing.

1 SPRINGS

Front Spring: Tapered leaf springs with shock absorbers, 12,000 lb. rating; Rear Spring: Semi-elliptical main, 21,000 lb. rating.

1 AXLESTD Rear Axle Ratio - Standard 5.57

---

**H-GAC Product Code: E7**  
**268A CONV. CAB, SRA**

Model 2016 Hino 268A

Transmission Auto - Allison 2200RDS w/Syn Fluids (PTO)

Wheelbase 152.0

**Standard Options**

**Qty Order Code Description**

**1 ENGINE**

Engine - HINO J08E-VC Turbo charged and intercooled with glow plugs, 6 cylinder, In-line water-cooled; Max Output 220hp @2500rpm; Max Torque 520lb.ft. @ 1500rpm; 7.68L displacement, EPA10 Emissions Certified.

1 OIL Oil Capacity - 16.15 quarts

**1 EXHBRAKE**

Exhaust Brake - Driver controlled w/steering column Stalk Switch

**1 FUELFILT**

Fuel Filter - Davco 243 Diesel Pro Heated fuel/water separator. (Diesel Pro 243)

1 ALT Alternator - Delco 12 volt 130 amp Brush Type

1 BATTERY Battery - Two 12 volt parallel connection, 600 CCA x 2

1 STARTER Starter - Denso 12 volt 4.8 kW / 6.4 HP rating

1 RADIO Radio - AM/FM with single CD, two speakers.

**1 AIRCOND**

Air Conditioning - Denso Cab AC System designed specifically for Hino - Refrigerant 134A

**1 DISPLAY**

Meter Cluster - Information display: Instant and trip fuel consumption, Diesel Particulate Reduction System performance/status, maintenance intervals, engine and vehicle diagnostics.

**1 GAUGES**

Gauges - Speedometer mph (km/h), odometer, fuel/DEF gauges, coolant temp gauge, engine tachometer, air pressure gauge.

1 FTGRILL Grille - Chrome plated

1 HORN Horn - Electric Dual Horn

1 HEAT/DEF Heater/Defroster - 18,357 BTU/h

**1 LAMPS**

Lighting - Marker lamps, stop/tail lights, back-up lights, side-flasher lights.

**1 MISC**

Cab Features - Standard: Cruise control, power steering with tilt and telescopic steering column, cup holders, cigarette lighter, coat hook, bag hook, two overhead compartments, two door pockets, sun visors, side mirrors (1 flat, 1 convex) each side.

**1 SEATS**

Seats - Vinyl driver seat adjustable reclining, with AIR suspension and two person passenger bench seat. Three point seatbelt for driver and outer passenger, two point seatbelt for center position.

**Standard Options**

**Qty Order Code Description**

**1 INDICATORS**

Warning Indicators - Oil pressure, brake pressure, coolant level, battery charge, high beam, turn signal, parking brake, engine control system and ABS.

1 FREIGHT Equalized Freight Charge

1 COOLSYS Cooling Capacity - 6.08 gallon cooling system capacity

**1 WARRANTY\_05**

Warranty - Basic Vehicle-24 months unlimited mileage; Engine-36 months unlimited mileage; Engine-60 month Extended Coverage, 250,000 miles (includes injectors, fuel supply pump and turbo); Emission-60 months 100,000 miles; Frame Rails & Cross Members-48 months unlimited

mileage; Cab-48 months unlimited mileage; ABS-24-36 months 300,000 miles.

1 HWATCH\_05

Hino Watch Roadside Assistance - 3-year unlimited roadside assistance including lockout, \*out of fuel/DEF, battery jumpstart, information, and warranty towing (2 year coverage). \*Fluids are customer pay responsibility. Tire Service - assist customer in arranging for roadside tire service if requested

1 FUELTK

Fuel Tank - Aluminum 50 gallon capacity. Clean CA position. (drivers side mounted)

1 GVWR GVWR - Gross Vehicle Weight Rating - 25,950 lbs.

1 AIRTANK Air Tank - Two 34 liter tanks (68L total),(15cfm@1250rpm)

1 BRAKES

Brakes - Full air dual circuit "S" cam type, leading and trailing shoes with automatic adjustment and Antilock Brake System (ABS). Front Brakes: 15.0" diameter x 4.0" x 0.73" thickness: Rear Brakes: 16.5" x 7.0" x 0.85".

1 AIRDRYER

Air Dryer - Bendix –AD-IS (Air Dryer Integrated Solution) heated air dryer.

1 FRAME

Frame - Straight C Channel frame, ladder type, powder coated, 34" wide, yield strength 80,000 PSI, resistance bending moment (RBM) 1,031,900 in./lbs. (one side no reinforcement).

1 WHEELS

Wheels - Accuride powder coated 22.5" x 8.25" 10-stud disc.

1 TIRES

Front tires - Bridgestone 11R 22.5 R268 Rib pattern; Rear tires - Bridgestone 11R 22.5 M726EL Lug pattern.

1 AXLES

Front Axle - Meritor MFS10, 10,000 lb. capacity, Reverse Elliot "I" beam oil lubricated hubs.

Rear Axle - Meritor RS19-145, 19,000 lb. capacity, full-floating single reduction single speed hypoid gearing.

1 SPRINGS

Front Spring: Tapered leaf springs with shock absorbers, 12,000 lb. rating; Rear Spring: Semi-elliptical main, 21,000 lb. rating.

1 AXLESTD Rear Axle Ratio - Standard 5.57

---

**H-GAC Product Code: E8**  
**338 CONV. CAB, SRA**

Model 2016 Hino 338  
Transmission Auto - Allison 2500RDS w/Syn Fluids (PTO)  
Wheelbase 152.0

**Standard Options**

**Qty Order Code Description**

**1 ENGINE**

Engine - HINO J08E-VB Turbo charged and intercooled with glow plugs, 6 cylinder, In-line water-cooled; Max Output 260hp @2500rpm; Max Torque 660lb.ft. @ 1500rpm; 7.68L displacement, EPA10 Emissions Certified.

1 OIL Oil Capacity - 16.15 quarts

**1 EXHBRAKE**

Exhaust Brake - Driver controlled w/steering column Stalk Switch

**1 FUELFILT**

Fuel Filter - Davco 243 Diesel Pro Heated fuel/water separator. (Diesel Pro 243)

1 ALT Alternator - Delco 12 volt 130 amp Brush Type

1 BATTERY Battery - Two 12 volt parallel connection, 600 CCA x 2

1 STARTER Starter - Denso 12 volt 4.8 kW / 6.4 HP rating

1 RADIO Radio - AM/FM with single CD, two speakers.

**1 AIRCOND**

Air Conditioning - Denso Cab AC System designed specifically for Hino - Refrigerant 134A

**1 DISPLAY**

Meter Cluster - Information display: Instant and trip fuel consumption, Diesel Particulate Reduction System performance/status, maintenance intervals, engine and vehicle diagnostics.

**1 GAUGES**

Gauges - Speedometer mph (km/h), odometer, fuel/DEF gauges, coolant temp gauge, engine tachometer, air pressure gauge.

1 FTGRILL Grille - Chrome plated

1 HORN Horn - Electric Dual Horn

1 HEAT/DEF Heater/Defroster - 18,357 BTU/h

**1 LAMPS**

Lighting - Marker lamps, stop/tail lights, back-up lights, side-flasher lights.

**1 MISC**

Cab Features - Standard: Cruise control, power steering with tilt and telescopic steering column, cup holders, cigarette lighter, coat hook, bag hook, two overhead compartments, two door pockets, sun visors, side mirrors (1 flat, 1 convex) each side.

**1 SEATS**

Seats - Vinyl driver seat adjustable reclining, with AIR suspension and two person passenger bench seat. Three point seatbelt for driver and outer passenger, two point seatbelt for center position.

**Standard Options**

**Qty Order Code Description**

**1 INDICATORS**

Warning Indicators - Oil pressure, brake pressure, coolant level, battery charge, high beam, turn signal, parking brake, engine control system and ABS.

1 FREIGHT Equalized Freight Charge

1 COOLSYS Cooling Capacity - 6.08 gallon cooling system capacity

**1 WARRANTY\_05**

Warranty - Basic Vehicle-24 months unlimited mileage; Engine-36 months unlimited mileage; Engine-60 month Extended Coverage, 250,000 miles (includes injectors, fuel supply pump and turbo); Emission-60 months 100,000 miles; Frame Rails & Cross Members-48 months unlimited

mileage; Cab-48 months unlimited mileage; ABS-24-36 months 300,000 miles.

1 HWATCH\_05

Hino Watch Roadside Assistance - 3-year unlimited roadside assistance including lockout, \*out of fuel/DEF, battery jumpstart, information, and warranty towing (2 year coverage). \*Fluids are customer pay responsibility. Tire Service - assist customer in arranging for roadside tire service if requested

1 FUELTK

Fuel Tank - Aluminum 50 gallon capacity. Clean CA position. (drivers side mounted)

1 GVWR GVWR - Gross Vehicle Weight Rating - 33,000 lbs.

1 AIRTANK Air Tank - Two 34 liter tanks (68L total),(15cfm@1250rpm)

1 BRAKES

Brakes - Full air dual circuit "S" cam type, leading and trailing shoes with automatic adjustment and Antilock Brake System (ABS). Front Brakes: 15.0" diameter x 4.0" x 0.73" thickness: Rear Brakes: 16.5" x 7.0" x 0.85".

1 AIRDRYER

Air Dryer - Bendix –AD-IS (Air Dryer Integrated Solution) heated air dryer.

1 FRAME

Frame - Straight C Channel frame, ladder type, powder coated, 34" wide, yield strength 80,000 PSI, resistance bending moment (RBM) 1,280,800 in./lbs. (one side no reinforcement).

1 WHEELS

Wheels - Accuride powder coated 22.5" x 8.25" 10-stud disc.

1 TIRES

Front tires - Bridgestone 11R 22.5 R268 Rib pattern; Rear tires - Bridgestone 11R 22.5 M726EL Lug pattern.

1 AXLES

Front Axle - Meritor MFS12, 12,000 lb. capacity, Reverse Elliot "I" beam with oil lubricated hubs.

Rear Axle - Meritor RS21-145, 21,000 lb. capacity, full-floating single reduction hypoid gearing.

1 SPRINGS

Front Spring: Tapered leaf springs with shock absorbers, 12,000 lb. rating; Rear Spring: Semi-elliptical main, 21,000 lb. rating.

1 AXLESTD Rear Axle Ratio - Standard 5.57

---