



***FORTBRAND***  
QUALITY • TRUST • RELIABILITY

# Fortbrand Services LLC

## 2025 Retail Price List

Prices effective December 1, 2024

Prices subject to change without notice

All Vammis items FOB Ottumwa, IA.

All Wille items FOB Ottawa, ON, CA

Freight and brokerage quotes for delivery available on request

## VAMMAS B750 Snow Blower

### Item #B750

The Vammas B750 is the largest capacity snow blower. Designed by Fresia, it is the flagship of the Vammas snow blower product line.

At 7,500 tons per hour capacity, the advanced design of the Vammas two stage blower head supports various types of snow casting.

The B750 offers a heavy duty built chassis for this specific application. The cab forward design offers the best visibility possible and it's three engine's support the blowers high speed and capacity.

The high capacity, two stage blower head is designed to effectively move snow through the blower head at high speed.



#### Cab

- High Visibility
- Comfortable Seating

#### Blower Unit

- Cutter Diameter: 56"
- Impeller DIiameter: 71"
- Clearing Width: 118"

#### Performance

- Clearing Capacity: 7500 tph
- Casting Distance: 150'

#### Steering

- Four Wheel Steering Standard

#### Suspension

- Leaf Springs Front and Rear

#### Fuel Tank

- 250/500 Gallon Capacity

### Three Engine Design

**Drive Engine** – The engine is a Volvo TAD1375VE four-stroke diesel type, six (6) cylinder, 12.78 -liter, developing a minimum of (405kW) 551 horsepower at 1900 RPM, and equipped with the latest diesel electronic control and engine management system. Engine emission is level is Tier IV final.

**Auxiliary Engine** – The blower engines are Twin-Volvo TAD 1375VE four-stroke diesel type, each with six (6) cylinders, 12.8L – liter, developing a total of (810kW) 1100HP horsepower at 1900RPM and are equipped with the latest diesel electronic cont

**Transmission** – The vehicle is driven by an Allison automatic transmission 4000 (6 speed +1 reverse) with torque converter.

**Base Model MSRP: \$1,563,557**



## VAMMAS B750d Snow Blower

### Item #B750d

The Vammas B750d is the latest addition to the Vammas family of snow fighting machines.

At 7,500 tons per hour capacity, the advanced design of the Vammas two stage blower head supports various types of snow casting.

The B750d offers a heavy duty built chassis for this specific application. The cab forward design offers the best visibility possible and it's dual engine support the blowers high speed and capacity.

The high capacity, two stage blower head is designed to effectively move snow through the blower head at high speed.



### Cab

- High Visibility
- Comfortable Seating

### Blower Unit

- Cutter Diameter: 55"
- Impeller Diameter: 55"
- Clearing Width: 98"

### Performance

- Clearing Capacity: 7500 tph
- Casting Distance: 150'

### Steering

- Four Wheel Steering Standard

### Suspension

- Leaf Springs Front and Rear

### Fuel Tank

- 260 Gallon Capacity

### Three Engine Design

**Drive Engine** – The engine is a Volvo Penta Tier 4 Final Stage V

**Auxiliary Engine** – The blower engine is a Volvo Penta Tier 4 Final Stage V- 585kW (approx. 785 hp)

**Transmission** – The vehicle is driven by an Allison 4000 automatic transmission with Auto-locking transfer reducer

**Base Model MSRP: \$ 995,557**



## VAMMAS ST/SB 5500

### Item #ST/SB5500

The Vammas ST (Snow Tractor) / SB (Sweeper Blower) 5500 offer the highest capacity in a modular multi-tasking design for use at North American and European airports. Vammas ST/SB units are manufactured in Ottumwa Iowa to the highest standards of quality for operator ergonomics, safety and reliability.

The superior ergonomics for the ST include 360 degree visibility, single joystick operation with air ride and heated seat providing optimum operator comfort for the demanding work required.



The Vammas operating system is fully automatic, initiating all systems based on the operator's selection within 8 seconds. The Aggregate engine will increase or decrease based purely on the joystick selection, saving fuel during operations.

The Vammas ST has 4x4 traction and with seamless rear SB steering, to effectively maneuver on airport taxiways, aprons and runways. With the capability of consistently operating at 37MPH (60 KM/H), the ST/SB 5500 minimizes runway occupancy times keeping your airfield operational.

#### Snow Tractor

- Unmatched Ergonomics
- Cab Forward Design
- Volvo Tier 4 Final Engine
- Allison Transmission
- Quick Disconnect Plow

#### Tow Behind Sweeper

- One Joystick Control
- Volvo Tier 4 Final Engine
- One Operator
- Rear Steering

#### Plow

The quick disconnect plow system with an innovative 30ft self-adjusting polyethylene flexible moldboard plow is provided. Including independent spring-loaded cutting edge segments placed at 45 degrees to maintain maximum production and contact area when operating over in pavement lights.

#### Broom

The 22ft, 46 inch diameter wafer system provides increased performance and flexibility to use steel or polypropylene wafers. Two large 17.5in broom castor wheels are designed specifically for high-speed applications. The broom can be placed in the transport position, allowing for easy storage in any maintenance facility. Plus the ST/SB can be separated to support even smaller storage requirements.

#### Blower

The large air blast at the rear of the unit is deployed and retracted as selected by the operator to remove any remnants from the surface.

**Base Model MSRP: \$1,269,910.**





ITEM #	VAMMAS ST/SB 5500 OPTIONS	PRICE
70101020 1	P8400 Plow	\$69,300
70101020 1	Steel broom wafers	\$7,672
70101020 1	Broom Core	\$45,134
70101020 1	Broom dolly	\$9,188
70101020 1	Broom Vibrator	\$6,370.00
70101020 1	Auto Lube	\$45,350.00
70101020 1	Tires (Michelin)	\$13,023.00
70101020 1	Upgraded wiper system	\$25,765.00
70101020 1	back-up camara	\$2,156.00

## VAMMAS PSB 5500

### Item #PSB5500

The Vammas 3-in-1 Plow Sweeper Blower 5500 offers a high capacity, multi-tasking design that is well established at North American and European airports.

All Vammas PSB units are manufactured to the highest standards of quality for operator ergonomics, safety and reliability. The superior ergonomics include 360 degree visibility, single joystick operation, air ride suspension and heated seats and windows, providing optimum operator comfort for the demanding work required.



Vammas PSB 5500 units have combined front wheel and rear articulated steering, to effectively maneuver on airport taxiways, aprons and runways. With the capability of operating at 37MPH (60 KM/H), the PSB 5500 minimizes runway occupancy times and keeps your airfield open longer.

### PSB Advanced Technological Design

- Plow provides a segmented cutting edge design with a flexible moldboard that maintain cutting edge surface contact in various surface and snow conditions
- Dense 46 inch wafer broom for increased performance with automatic broom pattern and speed adjustments
- Powerful air blower to remove remnants as well as snow from edge lights
- Ergonomically designed 'control tower' cab, with operator in the center to have excellent, allaround visibility
- All PSB functions are integrated into the Vammas CAN system which monitor and report any operating concerns to the operator

### Plow

Innovative 30ft self-adjusting, polyethylene moldboard plow, with independent spring-loaded cutting edge segments to maintain maximum contact area. The largest plow in the industry!

### Broom

22ft, 46 inch diameter wafer system provides increased performance and flexibility to use steel or polypropylene wafers. Large broom castor wheels are designed specifically for high-speed applications. The broom can be stowed in the transport position, allowing for easy storage in any maintenance facility.

### Blower

Air blast at the rear of the unit removes any remaining snow remnants from the surface.

**Base Model MSRP: \$1,595,641**





ITEM #	VAMMAS PSB 5500 OPTIONS	PRICE
70101020 1	P8400 Plow	\$69,300
70101020 1	Steel broom wafers	\$7,672
70101020 1	Broom Core	\$45,134
70101020 1	Broom dolly	\$9,188
70101020 1	Broom Vibrator	\$6,370.00
70101020 1	Auto Lube	\$45,350.00
70101020 1	Tires (Michelin)	\$13,023.00
70101020 1	Upgraded wiper system	\$25,765.00
70101020 1	back-up camara	\$2,156.00



# WILLE 275 Δ

## Item # 275 “D”

Kohler KDI1903TCR, Tier 4 Final (56 HP) 3-cylinder turbo diesel engine

Block heater

Hydrostatic transmission with variable displacement pump and 2 speed motor

1 speed reduction gear

Auto-load sensing hydraulic drive system

Electronic inching pedal

Electronic stepless hand throttle

Differential lock on/off activated from joystick

Hand operated, mechanical parking brake

Hydraulically assisted drum brake on driveline acting on all wheels

Heated side mirrors

Front and rear fenders

High pressure water hose through center section

Reverse alarm

Tires:

- 265/70R16 tires, machine width 1330mm (52.5")

Automatic driving lights

Front (4) and rear (4) LED work lights

High Power LED Beacon light with foldable arm (specify blue or amber)

ROPS (ISO 3471) and FOPS (ISO 3449 1365 J approved) cab

Hydrostatic articulated steering

Cab heater with variable fan speed control

Cab filter

Air conditioning

Smart Cruiser

Smart Flow

Smart Drive

Radio/mp3 Bluetooth/AUX-in/USB/SD-Card

Air ride heated seat with safety belt (2 point)

Tilt steering

Rear window wiper and washer

Manual hydraulic oil fill pump

Tow hitch

Over engine attachment brackets

Electrically adjustable valve drive hydraulics- 0-55L/min (14.5gpm) to front and rear

3rd cylinder front hydraulics, hydraulic pilot control

4th cylinder front hydraulics, hydraulic pilot control

Drive hydraulics (max flow at 2600 rpm):

- Front or Rear single acting – 0-55L/min (0-14.5gpm)
- Front single acting – 35L/min (9.2gpm)
- Front or Rear single acting – 20L/min (5.3gpm)
- Front or Rear single acting – 0-55L+35L/min (23.7gpm)
- Front single acting – 0-55L+20L/min (19.8gpm)
- Front or Rear single acting – 35L+20L/min (14.5gpm)
- Front or Rear single acting – 0-55L+35L+20L/min (29gpm)
- Combined Front 20L + 35L/min (14.5gpm) and Rear - 0-55L/min (0-14.5gpm)

Front lift:

- Category 1, 3-point hitch
- Hydraulic pilot control
- Ride control
- Mechanical attachment lock
- Float position



**Base Model MSRP: \$168,940**



WILLE NORTH AMERICA INC.

ITEM #	WILLE 275 Δ OPTIONS	PRICE
14020114/A	Hydraulic top link <ul style="list-style-type: none"> <li>Increases versatility of front lift</li> </ul>	\$530
923100238	Smart Lube Central automatic pressure lubrication <ul style="list-style-type: none"> <li>1.5L (1.6qt)</li> <li>Includes 5 year warranty (to a maximum of 5,000 hours) against defects in materials or workmanship on the complete center articulation section subject to the usual warranty terms &amp; conditions and all required maintenance being completed as described in the User Handbook service guidelines</li> </ul>	\$6,280
70101020	Filling pump for auto lube	\$730
14120107/K	Hydraulic tank heater	\$1,010
14020106	Auxiliary Cab Heater	\$430
923100199	Flashing LED light in cab corners <ul style="list-style-type: none"> <li>4 front, 4 rear</li> </ul>	\$ 2,070
13600110	Back up camera <ul style="list-style-type: none"> <li>RW-710151 with 7" color screen</li> <li>3 channel system with 1 camera</li> </ul>	\$2,070
42900103/1	Left side arm rest	\$355
13721032	Rear counterweight – 240kg (529lbs)	\$3,370
52050516	Turf tires <ul style="list-style-type: none"> <li>Set of 4 with rims</li> <li>31x15.5-15</li> </ul>	\$7,160
	Custom paint. Replaces yellow paint only.	\$2,750



ITEM #	WILLE 275 Δ ATTACHMENTS	PRICE
13000550	High-tipping bucket 550L (0.72cu yd) capacity – width 1580mm (62”), dump height of 813mm (32”)	\$8,140
A/SB200060	Horst 1524mm (60”) snow blade - crossover relief valve, lateral float, 610mm (24”) moldboard profile, replaceable and reversible cutting edge, skid shoe and spring trip cutting edge, 1524mm (60”) wide, angled snow clearing width 1245mm (49”)	\$6,950
VB55	WNAI VB55 Folding V plow 1400mm (55”) hydraulic wings angle change 30deg, relief valve protection, cutting edge with carbide inserts, trip spring protection, hardened steel skid shoes adjustable and replaceable, hydraulic hoses and case drain	\$10,820
15624	Tokvam F130H ribbon snow blower – clearing width 1300mm (51”), 495mm (19.5”) ribbon diameter, hydraulic drive, center-mounted differential, standard chute with hydraulic chute rotation and deflection, comes with 3- point hitch adapter with slotted oscillation mount and drift cutters	\$21,170
18399L/18398R	End plate for Tokvam ribbon snow blower. Specify left or right	\$1,230
23649	Wear plate for Tokvam skid shoe (each per item- order 2)	\$195
ST130	WNAI ST130 high capacity HD ribbon snow blower: clearing width 1300mm (51”), cutting height of 910mm (36”), hydraulic drive, center-mounted differential, standard chute with hydraulic chute rotation and double flap deflector	\$30,730
ST130CE	Chute extension for ST130, 1220mm (48”)	\$1,880
ST8253	ST130 Side protection kit	\$425
13150180	Galvanized drop spreader (self-loading) 250L (0.33cu yd) capacity – working width 1100mm (43”). Specify material- sand or salt.	\$9,285
13730181	Mechanical rear blade 1801 – working width 1690mm (66.5”), 20° fixed angle, 4° oscillation. <b>Rear hydraulic tilting hitch required</b> <b>LIMITED QUANTITIES AVAILABLE FOR 265/275 MODELS</b>	\$4,230
A/HF1300	GMR sweeper – width 1300mm (51”), 26° hydraulic angle, 600 mm (24”) brush diameter ***in stock demo units (subject to prior sale) available at a special retail of \$ 6,900***	\$11,980
13122140-1	Rotary brush 140 – width 1400mm (55”), 26° hydraulic angle left & right, 700 mm (27.5”) brush diameter, 220mm (8.6”) side shift left, 265mm (10.4”) side shift right	\$18,325
13122121	Water tank for rotary brush 140 (boom mounted), 150L (40gal), 10L/min (2.6gpm), 29psi. For use with 13122140	\$1,975



ITEM #	Wille 275 Δ Attachments	PRICE
13133205	Collecting sweeper 205 with side brush (right)– hopper capacity of 200L (0.26cu yd), water tank capacity of 100L (26.5gal), working width 1400mm (55”), 610mm (24”) brush diameter, hydraulic bottom dump. <b>Counterweight required</b>	\$21,420
13133206	Additional side brush assembly (left) for Collecting Sweeper 205 – increases overall working width by 300mm (12”) to 1700mm (67”)	\$3,430
13140560/KPA 921200108	High pressure baffled water tank 550L (145gal) capacity – mounted over engine, max flow 30L/min (8gpm), max pressure 145Bar (2100psi), support legs included, includes required 240kg (529lbs) front counterweight, hand held hose 15m (49’), and front mount nozzle pipe 1240 – min working width 1240mm (49”), 25° hydraulic angle left & right	\$27,490
A/FMWT001	Non baffled cylindrical water tank: 450L (120gal), over engine mount, electric water pump	\$5,990
13140560-1	Baffled water tank 550L (145gal), electric pump 10L/min (2.6gpm), 2bar (29psi), mounted over engine. Additional options: <ul style="list-style-type: none"> <li>• Legs \$1,895</li> <li>• Lights \$560</li> </ul>	\$11,050
14127500	Fixed platform 230L (0.3cu yd) capacity	\$3,450
A/104238	TOP HYD tilting dump body 250L (0.33cu yd)	\$7,825
A/131612503PH	GMR TH2500C triplex rotary mower: cutting width 2480mm (98”), mower width 2530mm (100”), transport width 1750mm (69”), adjustable height 30-80mm (1”-3”), hydraulic tilt, independent adjustable (hydraulic) wings cut 10° below level, cut 15° above level, and vertical tip, front mounting, 5 blades. <b>Turf tires recommended</b>	\$43,755
FM180	WNAI FM180 industrial flail mower: working width 1790mm (70.5”), cutting height 38mm-140mm (1.5”-5.5”) in 1” increments, hydraulic driven, floatation, 7 degree lateral tilt (left and right), choice of knives with forward rotation (34 scoop, 68 HD Y or 34 hammer knives), skid shoe. <b>Turf tires recommended</b>	\$16,400
RM1800	WNAI RM1800 rotary mower, working width 1829mm (72”), hydraulic tilt for cleaning and safety interlock. <b>Turf tires recommended</b>	\$15,670
A/7434977BT	Bomford 3.4 Robin front mounted boom flail mower, 3400mm (134”) boom reach, 1000mm (39”) flail head, with electric arm floatation. <b>Counterweight &amp; turf tires required</b>	\$42,195
14190200 92120010	Leaf collector 900L (1.2cu yd) capacity – tipping height 1850mm (73”), c/w suction hose and supporting legs, front mount suction nozzle with brush	\$44,750
14190060	Blower with pipe for leaf collector 25deg left/right mounted on loader	\$2,975



WILLE NORTH AMERICA INC.

ITEM #	WILLE 275 Δ ATTACHMENTS	PRICE
A/BTHYSS3HS3P	Buffalo Turbine hydraulic debris blower – high speed	\$27,450
A/LA-BOQF10H3PHC12	HD universal skid steer adapter plate	\$3,735



# WILLE 375 Δ

## Item # 921100149

Kohler KDI1903TCR, Tier 4 Final (56 HP) 3-cylinder turbo diesel engine

Block heater

Hydrostatic transmission with variable displacement pump and motor

1 speed reduction gear

Auto-load sensing hydraulic drive system

Electronic inching pedal

Electronic stepless hand throttle

Automatic differential lock on front axle

Electric/hydraulic engaged parking brake

Front axle servo operated multi disc brakes in oil bath

Heated side mirrors

Front and rear fenders

High pressure water hose through center section

Reverse alarm

31x11.5-15, machine width 1420mm (56")

Automatic driving lights

Front (4) and rear (4) LED work lights

High Power LED Beacon light with in cab foldable arm (specify blue or amber)

ROPS (ISO 3471) and FOPS (ISO 3449 1355 J approved) cab

Hydrostatic articulated steering

Electrical main switch

Parking brake interlock safety system

Cab heater with variable fan speed control

Cab filter

Air conditioning

Radio/mp3 Bluetooth/AUX-in/USB/SD-Card

Air ride heated seat with headrest and safety belt (3 point)

Smart Cruiser, Smart Flow, Smart Drive

Tilt steering

Roof window

Rear window wiper and washer

Manual hydraulic oil fill pump

Tow hitch

Over engine attachment brackets

Electrically adjustable valve drive hydraulics- 0-55L/min (14.5gpm) to front and rear

3rd cylinder front hydraulics, on/off electric valve

4th cylinder front hydraulics, on/off electric valve



Drive hydraulics (max flow at 2600rpm):

- Front double acting – 0-55L/min (0-14.5gpm)
- Front single acting – 35L/min (9.2gpm)
- Front single acting – 35L + 0-55L/min (23.7gpm)
- Front single acting – 20L + 35L + 0-55L/min (29gpm)
- Rear single acting – 20L/min (5.3gpm)
- Rear single acting – 20L + 0-55L/min (19.8gpm)
- Rear single acting – 20L + 35L + 0-55L/min (29gpm)
- Rear single acting – 0-55L/min (0-14.5gpm)
- Combined Front 20L + 35L/min (14.5gpm) and Rear - 0-55L/min (0-14.5gpm)

Rear, double acting, hydraulic cylinder couplers

Loader:

- Hydraulic self leveling Kunta 500 coupler
- Loader arm support for servicing
- Loader arm support for plowing
- Pilot pressure operated joystick
- Ride control
- Hydraulic attachment lock

**Base Model MSRP: \$187,940**



WILLE NORTH AMERICA INC.

ITEM #	WILLE 375 Δ OPTIONS	PRICE
922100234 923100172	Rear hydraulic tilting hitch (Kunta) <ul style="list-style-type: none"> <li>Includes rear cylinder hydraulics and rear float</li> </ul>	\$5,595
14120200	Smart Lube Central automatic pressure lubrication <ul style="list-style-type: none"> <li>1.5L (1.6qt)</li> <li>Includes 5 year warranty (to a maximum of 5,000 hours) against defects in materials or workmanship on the complete center articulation section subject to the usual warranty terms &amp; conditions and all required maintenance being completed as described in the User Handbook service guidelines</li> </ul>	\$8,050
70101020	Filling pump for auto lube	\$730
14120107/K	Hydraulic tank heater	\$1,010
923100175	Flashing LED light in cab corners <ul style="list-style-type: none"> <li>4 front, 4 rear</li> </ul>	\$ 2,070
923100185	Auxiliary hydraulic oil cooler (VT 50)	\$2,335
13500106	Back up camera <ul style="list-style-type: none"> <li>RW-710151 with 7" color screen</li> <li>3 channel system with 1 camera</li> </ul>	\$2,070
42900103/1	Left side arm rest	\$355
13721032	Rear counterweight - 240kg/528lbs <ul style="list-style-type: none"> <li>Must specify with or without rear hitch</li> </ul>	\$3,180
913000602	Turf tires <ul style="list-style-type: none"> <li>Set of 4 with rims</li> <li>400/50-15</li> </ul>	\$7,160
	Custom paint. Replaces yellow paint only.	\$2,750



WILLE NORTH AMERICA INC.

ITEM #	WILLE 375 Δ ATTACHMENTS	PRICE
13010400	Bucket 400L (0.52cu yd) capacity - working width 1445mm (57"). <b>Counterweight recommended</b>	\$2,810
13020800	Snow bucket 800L (1.05cu yd) capacity - working width 1550mm (61") comes with replaceable bolt on cutting edge. <b>Counterweight recommended</b>	\$4,050
13000550	High-tipping bucket 550L (0.72cu yd) capacity - width 1580mm (62"), tipping height 3130mm (123") dump height 3130mm (123"). <b>Counterweight recommended</b>	\$8,140
12960800-1	Multi-function bucket 750L (0.98cu yd) capacity - working width 1720mm (68") to 2685mm (106") comes with replaceable cross hatch cutting edge. <b>Counterweight recommended</b>	\$12,450
14903	Tokvam F150H ribbon snow blower – clearing width 1500mm (59"), hydraulic drive, center-mounted differential, standard chute with hydraulic chute rotation and deflection, Kunta 500 coupler mount, 500mm (20") diameter auger, 420mm (16.5") diameter impeller, drift cutters and adjustable skid shoes	\$21,770
18399L/18398R	End plate for Tokvam ribbon snow blower. Specify left or right	\$1,760
23649	Wear plate for Tokvam skid shoe (each per item- order 2)	\$1,230
ST150	WNAI ST150 high capacity HD ribbon snow blower: clearing width 1500mm (59"), cutting height of 910mm (36"), hydraulic drive, center- mounted differential, standard chute with hydraulic chute rotation and double flap deflector	\$32,920
ST150CE	Chute extension for ST150, 1220mm (48")	\$1,485
ST8253	ST150 Side protection kit	\$385
VB55/K	WNAI VB55 Folding V plow 1400mm (55") Kunta - hydraulic wings angle change 30deg, relief valve protection, cutting edge with carbide inserts, trip spring protection, hardened steel skid shoes adjustable and replaceable, hydraulic hoses and case drain	\$12,950
A/SB300006	Horst 6' snow blade 1829mm (72"), crossover relief valve, lateral float, 762mm (30") moldboard profile, replaceable and reversible cutting edge, skid shoe and spring trip cutting edge, 1829mm (72") wide, angled snow clearing width 1499mm (59")	\$6,950
A/TOP6113SA	SERCO TOP 6113SA expandable plow, 1300mm-2100mm (51"-82") expandable width, 600mm (23.6") wing height, hydraulic left/right swivel angle +/- 30°, manual fold up end plates with floating blades	\$18,890
13150250/CK	Galvanized drop spreader (self-loading) 250L (0.33cu yd) capacity – working width 1100mm (43"). Specify material- sand or salt. <b>Rear hydraulic tilting hitch required</b>	\$9,285



WILLE NORTH AMERICA INC.

ITEM #	WILLE 375 Δ ATTACHMENTS	PRICE
13122170-1	Rotary brush 170 – working width: 1515mm (60”) to 1700mm (67”), 26° hydraulic angle left & right, 700mm (27.5”) brush diameter	\$15,470
13133205	Collecting sweeper 205 with side brush (right)– hopper capacity of 200L (0.26cu yd), water tank capacity of 100L (26.5gal), working width 1400mm (55”), 610mm (24”) brush diameter, hydraulic bottom dump. Counterweight required	\$21,420
13133206	Additional side brush assembly (left) for Collecting Sweeper 205 – increases overall working width by 300mm (12”) to 1700mm (67”)	\$3,430
13140560	High pressure baffled water tank 550L (145gal) capacity – mounted over engine, max flow 30L/min (8gpm), max pressure 145Bar (2100psi), support legs included, includes required 240kg (529lbs) front counterweight, hand held hose 15m (49’), and front mount nozzle pipe 1240 – min working width 1240mm (49”), 25° hydraulic angle left & right	\$27,990
A/FMWT001	Non-baffled cylindrical water tank: 450L (120gal), over engine mount, electric water pump	\$8,990
13140560-1	Baffled water tank 550L (145gal), electric pump 10L/min (2.6gpm), 2bar (29psi), mounted over engine. Additional options: <ul style="list-style-type: none"> <li>• Legs \$1,895</li> <li>• Lights \$560</li> </ul>	\$11,080
14127500	Fixed platform 230L (0.3cu yd) capacity	\$3,450
FM180/C	WNAI FM180 industrial flail mower: working width 1790mm (70.5”), cutting height 38mm-140mm (1.5”-5.5”) in 1” increments, hydraulic driven, floatation, 7-degree lateral tilt (left and right), choice of knives with forward rotation (34 scoop, 68 HD Y or 34 hammer knives), skid shoe. <b>Hydraulic oil cooler required. Turf tires recommended</b>	\$19,240
RM1800/C	WNAI RM1800 rotary mower, working width 1825mm (72”), hydraulic tilt for cleaning and safety interlock. Hydraulic oil cooler required. <b>Turf tires recommended</b>	\$17,680
A/13161250QC	GMR TH2500C triplex rotary mower: cutting width 2480mm (98”), mower width 2530mm (100”), transport width 1750mm (69”), adjustable height 30-80mm (1”-3”), hydraulic tilt, independent adjustable (hydraulic) wings cut 10° below level, cut 15° above level, and vertical tip, front mounting, 5 blades. <b>Hydraulic oil cooler required. Turf tires recommended</b>	\$42,370
A/13161300QC	GMR TH3000C triplex rotary mower: cutting width 2900mm (114”), mower width 2975mm (117”), transport width 2000mm (79”), adjustable height 30-80mm (1”-3”), hydraulic tilt, independent adjustable (hydraulic) wings cut 10° below center, cut 15° above center, and vertical tip, front mounting, 5 blades. <b>Hydraulic oil cooler required. Turf tires recommended</b>	\$46,160



WILLE NORTH AMERICA INC.

ITEM #	WILLE 375 Δ ATTACHMENTS	PRICE
14190200 14190100-2	Leaf collector 900L (1.2cu yd) capacity - tipping height 1850mm (73”), suction hose and support legs included, suction nozzle with brush	\$44,750
14190060	Blower unit with pipe for leaf collector – 25° hydraulic angle left & right, mounted on loader	\$2,975
A/7443977BT	Bomford 4.3 Robin front mounted boom flail mower, 4300mm (169.3”) boom reach, 1000mm (39”) flail head, with electric arm floatation. <b>Counterweight, turf tires and hydraulic oil cooler required</b>	\$44,460
13062500	Pallet forks 120 – 2500kg (5500lbs), 1200mm (48”) length, adjustable width: 200mm (8”) to 1200mm (48”). <b>Counterweight recommended</b>	\$4,220
14509100	Wille 9 Access platform (includes machine wiring and plug kit) <b>Rear tilt required</b>	\$61,360
A/LA- BOQF10HWIKU500	Wille skid steer adapter plate, mechanical locking	\$3,735



# WILLE 475 Δ

## Item # 921100140

Kohler KDI2504TCR, Stage V (75.4 HP) 4-cylinder turbo diesel engine  
 Block heater  
 Hydrostatic transmission with variable displacement pump and motor  
 1 speed reduction gear  
 Auto-load sensing hydraulic drive system  
 Electronic inching pedal  
 Automatic differential lock on front axle  
 Electric/hydraulic engaged parking brake  
 Front axle servo operated multi disc brakes in oil bath  
 Heated side mirrors  
 Front and rear fenders  
 High pressure water hose through center section  
 Reverse alarm  
 305x70-16 tires  
 Automatic driving lights  
 Front (4) and rear (4) LED work lights  
 High Power LED Beacon light with in cab foldable arm (specify blue or amber)  
 ROPS (ISO 3471) and FOPS (ISO 3449 1355 J approved) cab  
 Hydrostatic articulated steering  
 Electrical main switch  
 Parking brake interlock safety system  
 Cab heater with variable fan speed control  
 Cab filter  
 Air conditioning- automatic  
 Smart Cruiser  
 Smart Flow  
 Smart Drive



Radio/mp3 Bluetooth/AUX-in/USB/SD-Card  
 Air ride heated seat with headrest and safety belt (3 point)  
 Tilt steering  
 Roof window  
 Rear window wiper and washer  
 Manual hydraulic oil fill pump  
 Tow hitch  
 Over engine attachment brackets  
 Electric regulating flow valve for drive hydraulics – regulates 80 L/min (21.1 gpm) pump  
 3rd cylinder front hydraulics, Proportional 0-52 L/min (0-13.7 gpm)  
 4th cylinder front hydraulics, Proportional 0-52 L/min (0-13.7 gpm)  
 Drive hydraulics (max flow at 2300 rpm):

- Front double acting – 0-80 L/min (0-21.1gpm)
- Front single acting – 52 L/min (13.7 gpm)
- Front single acting – 52L + 0-80 L/min (34.9gpm)
- Rear single acting – 52 L/min (13.7gpm)
- Rear single acting - 0-80 L/min (0-21.1gpm)
- Rear single acting – 52L + 0-80L/min (34.9gpm)

Rear, double acting, hydraulic cylinder couplers  
 Loader:

- Hydraulic self leveling Kunta 500 coupler
- Loader arm support for servicing
- Loader arm support for plowing
- Pilot pressure operated joystick
- Ride control
- Hydraulic attachment lock

**Base Model MSRP: \$224,980**



WILLE NORTH AMERICA INC.

ITEM #	WILLE 475 Δ OPTIONS	PRICE
14438000 14447800	Rear hydraulic tilting hitch (Kunta) <ul style="list-style-type: none"> <li>Includes rear cylinder hydraulics and rear float</li> </ul>	\$6,330
923100170	Smart Lube Central automatic pressure lubrication <ul style="list-style-type: none"> <li>1.5L (1.6qt)</li> <li>Includes 5 year warranty (to a maximum of 5,000 hours) against defects in materials or workmanship on the complete center articulation section subject to the usual warranty terms &amp; conditions and all required maintenance being completed as described in the User Handbook service guidelines</li> </ul>	\$7,975
70101020	Filling pump for auto lube	\$730
14440107	Hydraulic tank heater	\$1,010
14445100	Auxiliary hydraulic oil cooler (VT 50)	\$2,335
923100126	Flashing LED light in cab corners <ul style="list-style-type: none"> <li>4 front, 4 rear</li> </ul>	\$2,070
13500106	Back up camera <ul style="list-style-type: none"> <li>RW-710151 with 7" color screen</li> <li>3 channel system with 1 camera</li> </ul>	\$2,070
42900103/1	Left side arm rest	\$355
13721033	Rear counterweight – 300kg/661lbs <ul style="list-style-type: none"> <li>Specify if equipped with or without rear hitch)</li> </ul>	\$3,785
52050519	Turf tire <ul style="list-style-type: none"> <li>Set of 4 with rims</li> <li>380/60 R15</li> </ul>	\$8,385
	Custom paint. Replaces yellow paint only.	\$2,750



WILLE NORTH AMERICA INC.

ITEM #	WILLE 475 Δ ATTACHMENTS	PRICE
13010600	Bucket 600L (0.79cu yd) capacity - working width 1700mm (67"). <b>Counterweight recommended</b>	\$3,860
13021200	Snow bucket 1200L (1.57cu yd) capacity - working width 1950mm (77") with removable bolt on cutting edge. <b>Counterweight recommended</b>	\$4,880
13000800	High-tipping bucket 800L (1.05cu yd) capacity - working width 1700mm (67"), tipping height 3400mm (134"), dump height 3400mm (134"). <b>Counterweight recommended</b>	\$10,070
13021201	Leaf bucket 1200L (1.57cu yd) capacity – working width 1950mm (77")	\$11,185
12961000-1	Multi-function bucket 1000L (1.3cu yd) capacity - working width: 1825mm (72") to 3000mm (118") with removable cross hatch cutting edge. <b>Counterweight recommended</b>	\$12,855
15308	Tokvam F180H ribbon snow blower – clearing width 1800mm (71"), hydraulic drive, center-mounted differential, standard chute with hydraulic chute rotation and deflection, Kunta 500 coupler mount with slotted oscillation mount, 500mm (20") diameter auger, 420mm (16.5") diameter impeller, adjustable skid shoes, drift cutters and Hardox wear blade	\$22,735
15938	Tokvam F200H PRO ribbon snow blower – working width 1980mm (78"), hydraulic drive, center-mounted differential, standard chute with hydraulic chute rotation and deflection, Kunta 500 coupler mount with slotted oscillation mount, 650mm (25.6") diameter auger, 550mm (21.6") diameter impeller, adjustable skid shoes, drift cutters, Hardox wear blade	\$40,930
21531	Hydraulic telescopic loading chute for F200H PRO 1680mm (66") to 2680mm (105.5")	\$7,585
18399L/ 18398R	End plate for Tokvam Ribbon Snow Blower. Specify left or right	\$1,760
15698 (23549)	Wear plate for Tokvam skid shoe (each per item- order 2)	\$1,230
VB94/K	WNAI VB94 Folding V plow 2387mm (94") Kunta - hydraulic wings angle change 30deg, relief valve protection, cutting edge with carbide inserts, trip spring protection, hardened steel skid shoes adjustable and replaceable, hydraulic hoses and case drain	\$17,120
A/SB300007	Horst 7' snow blade 2134mm (84") , crossover relief valve, lateral float, 762mm (30") moldboard profile, replaceable and reversible cutting edge, skid shoe and spring trip cutting edge, 2134mm (84") wide, angled snow clearing width 1753mm (69")	\$7,890
A/UAR2950/1500	Stark Uplow, 1950mm (77") – 2920mm (115"), 180-degree rotation, 38 degree angle with pressure relief valve protection, moldboard profile height 760mm (30"), replaceable and reversible cutting edge, skid shoe and blade release system, clearing width closed 1950mm (77"), clearing width open 2920mm (115")	\$28,890



WILLE NORTH AMERICA INC.

ITEM #	WILLE 475 Δ ATTACHMENTS	PRICE
A/TOP6118HSA	SERCO TOP 6118SA expandable plow, 1800mm-2900mm (70.8"-114") expandable width, 800mm (31.5") wing height, hydraulic left/right swivel angle +/- 30°, manual fold up end plates with floating blades	\$23,230
921200111	Galvanized drop spreader (self-loading) 370L (0.5cu yd) capacity – working width 1400mm (55"). Specify material- sand or salt. <b>Rear hydraulic tilting hitch required</b>	\$9,758
13730181	Mechanical rear blade 1801 - working width 1690mm (66.5"), 20° fixed angle, 4° oscillation. <b>Rear hydraulic tilting hitch required</b> <b>LIMITED QUANTITIES AVAILABLE</b>	\$4,230
921200122	Hydraulic Rear Blade 1801 – working width 1832mm (72"), 25° hydraulic angle left & right, 10° hydraulic oscillation both directions	\$17,280
13122200	Rotary brush 200 - working width: 2000mm (79"), 27° hydraulic angle left & right, 700mm (27.5") brush diameter	\$15,710
13122240	Rotary brush 240 – working width: 2040mm (80.3") to 2400mm (94.5"), 27° hydraulic angle left & right, 700mm (27.5") brush diameter	\$16,185
13133306	Additional side brush assembly (left) for Collecting Sweeper 305 – increases overall working width by 450mm (18") to 2050mm (81")	\$3,570
13141000	High pressure baffled water tank 1000L (264gal) capacity - max flow 45L/min (12gpm), max pressure 148bar (2146psi), support legs included. Comes with hand held hose 15m (49') and front mount nozzle pipe, min working width 1630mm (64"), 25° hydraulic angle left & right	\$28,420
13141000-1	Baffled water tank: 1000L (264gal), electric pump 10L/min (2.6gal/min), 2bar (29 psi), mounted over engine, comes with support legs	\$11,570
A/13161300QC	GMR TH3000C triplex rotary mower: cutting width 2900mm (114"), mower width 2975mm (117"), transport width 2000mm (79"), adjustable height 30-80mm (1"-3"), hydraulic tilt, independent adjustable (hydraulic) wings cut 10° below center, cut 15° above center, and vertical tip, front mounting, 5 blades. <b>Hydraulic oil cooler required. Turf tires recommended</b>	\$48,160
A/7443977BT	Bomford 4.3 Robin front mounted boom flail mower, 4300mm (169.3") boom reach, 1000mm (39") flail head, with electric arm floatation. <b>Hydraulic oil cooler required. Counterweight recommended</b>	\$44,460
14190300 14190300-2	Leaf collector 1000L (1.3cu yd) capacity - tipping height 1900mm (75"), suction hose and support legs included, suction nozzle with brush	\$45,935
14190060	Blower unit with pipe for leaf collector - 25° hydraulic angle left & right, mounted on loader	\$2,975
13062500	Pallet forks 120 - 2500kg (5500lbs), 1200mm (48") length, adjustable width: 200mm (8") to 1200mm (48"). <b>Counterweight recommended</b>	\$4,220



WILLE NORTH AMERICA INC.

<b>ITEM #</b>	<b>WILLE 475 Δ ATTACHMENTS</b>	<b>PRICE</b>
14230151	Wille 9 Access platform (includes machine wiring and plug kit)	\$61,360
144447600	Hydraulic tilting platform 300L (0.4cu yd) includes support legs and rear lights	\$11,660
A/LA-BOQF10HW HD IKU500HYD	universal skid steer adapter with hydraulic locking (comes with hoses and couplers)	\$3,735
921200112	De-Icing fluid sprayer 1000L (264gal) application rate of 6 - 60 ml/m <sup>2</sup> (0.001 – 0.013gal/yd <sup>2</sup> ) over 2m – 4.5m (79”- 177”) width. Includes hand held wand with 15m (49’) hose	\$32,600



# WILLE 675 Δ

## Item # 921100144

Kohler KDI3404TCR, Tier 4 Final (134 HP) 4-cylinder turbo diesel engine

Block heater

Hydrostatic transmission with variable displacement pump and motor

2 speed gear box

Auto-load sensing hydraulic drive system

Electronic inching pedal

Automatic differential lock on front and rear axles

Electric/hydraulic engaged parking brake

Servo operated multi disc brakes in oil bath on front and rear axles

Heated side mirrors

Front and rear fenders

High pressure water hose through center section

Reverse alarm

420/65R24 TRI tires

Automatic driving lights

Front (4) and rear (4) LED work lights

High Power LED Beacon light with in cab foldable arm (specify blue or amber)

ROPS (ISO 3471) and FOPS (ISO 3449 1355 J approved) cab

Hydrostatic articulated steering

Electrical main switch

Parking brake interlock safety system

Cab heater with variable fan speed control

Cab filter

Air conditioning- automatic

Air ride heated seat with headrest and safety belt (3 point)

Tilt steering

Roof window Rear window wiper and washer

Manual hydraulic oil fill pump

Tow hitch

Over engine attachment brackets



Radio/mp3 Bluetooth/AUX-in/USB/SD-Card

Electric regulating flow valve for drive hydraulics – 145L/min (38.3gpm) pump

Auxiliary Hydraulic cooler (VT60)

Hydraulic tank heater

3rd cylinder front hydraulics, on/off, Proportional flow, 0-90L/min (0-23.8gpm)

4th cylinder front hydraulics, on/off, Proportional flow, 0-90L/min (0-23.8gpm)

5th cylinder front hydraulics, on/off, Proportional flow, 0-90L/min (0-23.8gpm)

Drive hydraulics (max flow at 2200rpm):

- Front double acting – 0-160L/min (0-42.2gpm)
- Front single acting – 55L - 210L/min (13.2 – 55.4gpm)
- Front single acting – 50L/min (14.5gpm)
- Rear single acting – 50L/min (13.2gpm)
- Rear single acting - 0-160L/min (0-42.2gpm)
- Rear double acting – 50-180L/min (13.2 – 47.5gpm)

Loader:

- Hydraulic self leveling Volvo BM coupler
- Loader arm support for servicing
- Loader arm support for plowing
- Pilot pressure operated joystick
- Ride control/automatic suspensions of the loader after 5kph
- Shock absorber on loader
- Hydraulic attachment lock

Selectable driving profiles for attachments and drivers

Programmable functions of the joystick

Motor hydraulics controlled by driving speed

Smart Cruiser, Smart Flow, Smart Drive

**Base Model MSRP: \$298,690**



WILLE NORTH AMERICA INC.

ITEM #	WILLE 675 Δ OPTIONS	PRICE
14238101	Rear lift with hydraulic hitch (Volvo) <ul style="list-style-type: none"> <li>Includes rear cylinder hydraulics with float position and mirror</li> </ul>	\$8,760
14240200	Smart Lube Central automatic pressure lubrication <ul style="list-style-type: none"> <li>4L (1gal)</li> <li>Includes 5 year warranty (to a maximum of 5,000 hours) against defects in materials or workmanship on the complete center articulation section subject to the usual warranty terms &amp; conditions and all required maintenance being completed as described in the User Handbook service guidelines</li> </ul>	\$8,500
70101020	Filling pump for auto lube	\$730
923100126	Flashing LED light in cab corners <ul style="list-style-type: none"> <li>4 front, 4 rear</li> </ul>	\$2,070
13500106	Back up camera <ul style="list-style-type: none"> <li>RW-710151 with 7" color screen</li> <li>3 channel system with 1 camera</li> </ul>	\$2,070
14235601	6th cylinder hydraulics <ul style="list-style-type: none"> <li>Divided from 4th cylinder hydraulics</li> </ul>	\$1,950
14230114	Flail mower mounting bars - for mounting between loader and front frame	\$975
14208401	Fender mounted tool box	\$955
14218006	Rear counterweight - 400kg/881lbs <ul style="list-style-type: none"> <li>Specify if equipped with or without rear hitch</li> </ul>	\$3,905
	Custom paint. Replaces yellow paint only.	\$2,750



ITEM #	WILLE 675 Δ ATTACHMENTS	PRICE
13010900	Bucket 1000L (1.3cu yd) capacity - working width 2100mm (83"). <b>Counterweight recommended</b>	\$4,522
13021900	Snow bucket 1900L (2.5cu yd) capacity - working width 2300mm (90.5"), comes with replaceable bolt on cutting edge. <b>Counterweight required</b>	\$6,855
13021901	Leaf bucket 1900L (2.5cu yd) capacity - working width 2300mm (90.5")	\$13,685
12961500-1	Multi-function bucket 1500L (2.0cu yd) capacity - working width: 2100mm (83") to 3590mm (141"), comes with replaceable cross hatch cutting edge. <b>Counterweight recommended</b>	\$17,740
15938	Tokvam F200H PRO ribbon snow blower – working width 1980mm (78"), hydraulic drive, center-mounted differential, standard chute with hydraulic chute rotation and deflection, Kunta 500 coupler mount with slotted oscillation mount, 650mm (25.6") diameter auger, 550mm (21.6") diameter impeller, adjustable skid shoes, drift cutters, Hardox wear blade	\$40,930
16355	Tokvam F220H PRO ribbon snow blower – clearing width 2200mm (87"), hydraulic drive, center-mounted differential, standard chute with hydraulic chute rotation and deflection, standard coupler mount, single 650mm (25.6") diameter auger, 550mm (21.6") diameter impeller, drift cutters, adjustable skid shoes	\$43,720
21531	Hydraulic telescopic loading chute for F200H PRO and F220H PRO 1680mm (66") to 2680mm (105.5")	\$7,585
15698 (23549)	Wear plate for Tokvam skid shoe (each per item- order 2)	\$1,760
13150551	Galvanized drop spreader (self-loading) 550L (0.72cu yd) capacity - working width 1700mm (67"). Specify material- sand or salt. <b>Rear lift with hydraulic hitch required</b>	\$13,565
25030510	Tokvam SMA510 spreader - self-loading, hydraulically operated front or rear 500L (0.65cu yd) drop-spreader, working width 1500mm (59"), total width 1680mm (66"), comes with mounting coupler, adjustable flow valve and hydraulic hoses and couplers	\$8,900
2503000/1	Hopper cover for SMA spreader	\$1,620
2503000/2	Tilt cylinder for SMA spreader (for use with 3 point linkage or when rear mounting spreader to Wille)	\$2,350
25060400	Tokvam UT-400 U-plow – max width 4000mm (157.5"), min width 2150mm (84.7"), 38 degree rotation, 300mm (12") oscillation, comes with smooth Hardox cutting edge at 15 degree positive attack angle, shock valve with accumulator, FlexFlow Volvo BM coupler, curb runner, LED lights and 6 hydraulic hoses with couplers. <b>Counterweight required</b>	\$46,225
20339	Tokvam U plow skid shoes (left and right wings)	\$3,005



ITEM #	WILLE 675 Δ ATTACHMENTS	PRICE
921200121	Hydraulic rear blade 2500mm (98.5") – 25° hydraulic angle left & right, 10° hydraulic oscillation in each direction. Includes caster/ support wheels and cross hatch cutting edge. <b>Rear lift with hydraulic hitch required</b>	\$25,040
921200121-1	Hydraulic rear blade 2500mm (98.5") – 25° hydraulic angle left & right, 10° hydraulic oscillation in each direction. Includes caster/ support wheels and Sandvik rotary bits. <b>Rear lift with hydraulic hitch required</b>	\$29,940
A/SB400009	Horst 9' Snow blade 2743mm (108"), crossover relief valve, lateral float, 864mm (34") moldboard profile, replaceable and reversible cutting edge, skid shoe and spring trip cutting edge, 2743mm (108") wide, angled snow clearing width 2250mm (89")	\$12,490
13122270	Rotary brush 270, working width: 2400mm (94.5") to 2700mm (106.3"), 27° hydraulic angle left & right, 700mm (27.5") brush diameter	\$16,660
13122320	Rotary brush 320 – working width: 2800mm (110") to 3200mm (126"), 27° hydraulic angle left & right, 900mm (35.4") brush diameter. <b>Counterweight required</b>	\$17,140
13133550	Collecting sweeper 650 with side brush (right) – hopper capacity 560L (0.75 cu yd), water tank capacity 200L (53gal), working width 2100mm (83"), 700mm (27.5") brush diameter, hydraulic bottom dump. <b>Counterweight required</b>	\$35,465
13133551-1	Additional side brush assembly (left) for Collecting Sweeper 650 – increases overall working width by 450mm (18") to 2550mm (100")	\$3,570
13141500-2	High-pressure baffled water tank 1500L (400gal) capacity – mounted over engine, max flow of 90L/min (23.8gpm), max pressure 2100psi, mounted over engine, comes with support legs, hand held hose 15m (49"), and front mount nozzle pipe – min working width 1900mm (75"), 25° hydraulic angle left & right	\$42,605
13065000	Pallet forks 120 – 5000kg (11,000lbs), 1200mm (48") length, adjustable width: 200mm (8") to 1200mm (48"). <b>Counterweight recommended</b>	\$5,785
144217600	Hydraulic tilting platform 800L (1.05 cu yd) includes support legs and rear lights	\$15,470
14506500	Wille 9 Access platform (includes machine wiring and plug kit)	\$61,360
A/13161400QC	GMR TH4000C triplex rotary mower: cutting width 4025mm (158.5"), mower width 4070mm (160.3"), transport width 2000mm (79"), adjustable height 30-80mm (1"-3"), hydraulic tilt, independent adjustable (hydraulic) wings cut 10° below center, cut 15° above center, and vertical tip, front mounting, 7 blades. <b>Counterweight required</b>	\$63,755
A/9020021FM	Bomford B54FM front mounted boom mower – 5400mm (212.6") reach, with Volvo BM mount and integrated counterweight. Comes with Bomford PRO Cut HD 1200 (48") 125L with case drain, ISPM with 44 Bushmaster Flails. <b>Counterweight required</b>	\$76,250



WILLE NORTH AMERICA INC.

ITEM #	WILLE 675 Δ ATTACHMENTS	PRICE
921200113	De-Icing fluid sprayer 1500L (400gal) application rate of 6 - 60 ml/m <sup>2</sup> (0.001 – 0.013gal/yd <sup>2</sup> ) over 2m – 4.5m (79” - 177”) width. Includes hand held wand with 15m (49’) hose	\$40,460



# WILLE 875 Δ

## Item # 921100147

Kohler KDI 3404 TCR-SCR Stage V (142 HP) 4-cylinder turbo diesel engine Block heater Hydrostatic transmission with variable displacement pump and motor  
 2 speed gear box  
 Auto-load sensing hydraulic drive system  
 Electronic inching pedal  
 Automatic differential lock on front and rear axles  
 Electric/hydraulic engaged parking brake  
 Servo operated multi disc brakes in oil bath on front and rear axles  
 Heated side mirrors  
 Front and rear fenders  
 High pressure water hose through center section  
 Reverse alarm  
 460/65R24 TRI tires  
 Automatic driving lights  
 Front (4) and rear (4) work LED lights  
 High Power LED Beacon light with in cab foldable arm (specify blue or amber)  
 ROPS (ISO 3471) and FOPS (ISO 3449 1355 J approved) cab  
 Hydrostatic articulated steering  
 Electrical main switch  
 Parking brake interlock safety system  
 Cab heater with variable fan speed control  
 Cab filter  
 Air conditioning- automatic  
 Radio/mp3 Bluetooth/AUX-in/USB/SD-Card  
 Air ride heated seat with headrest and safety belt (3 point)  
 Tilt steering  
 Roof window  
 Tow hitch  
 Smart Cruiser, Smart Flow, Smart Drive

Rear window wiper and washer

Manual hydraulic oil fill pump  
 Over engine attachment brackets

Electric regulating flow valve for drive hydraulics – regulates 145L/min (38.3gpm) pump

Auxiliary Hydraulic cooler (VT60)

Hydraulic tank heater

3rd cylinder front hydraulics, on/off, Proportional flow, 0-90L/min (0-23.8gpm)

4th cylinder front hydraulics, on/off, Proportional flow, 0-90L/min (0-23.8gpm)

5th cylinder front hydraulics, on/off, Proportional flow, 0-90L/min (0-23.8gpm)

Drive hydraulics (max flow at 2200rpm):

- Front double acting – 0-160L/min (0-42.2gpm)
- Front single acting – 55L - 210L/min (13.2 – 55.4gpm)
- Front single acting – 50L/min (14.5gpm)
- Rear single acting – 50L/min (13.2gpm)
- Rear single acting - 0-160L/min (0-42.2gpm)
- Rear double acting – 50-180L/min (13.2 – 47.5gpm)

Loader:

- Hydraulic self leveling Volvo BM coupler
  - Loader arm support for servicing
  - Loader arm support for plowing
  - Pilot pressure operated joystick
  - Ride control/automatic suspensions of the loader after 5kph
  - Shock absorber on loader
- Hydraulic attachment lock

Selectable driving profiles for attachments and drivers

Programmable functions of the joystick

Motor hydraulics controlled by driving speed



**Base Model MSRP: \$329,790**



ITEM #	WILLE 875 Δ OPTIONS	PRICE
14838102	Rear lift with hydraulic hitch (Volvo) <ul style="list-style-type: none"> <li>Includes rear cylinder hydraulics with float position and mirror</li> </ul>	\$8,760
14840200	Smart Lube Central automatic pressure lubrication <ul style="list-style-type: none"> <li>4L (1gal)</li> <li>Includes 5 year warranty (to a maximum of 5,000 hours) against defects in materials or workmanship on the complete center articulation section subject to the usual warranty terms &amp; conditions and all required maintenance being completed as described in the User Handbook service guidelines</li> </ul>	\$8,500
70101020	Filling pump for auto lube	\$730
923100126	Flashing LED light in cab corners <ul style="list-style-type: none"> <li>4 front, 4 rear</li> </ul>	\$2,070
13500106	Back up camera <ul style="list-style-type: none"> <li>RW-710151 with 7" color screen</li> <li>3 channel system with 1 camera</li> </ul>	\$2,070
14835601	6th cylinder hydraulics <ul style="list-style-type: none"> <li>Divided from the 4th cylinder hydraulics</li> </ul>	\$1,950
14830114	Flail mower mounting bars – for mounting between loader and front frame	\$975
14208401	Fender mounted tool box	\$955
14218006	Rear counterweight - 400kg/881lbs <ul style="list-style-type: none"> <li>Specify if equipped with or without rear hitch</li> </ul>	\$3,905
	Custom paint. Replaces yellow paint only.	\$2,750



WILLE NORTH AMERICA INC.

ITEM #	WILLE 875 Δ ATTACHMENTS	PRICE
13010900	Bucket 1000L (1.3cu yd) capacity - working width 2100mm (83"). <b>Counterweight recommended</b>	\$4,530
13011300	Bucket 1300L (1.7cu yd) capacity - working width 2300mm (90.5"). <b>Counterweight required</b>	\$6,200
13022501	Snow bucket 2500L (3.27cu yd) capacity - working width 2450mm (96.5"), comes with replaceable bolt on cutting edge. <b>Counterweight required</b>	\$6,905
13021901	Leaf bucket 1900L (2.5cu yd) capacity - working width 2300mm (90.5"). <b>Counterweight recommended</b>	\$14,635
12962000-1	Multi-function bucket 2000L (2.6cu yd) capacity - working width: 2500mm (98.4") to 4000mm (157.5"), comes with replaceable cross hatch cutting edge. <b>Counterweight required</b>	\$18,565
16355	Tokvam F220H PRO ribbon snow blower – clearing width 2200mm (87"), hydraulic drive, center-mounted differential, standard chute with hydraulic chute rotation and deflection, standard coupler mount, single 650mm (25.6") diameter auger, 550mm (21.6") diameter impeller, drift cutters, adjustable skid shoes	\$43,720
21531	Hydraulic telescopic loading chute for F200H PRO and F220H PRO 1680mm (66") to 2680mm (105.5")	\$7,585
15698 (23549)	Wear plate for skid shoe (each per item- order 2)	\$1,760
11860	Tokvam 240H PRO snow blower – clearing width 2400mm (94.5"), hydraulic drive, center-mounted differential, double hydraulic deflector flaps on chute, standard coupler mount, single 440mm (17.3") diameter auger, 750mm (29.5") diameter impeller, comes with, adjustable skid shoes, floatation frame, Hardox wear blade, extension wing with Hardox wear blade (right side, +5") standard chute and telescopic loading chute included  *** in stock demo units (subject to prior sale) available at a special retail of \$40,600.00	\$48,150
F240H Monster	Tokvam F240H Monster ribbon snow blower – clearing width 2400mm (94.5") hydraulic drive, center mounted differential, hydraulic telescopic loading chute with hydraulic chute rotation and deflection, standard coupler mount, single 950mm (37.4") diameter impeller, 1000mm (39.4") diameter auger, bank cutters, run flat wheels, curb runners	\$82,615
24110	Oscillation frame for Tokvam F240H Monster snow blower	\$5,685
13150701	Galvanized drop spreader (self-loading) 700L (1.0 cu yd) capacity - working width 1950mm (76.8"). Specify material- sand or salt. <b>Rear lift with hydraulic hitch required</b>	\$14,995



WILLE NORTH AMERICA INC.

ITEM #	WILLE 875 Δ ATTACHMENTS	PRICE
25030110	Tokvam SMA 1100 spreader - self-loading, hydraulically operated front or rear 1100L (1.44cu yd) drop-spreader, working width 2000mm (79”), total width 2120mm (83”), comes with mounting coupler, adjustable flow valve and hydraulic hoses and couplers	\$10,105
25030160	Tokvam SMA 1600 spreader – self-loading, hydraulically operated front or rear 1600L (2.1cu yd) drop-spreader, working width 2300mm (90.5”), total width 2450mm (96.5”), comes with mounting coupler, adjustable flow valve and hydraulic hoses and couplers. <b>Counterweight recommended</b>	\$11,665
25030160/1	Hopper extension 400L (0.52cu yd). For 25030160	\$2,270
25030240	Tokvam SMA 2400 spreader-self-loading, hydraulically operated front or rear 2400L (3.14 cu yd) drop-spreader, working width 2400mm (94.5”), total width 2520mm (99.2”), comes with mounting coupler, adjustable flow valve and hydraulic hoses and couplers. <b>Counterweight recommended</b>	\$17,985
25030240/1	Hopper extension 600L (0.8cu yd). For 25030240	\$2,270
25060430	Tokvam UT-430 U-plow – max width 4300mm (169.3”), min width 2450mm (96,5”), 38 degree rotation, 300mm (12”) oscillation, comes with smooth Hardox cutting edge at 15 degree positive attack angle, shock valve with accumulator, FlexFlow Volvo BM coupler, curb runner, LED lights and 6 hydraulic hoses with couplers. <b>Counterweight required</b>	\$47,460
25060490	Tokvam UT-490 U-plow – max width 4900mm (193”), min width 2450mm (96.5”), 38 degree rotation, 300mm (12”) oscillation, comes with smooth Hardox cutting edge at 15 degree positive attack angle, shock valve with accumulator, FlexFlow Volvo BM coupler, curb runner, LED lights and 6 hydraulic hoses with couplers. Counterweight required	\$50,740
20339	Tokvam U plow skid shoes (left and right wings)	\$3,005
13730250	Hydraulic rear blade 2500mm (98.4”) – 25° hydraulic angle left & right, 10° hydraulic oscillation in each direction. Includes caster/ support wheels and cross hatch cutting edge. <b>Rear lift with hydraulic hitch required</b>	\$22,610
13730250-1	Hydraulic rear blade 2500mm (98.4”) – 25° hydraulic angle left & right, 10° hydraulic oscillation in each direction. Includes caster/ support wheels and Sandvik 2000 rotary bits. <b>Rear lift with hydraulic hitch required</b>	\$26,660
A/SB400010	Horst 10’ Snow blade 2743mm (120”) snow blade, crossover relief valve, lateral float, 864mm (34”) moldboard profile, replaceable and reversible cutting edge, skid shoe and spring trip cutting edge, 2743mm (120”) wide, angled snow clearing width 2260mm (98.4”)	\$12,490



WILLE NORTH AMERICA INC.

ITEM #	WILLE 875 Δ ATTACHMENTS	PRICE
13122270	Rotary brush 270, working width: 2400mm (94.5") to 2700mm (106.3"), 27° hydraulic angle left & right, 700mm (27.5") brush diameter	\$16,660
13122320	Rotary brush 320 – working width: 2800mm (110") to 3200mm (126"), 27° hydraulic angle left & right, 900mm (35.4") brush diameter. <b>Counterweight required</b>	\$17,140
921200127	Rotary brush MTE 320 – Rear mount, hydraulic float with mechanical adjustment and oscillation frame to maintain surface contact, working width: 2800mm (110") to 3200mm (126"), 27° hydraulic angle left & right, 900mm (35.4") brush diameter.	\$24,990
13133550	Collecting sweeper 650 with side brush right – hopper capacity 560L (0.75cu yd), water tank capacity 200L (53 gal), working width 2100mm (83"), 700mm (27.5") brush diameter, hydraulic bottom dump. <b>Counterweight required</b>	\$34,465
13133551-1	Additional side brush assembly (left) for Collecting Sweeper 650, increases overall working width by 450mm (18") to 2550mm (100")	\$3,570
13141500-2	High-pressure baffled water tank 1500L (400gal) capacity – mounted over engine, max flow of 90L/min (23.8gpm), max pressure 2100psi, mounted over engine, comes with support legs, hand held hose 15m (49'), and front mount nozzle pipe – min working width 1900mm (75"), 25° hydraulic angle left & right	\$42,605
13065000	Pallet Forks 120 – 5000kg (11,000lbs), 1200mm (48") length, adjustable width: 200mm (8") to 1200mm (48"). <b>Counterweight recommended</b>	\$5,785
144217600	Hydraulic tilting platform 800L (1.05 cu yd) includes support legs and rear lights	\$15,470
14506500	Wille 9 Access platform (includes machine wiring and plug kit)	\$61,360
A/13161400	GMR TH4000C triplex rotary mower: cutting width 4025mm (158.5"), mower width 4070mm (160.3"), transport width 2000mm (79"), adjustable height 30-80mm (1"-3"), hydraulic tilt, independent adjustable (hydraulic) wings cut 10° below center, cut 15° above center, and vertical tip, front mounting, 7 blades.	\$63,755
A/9020014FM	Bomford B58TFM telescopic front mounted boom mower – 5791mm (231") reach, with Volvo BM mount and integrated counterweight. Comes with Bomford PRO Cut HD 1200 (48") 125L with case drain, ISPM with 44 Bushmaster Flails. <b>Counterweight required</b>	\$76,480
921200113	De-icing fluid sprayer 1500L (400gal) application rate of 6 – 60 ml/m2 (0.001 – 0.013gal/yd2) over 2m-4.5m (79" – 177") width. Includes hand held wand with 15m (49') hose	\$40,460



WILLE NORTH AMERICA INC.

ITEM #	WILLE 875 Δ ATTACHMENTS	PRICE
PPHYD/PTO	WNAI PPHYD/PTO hydraulic PTO power pack complete with rear hitch platform (to fit Wille 855/865 rear lift) with 1” drop pin drawbar hitch, hydraulically driven PTO motor (1,000 RPM), auxiliary electric hydraulic oil cooler (with wiring and plug), 1” hydraulic hoses and quick couplers, diverter and load-holding valves with hoses and ½” quick couplers. Choice of output shaft (specify at time of order) to fit customer PTO shaft- note PTO shaft for implement not included. <b>Front Counterweight required</b>	\$27,700
A/BTHYSS3HS3P	Buffalo Turbine hydraulic debris blower – high speed	\$27,450