



Over the last forty years, the airline industry has grown significantly, as has the need for a greener, safer and more efficient way to remove runway rubber. **AvaSol** provides industry leading solutions for both asphalt and concrete runways, achieving optimum rubber removal with minimal time and effort.

PERFORMANCE

In a market of diverse runway applications, we have engineered two distinct **AvaSol** Solutions for both grooved & non-grooved runways. Both products provide powerful, efficient cleaning without compromising the environment or the user's safety. These products contain no hazardous carcinogens or phosphates, therefore no special safety equipment is required.

AvaSol-GR3 is engineered especially for grooved runways to minimize runoff and ensure optimum contact with the working surface of the runway. This product is easy to apply and goes to work immediately to dissolve the rubber prior to agitation for an efficient runway turnaround. Because of its viscosity, **AvaSol-GR3** is also extremely effective on non-grooved runways.

AvaSol-NR3 provides an easy-to-use, safe and efficient solution for both grooved and non-grooved runways and can be applied with sprayers prior to agitation. Due to the less viscous nature of **AvaSol-NR3** it should be misted over grooved runways and should be agitated immediately to minimize run off.

HEALTH

- Low oral toxicity
- Non-carcinogenic
- Non-sensitizing

SAFETY

- Safe on skin (non-irritant)
- Flash Point 79°C (174°F)
- Non-corrosive
- No special protective gear required during application

ENVIRONMENT

- Readily biodegradable
- Low acute aquatic toxicity
- Limited effect on aquatic life
- No ozone-depleting substances
- Safe alternative to hazardous substances