



CSM - KENWORTH OF SOUTH TEXAS - SAN ANTONIO (F428) Stock  
P.O. BOX 200187  
SAN ANTONIO, Texas 78220

Kristian Martinez  
Cell Phone:  
Office Phone: 210-662-9333  
Email: kristian.martinez@frenchellison.com

Stock Order

## Vehicle Summary

Unit		Chassis	
Model:	T270 Series Conventional	Fr Axle Load (lbs):	10000
Type:	FULL TRUCK	Rr Axle Load (lbs):	16000
Description 1:	HT06 20H4	G.C.W. (lbs):	26000
Description 2:	T300-270, Conventional Cab, SBFA, SRA		
Application		Road Conditions:	
Intended Serv.:	Local pickup & delivery: Vehicles which	Class A (Highway)	90
Commodity:	General freight.	Class B (Hwy/Mtn)	10
Body		Class C (Off-Hwy)	0
Type:	Van.	Class D (Off-Road)	0
Length (ft):	10	Maximum Grade:	6
Height (ft):	12	Wheelbase (in):	204
Max Laden Weight (lbs):	4000	Overhang (in):	63
Trailer		Fr Axle to BOC (in):	68
No. of Trailer Axles:	0	Cab to Axle (in):	136
Type:		Cab to EOF (in):	199
Length (ft):	0	Overall Comb. Length (in):	307.9
Height (ft):	0	Special Req.	
Kingpin Inset (in):	0	U.S. Domestic registry, 50-state.	
Corner Radius (in):	0		
Restrictions			
Length (ft):	75		
Width (in):	102		
Height (ft):	13.5		

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

Note: All sales are F.O.B. designated plant of manufacture.

Sales Code	Std/Opt	Description	Weight
<b>Model</b>			
0000270	O	<b>T270 Series Conventional</b> Electric Door locks LH/RH; Ignition & doors keyed alike; Single electric horn; Single-piece windshield; Electric windshield wipers, 2-speed plus intermittent; Electric windshield washers; Steering wheel 18in. 4-spoke; Glovebox door with locking latch; Dash-mounted cruise control with switches; Turn signal switch with column-mounted dimmer; Standard dash panels include gray w/ burl wood accents; Slate Gray interior primary color; Dark Slate Gray seat color; Floor mat; Inside sunvisor, LH/RH; Door courtesy lights; Under-dash center console with 1 cup holder, 1 ashtray & 1 lighter.	9,264
0070005	S	<b>T270 Class 6: medium-duty Conventional.</b>	0
0080050	O	<b>CARB Idle Emissions Reduction Feature for PX-7 and PX-9</b>	0
0090014	S	<b>Class 6 4x2 manual.</b>	0
<b>Engine &amp; Equipment</b>			
0120202	S	<b>PACCAR PX-7 200 2017 200@2400 195@2600 520@1600</b> Includes turbo exhaust brake, no code is used. Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing. N09260 P14 64....Max Vehicle Speed in Top Gear N09440 P11 NO....Engine Protection Shtdwn N09460 P06 NO....Gear Down Protection N09300 P19 64....Max Cruise Control Speed N09720 P230 YES...Enable Hot Ambient Automatic N09500 P02 NO....Cruise Control Auto Resume N09520 P04 NO....Auto Engine Brake in Cruise N09480 P26 1400..Max PTO Speed N09580 P32 5.....Idle Shtdwn Time N09680 P33 NO....Idle Shtdwn Override N09560 P520 YES...Enable Idle Shutdown Park Br N09600 P233 YES...Enable Impending Shutdown Wa N09780 P47 80....High Ambient Temperature Thr N09740 P46 40....Low Ambient Temperature Thre N09200 N205 120...Standard Maximum Speed Limit N09620 P234 60....Timer For Impending Shutdown N09360 N203 252...Reserve Speed Function Reset N09640 P516 35....Engine Load Threshold N09400 N206 10....Maximum Active Distance (N20 N09420 N201 0.....Reserve Speed Limit Offset (N N09760 P56 60....Intermediate Ambient Tempera N09380 N202 0.....Maximum Cycle Distance (N202 N09220 N207 0.....Expiration Distance (N207) N09540 N209 0.....Expiration Distance (N209)	0
1000151	S	<b>PremierSpec</b>	0
1000684		<b>Effective VSL Setting NA</b>	0

Price Level: January 1, 2019

Deal: HT06 20H4

Printed On: 1/21/2020 10:01:23 AM

Date: January 14, 2020

Quote Number: QUO-493804-G1D7G5

<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>Weight</b>
1000857	O	<b>Engine Idle Shutdown Timer Enabled</b>	0
1000859	O	<b>Enable EIST Ambient Temp Override</b>	0
1000891		<b>Eff EIST NA Expiration Miles</b>	0
1002060	S	<b>Air compressor: Cummins 18.7 CFM For Cummins And PACCAR PX engines.</b>	0
1031130	O	<b>Air Cleaner: Dry-type firewall mounted w/filter restriction indicator.</b>	0
1105261	S	<b>Fan Hub: Horton On/Off for PX-7</b>	0
1121200	S	<b>Cooling module: 1000 square inches</b> T170/T270/T370/T470. Includes metal surge tank on T170/T270/T370.	0
1247137	S	<b>Exhaust: 2017 EPA Horizontal Under Rail</b> DPF/SCR for PX-7 w/ Horizontal Tailpipe Below RH Rail, BOC.	0
1321109	S	<b>Fuel Filter:PACCAR Standard Service Interval</b> Fuel/Water Separator. 2017 and Later Emissions	0
1321200	O	<b>Run Aid:None</b> *For Fuel Filter	0
1321300	S	<b>Start Aid:None</b> *For Fuel Filter	0
1816160	S	<b>Alternator: 160 amp brush type T3</b>	0
1821220	S	<b>Batteries: 2 PACCAR GP31 threaded post (700-730)</b> 1400-1460 CCA dual purpose.	0
1836107	S	<b>Starter: PACCAR 90P47 12V with PACCAR PX-7</b>	0
<b>Transmission &amp; Clutch</b>			
2050121	S	<b>Transmission: Eaton Fuller FS5406A 6-spd</b> synchro. *Torque Limit: 560 pound-feet.	0
2240001	O	<b>Clutch: ceramic to 605 lb-ft 14 in. Fuller.</b> Includes manual adjusting clutch cover, extended grease fitting for clutch bearing and cross shaft, and synthetic lubricant for the transmission.	0
2401905	S	<b>Driveline: 3 Dana standard-duty; 2 centerbearing.</b> *Standard duty is 1710 series.	0
<b>Front Axle &amp; Equipment</b>			
2501010	S	<b>Dana Spicer E-1002IL Front Axle rated 10K</b> 3-1/2in. drop. Use w/ air brakes only.	0
2603006	S	<b>Front brakes included w/ front hub package.</b>	0
2703051	S	<b>Front Brake: 10,000 lb. Bendix air brake</b> package 15x4 brakes, cast drums, iron preset 10-bolt hub pilot hubs, hub caps, oil seals & slack adjusters.	20
2862090	S	<b>Front Springs: Taperleaf 10K w/ shock absorbers</b> for use on 2010+ chassis w/ 22.5in. wheels only.	0
2895223	S	<b>Single power steering gear: 13.2K for air brakes.</b>	0

Price Level: January 1, 2019

Deal: HT06 20H4

Printed On: 1/21/2020 10:01:23 AM

Date: January 14, 2020

Quote Number: QUO-493804-G1D7G5

Sales Code	Std/ Opt	Description	Weight
<b>Rear Axle &amp; Equipment</b>			
3011046	S	<b>Dana S17-140 17K rated at 16k-single rear axle</b> w/air brakes.	0
3200391	O	<b>Rear Axle Ratio - 3.91.</b>	0
3300000	S	<b>Single rear brakes included w/rear hub package.</b>	0
3403042	S	<b>26K air brake package includes 16-1/2x7 in. brake</b> , cast drums, iron preset 10-bolt hub pilot hubs, slack adjusters	2
3485019	S	<b>Spring Brake: 2430 single for medium duty T300;</b> maximum capacity 17K.	0
3495226	S	<b>Bendix 4S/4M anti-lock brake system.</b>	0
3626479	S	<b>Rear suspension: single Reyco 79KB taperleaf 20K.</b> Medium-duty. Unladen Height: 9 in. Laden Height: 7.6 in. Not rear air disc brake compatible.	0
<b>Tires &amp; Wheels</b>			
4079054	S	<b>Front tires: Bridgestone R268 Ecopia</b> 295/75R22.5 14PR. 40.3 in. diameter, all position. Side wall protector bar. 18.8 in. SLR. For P&D & construction vocations. Smartway certified.	0
4279054	S	<b>Rear Tires: Bridgestone R268 Ecopia 295/75R22.5</b> 14PR. 40.3 in. diameter, all position. Side wall protector bar. 18.8 in. SLR. For P&D & construction vocations. Smartway certified. Code is priced per pair of tires.	0
4900004	O	<b>Rear Tire Quantity: 4</b>	0
5042289	S	<b>Front Wheel: Accuride 51487 22.5x8.25 steel</b> Steel Armor[TM] powder coat, hub-pilot mount. 7400lb. maximum rating. 5-hand hole. Air disc brake compatible.	0
5242389	S	<b>Rear Wheel: Accuride 51487 22.5x8.25 steel</b> Steel Armor[TM] powder coat, hub-pilot mount. 7400lb. maximum rating. 5-hand hole. Air disc brake compatible. Code is priced per pair of wheels.	0
5853906	O	<b>Powder coat white steel wheel. Use in conjunction</b> with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color.	0
5900004	O	<b>Rear Wheel/Rim Quantity: 4</b>	0
<b>Frame &amp; Equipment</b>			
6054250	O	<b>Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to</b> 308 in. Truck frame weight is 2.91 lb.-in. per pair of rails. Section modulus is 14.80 cu.in., RBM is 1,776,000 in.-lbs per rail. 120,000 PSI yield. Heat treated. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is	195

Sales Code	Std/Opt	Description	Weight
		required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	
6308710	O	<b>Bumper: Aerodynamic, Painted. Requires a bumper setting code.</b>	0
6319409	S	<b>40.9 in. Bumper setting. Requires a bumper code.</b>	0
6390103	S	<b>Front mudflaps.</b>	0
6404406	S	<b>Battery box: Steel parallel under w/ aluminum diamond plate cover w/ step w/ aluminum step brackets.</b>	0
6409901	S	<b>Battery box location: LH Side.</b>	0
6490122	S	<b>One-piece welded crossmember assembly with 12mm frame fasteners, center and rear frame. Standard crossmember.</b>	0
6742009	S	<b>Square end-of-frame w/o crossmember; non-towing.</b>	0
<b>Fuel Tanks &amp; Equip</b>			
7130045	S	<b>Fuel Tank: 45 US gallon, rectangular steel with step under replacement.</b>	0
7722008	S	<b>Rectangular DEF tank. 7.5 gallons of usable volume. The tank will be located just forward of the under cab component on the side you specified. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.</b>	0
7889203	S	<b>DEF to fuel fill ratio 2:1 or greater.</b>	0
7889604	S	<b>DEF tank location is LH.</b>	0
7910045	S	<b>Location: 45 gal fuel tank RH under cab</b>	0
<b>Cab &amp; Equipment</b>			
8024310	S	<b>Cab: Curved Glass Conventional.</b> Cab Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Single electric horn standard. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection (excluding T3 series), short and open check diagnostics. Warning alarm will sound when lights are left on.	0
8090310	S	<b>Hood: Sloped aerodynamic hood includes grill &amp; separate bumper.</b>	0
8108010	S	<b>Cab heater: W/integral defrosters &amp; A/C 45,000 btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control. T660 include filter media.</b>	0
8201200	S	<b>Adjustable telescoping tilt steering column.</b>	10
8282009	S	<b>Instrument package: Includes speedometer,</b>	0

Sales Code	Std/ Opt	Description	Weight
		tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	
8330003	S	<b>Cab interior: Pinnacle. Includes vinyl headliner</b> & cab back panel, slate gray interior, dark slate gray seats, floormats, LH/RH inside sunvisor & door courtesy lights.	0
8410081	S	<b>Driver Seat: Kenworth Air Cushion Plus IB Cloth</b> .Standard features include 7 in. fore and aft slide adjustment with isolator, 6 to 23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide with 2 position tilt and 2 position front cushion extension. Seat material has a horizontal stitch pattern and is 2 tone in color. Seat back is carpeted. Seat is manufactured by National. Includes inside visor and retractable 3 point matching seat belts. Grey seat belts.	0
8480080	S	<b>Rider Seat: Kenworth Toolbox Plus IB cloth.</b> Standard features include fixed base and backrest, tool box seat base w/ door, and dual armrests. Seat cushion is 19.5 inches. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	0
8601421	S	<b>Kenworth Radio with AM/FM/WB/USB and Bluetooth</b>	4
8700083	S	<b>Under-dash center console: W/2 cup holders, 1</b> ashtray, 1 lighter, 1 12V outlet & a storage compartment.	0
8700154	S	<b>Self cancelling turn signal: W/head light dimmer</b> switch .	0
8800200	S	<b>Cab access contoured grabhandles, LH/RH.</b>	0
8832115	S	<b>Daylite Door: LH/RH includes RH peeper window</b>	0
8850210	S	<b>Dual convex mirrors 7-1/2 in. w/ offset mounting,</b> and non-heated.	0
8850300	S	<b>Look-Down, Pass. Door, Stainless 8.5x4.4</b>	0
8862101	S	<b>Mirror: Dual Prutsmann mirror 7 in. x 16 in.</b> polished stainless steel, and non-heated.	0
8869005	S	<b>Mirror brackets 8-1/2 ft load width.</b>	0
8871438	S	<b>Rear Cab Stationary Window 17 in. x 36 in.</b>	0
8879200	S	<b>Manual LH &amp; electric-powered RH door window.</b> Switch located on door.	0
<b>Lights &amp; Instruments</b>			
9010801	S	<b>Headlamps: Halogen Projector Low Beam, Halogen</b> Complex Reflector High Beam	0
9020164	S	<b>Marker Lights: with small round base,</b>	0



Sales Code	Std/Opt	Description	Weight
		Five cab roof mounted.	
9030010	S	<b>Turn Signal Lights: Mounted on fender</b>	<b>0</b>
9070138	S	<b>Combination Stop, Tail, Turn &amp; Backup Lights RH &amp; LH.</b>	<b>0</b>
<b>Air Equipment</b>			
9101215	S	<b>Air Dryer Bendix AD-IS heated Puraguard</b>	<b>0</b>
<b>Extended Warranty</b>			
9200007	O	<b>Base Warranty - PACCAR PX-7 Engine</b> 36 months / Unlimited miles & km / Unlimited hours.	<b>0</b>
9200022	S	<b>Base Warranty - Standard Service Medium Duty</b> 12 months / Unlimited miles & km	<b>0</b>
<b>Miscellaneous</b>			
9400072	O	<b>Ship to Dealer.</b>	<b>0</b>
9409852	S	<b>GHG Secondary Manufacturer: Does Not Apply</b>	<b>0</b>
<b>Promotions</b>			
<b>Paint</b>			
9700000	O	<b>Paint color number(s).</b>	<b>0</b>
		N9702 A - L0006 WHITE N9770 BUMPER L0006 WHITE N9720 FRAME N0001 BLACK	
9943001	S	<b>Bumper Painted Color A</b>	<b>0</b>
9943050	O	<b>Day Cab Standard Paint</b>	<b>0</b>
9944820	S	<b>1 - Color Paint - Day Cab</b> Color will be White if no other color is specified.	<b>0</b>
9965510	S	<b>Base coat/clear coat.</b> The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	<b>0</b>

## Order Comments

Total Weight

9,495

Price Level: January 1, 2019

Deal: HT06 20H4

Printed On: 1/21/2020 10:01:23 AM

Date: January 14, 2020

Quote Number: QUO-493804-G1D7G5

## Prices and Specifications Subject to Change Without Notice.

---

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

### **PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*