



CSM - KENWORTH OF SOUTH TEXAS - SAN ANTONIO (F428)  
 P.O. BOX 200187  
 SAN ANTONIO, Texas 78220

HGAC  
 3100 COMMUNICATIONS RD  
 ST CLOUD, Florida 34769  
 United States of America

Kristian Martinez  
 Cell Phone:  
 Office Phone: 210-662-9333  
 Email: kristian.martinez@frenchellison.com

Neal Whitty  
 Office Phone: (713) 499-6693  
 Email: neal.whitty@h-gac.com

## Vehicle Summary

	<b>Unit</b>		<b>Chassis</b>	
Model:	T370 SERIES CONVENTIONAL	Fr Axle Load (lbs):		10000
Type:	FULL TRUCK	Rr Axle Load (lbs):		40000
Description 1:	HT06 20H6 T370 TRA	G.C.W. (lbs):		50000
Description 2:	T300-370, Conventional Cab, SBFA,			
	<b>Application</b>	Road Conditions:		
Intended Serv.:	Local pickup & delivery: Vehicles	Class A (Highway)		90
	which			
Commodity:	General freight.	Class B (Hwy/Mtn)		10
		Class C (Off-Hwy)		0
	<b>Body</b>	Class D (Off-Road)		0
Type:	Van.	Maximum Grade:		6
Length (ft):	10	Wheelbase (in):		229
Height (ft):	12	Overhang (in):		63
Max Laden Weight (lbs):	4000	Fr Axle to BOC (in):		68
		Cab to Axle (in):		161
	<b>Trailer</b>	Cab to EOF (in):		224
No. of Trailer Axles:	0	Overall Comb. Length (in):		332.9
Type:				
Length (ft):	0	<b>Special Req.</b>		
Height (ft):	0	U.S. Domestic registry, 50-state.		
Kingpin Inset (in):	0			
Corner Radius (in):	0			
	<b>Restrictions</b>			
Length (ft):	75			
Width (in):	102			
Height (ft):	13.5			

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

**Note: All sales are F.O.B. designated plant of manufacture.**



Sales Code	Std/Opt	Description	Weight
<b>Model</b>			
0000370	O	<b>T370 SERIES CONVENTIONAL</b> Electric Door locks LH/RH; Ignition & doors keyed alike; Single electric horn; Single-piece windshield; Electric windshield wipers, 2-speed plus intermittent; Electric windshield washers; Steering wheel 18in. 4-spoke; Glovebox door with locking latch; Dash-mounted cruise control with switches; Turn signal switch with column-mounted dimmer; Standard dash panels include gray w/ burl wood accents; Slate Gray interior primary color; Dark Slate Gray seat color; Floor mat; Inside sunvisor, LH/RH; Door courtesy lights; Under-dash center console with 1 cup holder, 1 ashtray & 1 lighter.	9,509
0070006	S	<b>T370 Class 7: medium-duty Conventional.</b>	0
0080050	O	<b>CARB Idle Emissions Reduction Feature for PX-7 and PX-9</b>	0
0090018	O	<b>Medium-duty 6x4 manual.</b>	0
<b>Engine &amp; Equipment</b>			
0120202	S	<b>PACCAR PX-7 200 2017 200@2400 195@2600 520@1600</b> Includes turbo exhaust brake, no code is used. Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing. N09260 P14 64....Max Vehicle Speed in Top Gea N09440 P11 NO....Engine Protection Shtdwn N09460 P06 NO....Gear Down Protection N09300 P19 64....Max Cruise Control Speed N09720 P230 YES...Enable Hot Ambient Automatic N09500 P02 NO....Cruise Control Auto Resume N09520 P04 NO....Auto Engine Brake in Cruise N09480 P26 1400..Max PTO Speed N09580 P32 5.....Idle Shtdwn Time N09680 P33 NO....Idle Shtdwn Override N09560 P520 YES...Enable Idle Shutdown Park Br N09600 P233 YES...Enable Impending Shutdown Wa N09780 P47 80....High Ambient Temperature Thr N09740 P46 40....Low Ambient Temperature Thre N09200 N205 120...Standard Maximum Speed Limit N09620 P234 60....Timer For Impending Shutdown N09360 N203 252...Reserve Speed Function Reset N09640 P516 35....Engine Load Threshold N09400 N206 10....Maximum Active Distance (N20 N09420 N201 0.....Reserve Speed Limit Offset ( N09760 P56 60....Intermediate Ambient Tempera N09380 N202 0.....Maximum Cycle Distance (N202 N09220 N207 0.....Expiration Distance (N207) N09540 N209 0.....Expiration Distance (N209)	0
1000151	S	<b>PremierSpec</b>	0
1000684		<b>Effective VSL Setting NA</b>	0

Sales Code	Std/Opt	Description	Weight
1000857	O	Engine Idle Shutdown Timer Enabled	0
1000859	O	Enable EIST Ambient Temp Overrule	0
1000891		Eff EIST NA Expiration Miles	0
1002060	S	Air compressor: Cummins 18.7 CFM For Cummins And PACCAR PX engines.	0
1031130	S	Air Cleaner: Dry-type firewall mounted w/filter restriction indicator.	0
1105261	S	Fan Hub: Horton On/Off for PX-7	0
1121200	S	Cooling module: 1000 square inches T170/T270/T370/T470. Includes metal surge tank on T170/T270/T370.	0
1247137	S	Exhaust: 2017 EPA Horizontal Under Rail DPF/SCR for PX-7 w/ Horizontal Tailpipe Below RH Rail, BOC.	0
1321109	S	Fuel Filter:PACCAR Standard Service Interval Fuel/Water Separator. 2017 and Later Emissions	0
1321200	O	Run Aid:None *For Fuel Filter	0
1321300	S	Start Aid:None *For Fuel Filter	0
1816260	S	Alternator: PACCAR 160 amp, brush type	0
1821220	S	Batteries: 2 PACCAR GP31 threaded post (700-730) 1400-1460 CCA dual purpose.	0
1836107	S	Starter: PACCAR 90P47 12V with PACCAR PX-7	0
<b>Transmission &amp; Clutch</b>			
2050121	S	Transmission: Eaton Fuller FS5406A 6-spd synchro. *Torque Limit: 560 pound-feet.	0
2240001	S	Clutch: ceramic to 605 lb-ft 14 in. Fuller. Includes manual adjusting clutch cover, extended grease fitting for clutch bearing and cross shaft, and synthetic lubricant for the transmission.	0
2401405	O	Driveline: 2 Dana standard-duty; 1 centerbearing. *Standard duty is 1710 series.	77
<b>Front Axle &amp; Equipment</b>			
2501010	O	Dana Spicer E-1002IL Front Axle rated 10K 3-1/2in. drop. Use w/ air brakes only.	-52
2603006	S	Front brakes included w/ front hub package.	0
2701015	S	Front Brake: 14,600 lb. Bendix air brake package 16.5x5 brakes, cast drums, iron preset 10-bolt hub pilot hubs, hub caps & slack adjusters.	23
2863015	S	Front Springs: Taperleaf 12K w/ shock absorber for use on 2010+ chassis w/ 22.5in. wheels only.	0

Sales Code	Std/Opt	Description	Weight
2895223	S	<b>Single power steering gear: 13.2K for air brakes.</b>	0
<b>Rear Axle &amp; Equipment</b>			
3124403	O	<b>Dual Dana Spicer DSP41 rear axle rated at 40K.</b> (DSP40 w/ heavy-wall housing) w/ 11mm housing and 1.88in. shaft diameter. Tandem rear axles.	2,126
3200411	O	<b>Rear Axle Ratio - 4.11.</b>	0
3300002	O	<b>Dual rear brakes included w/rear hub package.</b>	0
3401002	O	<b>Dual 46K Air Brake package includes 16-1/2x7 in.</b> brakes, cast drums, aluminum 10-bolt hub pilot Preset hubs, slack adjusters and oil seals for use w/ 22.5 in. wheels.	0
3485207	O	<b>Spring Brake: 3030 long stroke dual 30 square</b> inches travel. Helps keep brakes in adjustment longer.	4
3495226	S	<b>Bendix 4S/4M anti-lock brake system.</b>	0
3500037	O	<b>Interaxle driveline:1 Dana 1710 Series</b>	0
3730028	O	<b>Rear suspension: Tandem Kenworth Airglide 400L</b> 40K. 52 in. axle spacing. Air suspension w/ 8.5 in. ride height. Includes single leveling valve. Includes air suspension dump valve.	258
<b>Tires &amp; Wheels</b>			
4079054	S	<b>Front tires: Bridgestone R268 Ecopia</b> 295/75R22.5 14PR. 40.3 in. diameter, all position. Side wall protector bar. 18.8 in. SLR. For P&D & construction vocations. Smartway certified.	0
4279054	S	<b>Rear Tires: Bridgestone R268 Ecopia 295/75R22.5</b> 14PR. 40.3 in. diameter, all position. Side wall protector bar. 18.8 in. SLR. For P&D & construction vocations. Smartway certified. Code is priced per pair of tires.	0
4900008	O	<b>Rear Tire Quantity: 8</b>	0
5042289	S	<b>Front Wheel: Accuride 51487 22.5x8.25 steel</b> Steel Armor[™] powder coat, hub-pilot mount. 7400lb. maximum rating. 5-hand hole. Air disc brake compatible.	0
5242389	S	<b>Rear Wheel: Accuride 51487 22.5x8.25 steel</b> Steel Armor[™] powder coat, hub-pilot mount. 7400lb. maximum rating. 5-hand hole. Air disc brake compatible. Code is priced per pair of wheels.	0
5853906	O	<b>Powder coat white steel wheel. Use in conjunction</b> with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color.	0
5900008	O	<b>Rear Wheel/Rim Quantity: 8</b>	0
<b>Frame &amp; Equipment</b>			
6054410	O	<b>Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to</b> 309 in. to 380 in. Truck frame weight is 2.91 lb.-in. per pair of rails. Section modulus is 14.80 cu.in., RBM is 1,776,000 in.-lbs per rail.	268

Price Level: January 1, 2019

Deal: HT06 20H6 T370 TRA

Printed On: 1/21/2020 10:03:35 AM

Date: January 14, 2020

Quote Number: QUO-493855-X2C7S7

Sales Code	Std/Opt	Description	Weight
		120,000 PSI yield. Heat treated. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	
6308710	S	<b>Bumper: Aerodynamic, Painted. Requires a bumper setting code.</b>	0
6319409	S	<b>40.9 in. Bumper setting. Requires a bumper code.</b>	0
6390103	S	<b>Front mudflaps.</b>	0
6404406	S	<b>Battery box: Steel parallel under w/ aluminum diamond plate cover w/ step w/ aluminum step brackets.</b>	0
6409901	S	<b>Battery box location: LH Side.</b>	0
6490122	S	<b>One-piece welded crossmember assembly with 12mm frame fasteners, center and rear frame. Standard crossmember.</b>	0
6742009	S	<b>Square end-of-frame w/o crossmember; non-towing.</b>	0
<b>Fuel Tanks &amp; Equip</b>			
7130045	S	<b>Fuel Tank: 45 US gallon, rectangular steel with step under replacement.</b>	0
7722008	S	<b>Rectangular DEF tank. 7.5 gallons of usable volume. The tank will be located just forward of the under cab component on the side you specified. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.</b>	0
7889203	S	<b>DEF to fuel fill ratio 2:1 or greater.</b>	0
7889604	S	<b>DEF tank location is LH.</b>	0
7910045	S	<b>Location: 45 gal fuel tank RH under cab</b>	0
<b>Cab &amp; Equipment</b>			
8024310	S	<b>Cab: Curved Glass Conventional.</b> Cab Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Single electric horn standard. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection (excluding T3 series), short and open check diagnostics. Warning alarm will sound when lights are left on.	0
8090310	S	<b>Hood: Sloped aerodynamic hood includes grill &amp; separate bumper.</b>	0
8108010	S	<b>Cab heater: W/integral defrosters &amp; A/C 45,000 btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control. T660 include filter media.</b>	0

Sales Code	Std/Opt	Description	Weight
8201200	S	<b>Adjustable telescoping tilt steering column.</b>	10
8282009	S	<b>Instrument package: Includes speedometer,</b> tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	0
8330003	S	<b>Cab interior: Pinnacle. Includes vinyl headliner</b> & cab back panel, slate gray interior, dark slate gray seats, floormats, LH/RH inside sunvisor & door courtesy lights.	0
8410081	S	<b>Driver Seat: Kenworth Air Cushion Plus IB Cloth</b> .Standard features include 7 in. fore and aft slide adjustment with isolator, 6 to 23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide with 2 position tilt and 2 position front cushion extension. Seat material has a horizontal stitch pattern and is 2 tone in color. Seat back is carpeted. Seat is manufactured by National. Includes inside visor and retractable 3 point matching seat belts. Grey seat belts.	0
8480080	S	<b>Rider Seat: Kenworth Toolbox Plus IB cloth.</b> Standard features include fixed base and backrest, tool box seat base w/ door, and dual armrests. Seat cushion is 19.5 inches. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	0
8700154	S	<b>Self cancelling turn signal: W/head light dimmer</b> switch .	0
8800200	S	<b>Cab access contoured grabhandles, LH/RH.</b>	0
8832115	S	<b>Daylite Door: LH/RH includes RH peeper window</b>	0
8850210	S	<b>Dual convex mirrors 7-1/2 in. w/ offset mounting,</b> and non-heated.	0
8850300	S	<b>Look-Down, Pass. Door, Stainless 8.5x4.4</b>	0
8862101	S	<b>Mirror: Dual Prutsman mirror 7 in. x 16 in.</b> polished stainless steel, and non-heated.	0
8869005	S	<b>Mirror brackets 8-1/2 ft load width.</b>	0
8871438	S	<b>Rear Cab Stationary Window 17 in. x 36 in.</b>	0
8879200	S	<b>Manual LH &amp; electric-powered RH door window.</b> Switch located on door.	0
<b>Lights &amp; Instruments</b>			
9010801	S	<b>Headlamps: Halogen Projector Low Beam, Halogen</b> Complex Reflector High Beam	0
9020164	S	<b>Marker Lights: with small round base,</b> Five cab roof mounted.	0



Sales Code	Std/Opt	Description	Weight
9030010	S	Turn Signal Lights: Mounted on fender	0
9070138	S	Combination Stop, Tail, Turn & Backup Lights RH & LH.	0
<b>Air Equipment</b>			
9101215	S	Air Dryer Bendix AD-IS heated Puraguard	0
<b>Extended Warranty</b>			
9200007	O	Base Warranty - PACCAR PX-7 Engine 36 months / Unlimited miles & km / Unlimited hours.	0
9200022	S	Base Warranty - Standard Service Medium Duty 12 months / Unlimited miles & km	0
<b>Miscellaneous</b>			
9400072	O	Ship to Dealer.	0
9409852	O	GHG Secondary Manufacturer: Does Not Apply	0
<b>Promotions</b>			
<b>Paint</b>			
9700000	O	Paint color number(s). N9702 A - L0006 WHITE N9770 BUMPER L0006 WHITE N9720 FRAME N0001 BLACK	0
9943001	S	Bumper Painted Color A	0
9943050	O	Day Cab Standard Paint	0
9944820	S	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0
9965510	S	Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0

**Order Comments**

Total Weight

12,223



## Prices and Specifications Subject to Change Without Notice.

---

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

### **PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*