



CSM - KENWORTH OF SOUTH TEXAS - SAN ANTONIO (F428)
P.O. BOX 200187
SAN ANTONIO, Texas 78220

HGAC
3100 COMMUNICATIONS RD
ST CLOUD, Florida 34769
United States of America

Kristian Martinez
Cell Phone:
Office Phone: 210-662-9333
Email: kristian.martinez@frenchellison.com

Neal Whitty
Office Phone: (713) 499-6693
Email: neal.whitty@h-gac.com

Vehicle Summary

| Unit | | Chassis | |
|-------------------------|---|-----------------------------------|-------|
| Model: | T800 Series Conventional. | Fr Axle Load (lbs): | 12000 |
| Type: | FULL TRUCK | Rr Axle Load (lbs): | 22700 |
| Description 1: | HT06 20H13 T800 SRA | G.C.W. (lbs): | 34700 |
| Description 2: | T800, Conventional Cab, SBFA, SRA | | |
| Application | | Road Conditions: | |
| Intended Serv.: | Local pickup & delivery: Vehicles which | Class A (Highway) | 90 |
| Commodity: | Other building materials. | Class B (Hwy/Mtn) | 10 |
| Body | | Class C (Off-Hwy) | 0 |
| Type: | Flatbed. | Class D (Off-Road) | 0 |
| Length (ft): | 12 | Maximum Grade: | 6 |
| Height (ft): | 13 | Wheelbase (in): | 150 |
| Max Laden Weight (lbs): | 4000 | Overhang (in): | 60 |
| | | Fr Axle to BOC (in): | 74 |
| Trailer | | Cab to Axle (in): | 76 |
| No. of Trailer Axles: | 0 | Cab to EOF (in): | 136 |
| Type: | | Overall Comb. Length (in): | 258.5 |
| Length (ft): | 0 | Special Req. | |
| Height (ft): | 0 | U.S. Domestic registry, 50-state. | |
| Kingpin Inset (in): | 0 | | |
| Corner Radius (in): | 0 | | |
| Restrictions | | | |
| Length (ft): | 75 | | |
| Width (in): | 102 | | |
| Height (ft): | 13.5 | | |

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

| Sales Code | Std/ Opt | Description | Weight |
|-------------------------------|----------|--|---------------|
| Model | | | |
| 0000800 | S | T800 Series Conventional. Elastomer bushed front spring pins & heavy-duty shock absorber brackets, 16mm. fasteners from rear cab support to end-of-frame, except tractor taper crossmember. Vinyl inside sunvisors, driver side includes strap & mirror, rider side includes strap; Under-dash center console w/ 2 cup holders, 2-12V outlets & a storage compartment, Glove box door with locking latch. | 15,004 |
| 0070066 | S | T800: Sloped Hood. | 0 |
| 0080066 | O | CARB Idle Emissions Reduction - MX | 0 |
| 0090000 | S | Non-Sleeper w/rear axle capacity less than 59K. | 0 |
| Engine & Equipment | | | |
| 0700656 | S | PACCAR MX-13 455 2017 455@1600 1650@900 with engine brake N09020 N170 155...Standard Maximum Speed Limit N09040 N162 64....Maximum Accelerator Pedal Ve N09070 N052 650...Engine Idle Speed (N052) N09110 N019 0.....Delay in Engine Brake Activa N09120 N014 2.....Auto Retard Vehicle Speed Of N09130 N013 4.....Downhill Speed Limiter Vehic N09140 N006 64....Max Cruise Speed (N006) N09150 N001 16....Minimum Speed to Turn Cruise N09160 N003 19....Minimum Cruise Control Speed N09170 N002 19....Min Speed to Automatically T N09230 N187 5.....Timer Setting Non-PTO Mode w N09250 N190 YES...Reset EIST Timer Based on En N09260 N191 NO....Override EIST Timer Based on N09390 N072 1900..Maximum Fast Idle Control En N09450 N078 ON....PTO Mode Disabled w/ Clutch N09460 N101 ON....PTO Mode Disabled w/ Service N09470 N079 ON....PTO Mode Enable Only w/ Park N09480 N089 ON....PTO Mode Enable Only w/ Tran N09550 N086 2000..Maximum Engine Speed During N09350 N197 YES...Enable Accelerator Pedal Res N09360 N199 YES...Enable Clutch Pedal Reset (N N09370 N198 YES...Enable Service Brake Reset (N N09540 N087 780...RPM Set Point (N087) N09300 N185 40....Low Ambient Temperature Over N09310 N184 80....High Ambient Temperature Ove N09280 N186 5.....Timer Setting When in PTO Mo N09100 N015 NO....Enable Retarder During Manua N09290 N200 YES...Allow EIST Timer Overrides i N09220 N188 5.....Timer Setting Non-PTO Mode w N09510 N307 OFF...Cab Accelerator Active in Re N09440 N080 1.....PTO Vehicle Speed Limit (N08 N09500 N076 2000..Max Accelerator Controlled E N09600 N106 650...Minimum Engine Speed During | 0 |

| Sales Code | Std/Opt | Description | Weight |
|------------|---------|---|----------|
| | | N09940 N055 780...RPM Set Point 1 (N055) | |
| | | N09960 N056 1030..RPM Set Point 2 (N056) | |
| | | N09840 N179 YES...Enable Park Brake Reset (N17 | |
| | | N09900 N182 30....Coolant Temperature Override | |
| | | N08030 N224 2.....Maximum Vehicle Speed Bonus | |
| | | N08040 N227 -2.....Maximum Vehicle Speed Penalt | |
| | | N08190 N246 4.....Minimum Vehicle Speed for DS | |
| | | N08200 N247 1.....Lowest Gear that DSA will be | |
| | | N08210 N248 10....Highest Gear that DSA will b | |
| | | N09640 N173 0.....Reserve Speed Offset (N173) | |
| | | N09880 N164 252...Reserve Speed Function Reset | |
| | | N09530 N110 1.....Enable Set Point w/ Set/Acce | |
| | | N08000 N219 0.....Offset mode (N219) | |
| | | N09920 N073 0.....Cab Accel Pedal Type in PTO | |
| | | N09380 N071 ON....FIC Enable/Disable (N071) | |
| | | N09200 N039 OFF...Allow Multi-Torque Only When | |
| | | N09030 N169 0.....VSL Expiration Distance (N16 | |
| | | N09210 N193 0.....EIST Expiration Distance (N1 | |
| | | N09060 N163 0.....Maximum Cycle Distance (N163 | |
| 1000151 | S | PremierSpec | 0 |
| 1000204 | O | Engine monitoring protection -Derate- PACCAR MX engine parameter. | 0 |
| 1000239 | O | Engine parameter: Driveline Protect - torque limiting Paccar MX | 0 |
| 1000244 | O | Gearing Analysis: Balance power/economy blend results. | 0 |
| 1000256 | S | Customer's Typical Operating Spd: 64 MPH | 0 |
| 1000282 | O | MX Retarder State Cruise Control On Manual Mode Selecting this code will program the engine controller to make manual mode available when cruise control is on, but not set, and the engine brake switch is on. Manual mode means the engine retarder activates whenever the throttle pedal is not depressed. 2013+ | 0 |
| 1000684 | | Effective VSL Setting NA | 0 |
| 1000857 | S | Engine Idle Shutdown Timer Enabled | 0 |
| 1000859 | O | Enable EIST Ambient Temp Override | 0 |
| 1000891 | | Eff EIST NA Expiration Miles | 0 |
| 1006003 | S | Air Compressor: WABCO 25.9 CFM PACCAR MX 2017 440cc Air Compressor | 0 |
| 1051086 | S | Air cleaner: Powercore engine mount 10 in. w/constant torque SS clamps, pop-up air restriction indicator. Holds 10% more fine dust than 2500. Pop-up indicator is standard. | 0 |
| 1105210 | S | Fan hub: Horton 2-Speed for PACCAR MX | 0 |

| Sales Code | Std/Opt | Description | Weight |
|-----------------------------------|---------|---|--------|
| 1125640 | S | Cooling module: T8SH/T8B/W9S 1440 square inches. Includes aluminum radiator core, aluminum charge air cooler, translucent surge tank and washer bottle, silicone hoses, and extended life coolant. Drain valve is not available w/Allison transmissions. | 0 |
| 1247166 | S | Exhaust: 2017 EPA RH Under DPF/SCR w/ RH side of cab vertical tailpipe w/ daycabs, extended daycabs, or modular sleepers. | 0 |
| 1290136 | S | Tailpipe: 5 in. single 36 in. 45 degree curved. | 0 |
| 1321109 | S | Fuel Filter:PACCAR Standard Service Interval Fuel/Water Separator. 2017 and Later Emissions | 0 |
| 1321205 | S | Run Aid:Fuel Heat *For Fuel Filter | 0 |
| 1321300 | S | Start Aid:None *For Fuel Filter | 0 |
| 1816260 | S | Alternator: PACCAR 160 amp, brush type | 0 |
| 1821210 | S | Batteries: 3 PACCAR GP31 threaded post (700-730) 2100-2190 CCA dual purpose. | 0 |
| 1836102 | S | PACCAR Premium 12V Starter with PACCAR MX Engines PACCAR 12 volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded. | 0 |
| 1900084 | O | Multi-function engine connector for body builder interface PACCAR MX engine only. T680/T880: This feature is standard, no code required. | 0 |
| Transmission & Clutch | | | |
| 2058437 | S | Fuller Advantage Automated FAO-16810C-EA3 10Speed No Cooler w/ HSA *Use w/ 2250385 Only. | 0 |
| 2250385 | S | Clutch:UltraShift Plus Or Fuller Advantage Series Automated transmissions. | 0 |
| 2408401 | O | Driveline: 2 Meritor RPL25; 1 Centerbearing Require 3500058 | 77 |
| 2429100 | O | Chassis will be fitted w/ LH transmission PTO. (Prevents ECU F/Interfering w/ PTO Only). | 0 |
| Front Axle & Equipment | | | |
| 2512042 | O | Meritor MFS12E PLUS 12.5K 3.5in. drop standard track | 0 |
| 2621310 | O | Front Brakes: 14.6K Bendix ES s-cam 16.5x5 in. | -62 |
| 2690002 | O | Front Brake Drums: 14.6K 16.5x5 in. cast. | 78 |
| 2690039 | S | Integral Knuckle for Air Disc Brake, for use on PACCAR Steer Axle | 0 |
| 2701300 | O | Front Hub: aluminum hub pilot 13,200 lbs. 10-Bolt, 11-1/4 in. bolt circle . | 0 |
| 2741970 | S | ConMet PreSet Plus Hub package; front axle. | 0 |

| Sales Code | Std/ Opt | Description | Weight |
|----------------------------------|-----------------|---|---------------|
| 2750001 | S | Hubcap: front vented. | 0 |
| 2765001 | O | Front Auto Slack Adjuster. | 0 |
| 2863012 | O | Front Springs: Taperleaf 12K w/ shock absorbers w/ maintenance-free elastomer spring pin bushings. Standard with rubber pins except for C500 which has threaded pins. Not available on W900L. | 0 |
| 2895121 | O | Single power steering gear: 13.2K Sheppard M100P. | 0 |
| 2899336 | S | Power Steering Cooler:Radiator Mounted Air-to-Oil | 11 |
| Rear Axle & Equipment | | | |
| 3042160 | O | Single Meritor R23-160 rear axle rated at 23K. | -1,863 |
| 3200342 | O | Rear Axle Ratio - 3.42. | 0 |
| 3330004 | O | Single Rear Brakes 16-1/2x7 in. Bendix ES- extended service S-cam. | 0 |
| 3392007 | O | Single Rear Brake Drums: cast. | 0 |
| 3401010 | O | Single Rear Hubs: Aluminum hub pilot 23K; 11-1/4 in. bolt circle. | 0 |
| 3465001 | O | Single Rear axle automatic slack adjusters. | 0 |
| 3485007 | O | Spring Brake: 3030 long stroke single 3 in. travel. Helps keep brakes in adjustment longer. | 2 |
| 3495228 | S | Bendix 4S/4M anti-lock brake system w/ air traction control (ATC). | 0 |
| 3636480 | O | Rear suspension: single Reyco 79KB taperleaf 23K. Steel crossmembers & gussets, Kenworth longlife spring w/helper. Unladen Height: 11.0 in. Laden Height: 9.3 in. Not available with shocks or swaybars. | -162 |
| 3830145 | O | Delete standard heavy-duty air springs for rear suspension. | 0 |
| Tires & Wheels | | | |
| 4070040 | O | Front Tires: Bridgestone R284 Ecopia 295/75R22.5 | 0 |
| 4270040 | S | Rear Tires: Bridgestone R284 Ecopia 295/75R22.5 14PR | 0 |
| 4900004 | O | Rear Tire Quantity: 4 | 0 |
| 5142289 | O | Front Wheel: Accuride 51487 22.5x8.25 steel twin steer 4-4: Steel Armor[TM] powder coat, hub-pilot mount. 7400lb. maximum rating. 5-hand hole. Air disc brake compatible. | 0 |
| 5242389 | O | Rear Wheel: Accuride 51487 22.5x8.25 steel | 0 |

| Sales Code | Std/Opt | Description | Weight |
|------------|---------|---|--------|
| | | Steel Armor[™] powder coat, hub-pilot mount. 7400lb. maximum rating. 5-hand hole. Air disc brake compatible. Code is priced per pair of wheels. | |
| 5853906 | S | Powder coat white steel wheel. Use in conjunction with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color. | 0 |
| 5900004 | O | Rear Wheel/Rim Quantity: 4 | 0 |

Frame & Equipment

| | | | |
|---------|---|--|-----|
| 6056200 | S | Frame Rails: 10-3/4 x 3-1/2 x 3/8in. Steel to 284 in. Truck frame weight is 3.48 lb.-in. per pair of rails. Section modulus is 17.80, RBM is 2,132,000 in.-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail. | 108 |
| 6301360 | S | Bumper: Straight Aluminum Channel. Requires a bumper setting code. | 0 |
| 6319485 | O | 48.5 in. Bumper setting. Requires a bumper code. | 0 |
| 6390103 | S | Front mudflaps. | 0 |
| 6405048 | S | Battery box module: Short length aluminum parallel under cab, aluminum diamond plate cover w/ step. Up to 2 air tanks may mount to bottom of box. Batteries will be oriented perpendicular on rail. | 0 |
| 6409901 | S | Battery box location: LH Side. | 0 |
| 6451090 | S | T470,C5, T6, T8 non-polished DPF/SCR or CNG cover diamond plate w/ step. For use w/ 2010 or later exhaust systems. For T8, use extended length non-polished battery box on opposite rail to match the length of under cab components. End plates will be painted standard black frame color. | 0 |
| 6721102 | S | Rear mudflap arms: Betts B-25 standard-duty, straight. Includes B1732 mounting brackets as standard. | 0 |
| 6722000 | S | Rear mudflap shields: White plastic antisail w/ Kenworth logo. | 0 |
| 6742009 | S | Square end-of-frame w/o crossmember; non-towing. | 0 |

Fuel Tanks & Equip

| | | | |
|---------|---|---|-----|
| 7214075 | O | Fuel Tank: 75 US gallon 24.5in. aluminum BOC replace. Class 8 fuel tanks w/ o locking caps include an anti-siphon device on the filler neck. | -11 |
| 7722011 | S | Small round DEF tank. 11 gallons of usable volume. The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated | 0 |

| Sales Code | Std/Opt | Description | Weight |
|----------------------------|---------|---|--------|
| | | by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204. | |
| 7889203 | S | DEF to fuel fill ratio 2:1 or greater. | 0 |
| 7889245 | S | Anti-siphon device swaged in place. For any number of fuel tanks. | 0 |
| 7889604 | S | DEF tank location is LH. | 0 |
| 7930075 | O | Location: 75 gal fuel tank RH behind cab | 0 |
| Cab & Equipment | | | |
| 8024310 | S | Cab: Curved Glass Conventional. Cab Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Single electric horn standard. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection (excluding T3 series), short and open check diagnostics. Warning alarm will sound when lights are left on. | 0 |
| 8090103 | S | Hood: Sloped Metton Hood W/ Grille & Shell Use For T800B 1-Piece Requires Engine Mounted Air Cleaner, 1440 Square In. Radiator & 2007+ Engines. | 0 |
| 8108010 | S | Cab heater: W/integral defrosters & A/C 45,000 btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control. T660 include filter media. | 0 |
| 8201013 | S | Steering wheel: 18 in. 4-spoke. | 0 |
| 8201200 | S | Adjustable telescoping tilt steering column. | 10 |
| 8282004 | S | KW Driver Information Center: Includes fuel economy, RPM display, trip information, truck information, diagnostics, gear display, alarm clock. | 0 |
| 8282009 | S | Instrument package: Includes speedometer, tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada. | 0 |
| 8331100 | S | Cab interior: Splendor. Includes smooth upholstered side & back panels w/stitched accent lines, upholstered door pads, full vinyl headliner, black dash panels & black rubber floormats. | 0 |
| 8343304 | S | Interior color: Slate Gray w/trim Dark Slate Gray | 0 |
| 8410091 | S | Driver seat: Kenworth Air cushion Plus HB cloth. Standard features includes 7 in. fore and aft slide adjustment w/isolator, 6-23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide w/ 2-position tilt and 2-position front cushion extension. Seat material has a | 0 |

Price Level: January 1, 2019

Deal: HT06 20H13 T800 SRA

Printed On: 1/21/2020 10:20:02 AM

Date: January 20, 2020

Quote Number: QUO-494888-B2D8K8

| Sales Code | Std/ Opt | Description | Weight |
|------------|----------|---|--------|
| | | horizontal stitch pattern and is 2-tone in color. Seat back is carpeted and includes a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts. | |
| 8480090 | S | Rider seat: Kenworth Toolbox Plus HB cloth. Standard features include fixed base and backrest, tool box seat base w/ door, and dual armrests. Seat cushion is 19.5 inches. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted with a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts. | 0 |
| 8490110 | S | Seat color: Dark Slate Gray. | 0 |
| 8700108 | S | Under dash center console: Includes one cupholder & two 12V outlets. For use w/Autoshift, Ultrashift, & Allison Gen IV only. | 0 |
| 8700168 | S | Non-self cancelling turn signal: W/column-mounted headlight dimmer switch & intermittent wiper control. | 0 |
| 8700186 | S | Electric LH & RH door locks. | 0 |
| 8700663 | S | Kenworth TruckTech+ The Kenworth Remote Diagnostics system provides the Worlds Best reporting of engine and aftertreatment fault codes, as well as enhanced support for the truck owner through rapid communication of fault severity and recommended actions. This option is Standard on all Heavy Duty Kenworths with a PACCAR MX engine, Cummins X15 engine, PX engine or Natural Gas engine. Optional on Medium Duty Kenworths. | 0 |
| 8800271 | S | Long grabhandle RH side of cab. | 0 |
| 8800373 | S | Long grabhandle LH side of cab. | 0 |
| 8800400 | S | Grabhandle: LH inside door frame above dash. | 0 |
| 8800401 | S | Grabhandle: RH inside door frame above dash. | 0 |
| 8832115 | S | Daylite Door: LH/RH includes RH peeper window | 0 |
| 8841411 | S | Single air horn under cab. | 0 |
| 8850300 | S | Look-Down, Pass. Door, Stainless 8.5x4.4 | 0 |
| 8866100 | S | Mirror: Dual Prutsman fixed heated mirrors 7 in. x 16 in. includes 7-1/2 in. convex mirror, RH. | 0 |
| 8869005 | S | Mirror brackets 8-1/2 ft load width. | 0 |
| 8871438 | S | Rear Cab Stationary Window 17 in. x 36 in. | 0 |
| 8879200 | S | Manual LH & electric-powered RH door window. Switch located on door. | 0 |
| 8890100 | S | One-piece windshield, w/ curved glass. | 0 |
| 8890134 | S | Exterior aerodynamic sunvisor w/ integral marker | 0 |

| Sales Code | Std/Opt | Description | Weight |
|---------------------------------|---------|---|--------|
| | | lights. | |
| Lights & Instruments | | | |
| 9010802 | S | Headlamps: Dual Rectangular, extended life halogen | 0 |
| 9026200 | S | Marker Lights: Five aerodynamic mounted in sunvisor. | 0 |
| 9030010 | S | Turn Signal Lights: Mounted on fender | 0 |
| 9030052 | S | LED Stop,Turn,Tail: With Two LED Backup Lights and With An LED License Plate. | 0 |
| 9090039 | S | Marker Lights: Interrupter Switch. Included in Turn Signal For All Models Except T3. The T3 Switch Is In The Dash. | 0 |
| 9090049 | S | Omit Brake Light with Engine Brake. Can only be selected when chassis also has engine brake. Cannot be used with options to delete engine brake. | 0 |
| Air Equipment | | | |
| 9101215 | S | Air Dryer Bendix AD-IS heated Puraguard | 0 |
| 9108001 | S | Moisture ejection valve w/ pull cable drain. | 0 |
| 9140020 | S | Nylon air tubing in frame & cab, excluding hoses subject to excessive heat or flexing. | 0 |
| Extended Warranty | | | |
| 9200006 | O | Base Warranty - PACCAR MX-11 & MX-13 Engine 24 months / 250,000 miles / 400,000 km / 6250 hours. | 0 |
| 9200021 | S | Base Warranty - Standard Service Heavy Duty 12 months / 100,000 miles / 160,000 km. | 0 |
| Miscellaneous | | | |
| 9400072 | O | Ship to Dealer. | 0 |
| 9409852 | O | GHG Secondary Manufacturer: Does Not Apply | 0 |
| Promotions | | | |
| Paint | | | |
| 9700000 | O | Paint color number(s). N9702 A - L0006 WHITE N9720 FRAME N0001 BLACK | 0 |
| 9943004 | O | Bumper Unpainted | 0 |
| 9943050 | S | Day Cab Standard Paint | 0 |

| Sales Code | Std/ Opt | Description | Weight |
|------------|----------|--|--------|
| 9944820 | S | 1 - Color Paint - Day Cab Color will be White if no other color is specified. | 0 |
| 9965510 | O | Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint. | 0 |

Order Comments

Total Weight

13,159

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information