



CSM - KENWORTH OF SOUTH TEXAS - SAN ANTONIO (F428)
P.O. BOX 200187
SAN ANTONIO, Texas 78220

HGAC
3100 COMMUNICATIONS RD
ST CLOUD, Florida 34769
United States of America

Kristian Martinez
Cell Phone:
Office Phone: 210-662-9333
Email: kristian.martinez@frenchellison.com

Neal Whitty
Office Phone: (713) 499-6693
Email: neal.whitty@h-gac.com

Vehicle Summary

Unit		Chassis	
Model:	T170 SERIES CONVENTIONAL	Fr Axle Load (lbs):	8000
Type:	FULL TRUCK	Rr Axle Load (lbs):	11500
Description 1:	HT06 20H3	G.C.W. (lbs):	19500
Description 2:	T300-170, Conventional Cab, SBFA, SRA		
Application		Road Conditions:	
Intended Serv.:	Local pickup & delivery: Vehicles which	Class A (Highway)	90
Commodity:	General freight.	Class B (Hwy/Mtn)	10
Body		Class C (Off-Hwy)	0
Type:	Van.	Class D (Off-Road)	0
Length (ft):	10	Maximum Grade:	6
Height (ft):	12	Wheelbase (in):	206
Max Laden Weight (lbs):	4000	Overhang (in):	58
Trailer		Fr Axle to BOC (in):	68
No. of Trailer Axles:	0	Cab to Axle (in):	138
Type:		Cab to EOF (in):	196
Length (ft):	0	Overall Comb. Length (in):	304.9
Height (ft):	0	Special Req.	
Kingpin Inset (in):	0	U.S. Domestic registry, 50-state.	
Corner Radius (in):	0		
Restrictions			
Length (ft):	75		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

Sales Code	Std/Opt	Description	Weight
Model			
0000170	O	T170 SERIES CONVENTIONAL Electric Door locks LH/RH; Ignition & doors keyed alike; Single electric horn; Single-piece windshield; Electric windshield wipers, 2-speed plus intermittent; Electric windshield washers; Steering wheel 18in. 4-spoke; Glovebox door with locking latch; Dash-mounted cruise control with switches; Turn signal switch with column-mounted dimmer; Standard dash panels include gray w/ burl wood accents; Slate Gray interior primary color; Dark Slate Gray seat color; Floormat; Inside sunvisor, LH/RH; Door courtesy lights; Under-dash center console with 1 cup holder, 1 ashtray & 1 lighter.	8,102
0070004	S	T170 Class 5: medium-duty Conventional.	0
0080050	O	CARB Idle Emissions Reduction Feature for PX-7 and PX-9	0
0090019	S	Class 5 4x2 manual.	0
Engine & Equipment			
0120202	S	PACCAR PX-7 200 2017 200@2400 195@2600 520@1600 Includes turbo exhaust brake, no code is used. Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing. N09260 P14 64....Max Vehicle Speed in Top Gea N09440 P11 NO....Engine Protection Shtdwn N09460 P06 NO....Gear Down Protection N09300 P19 64....Max Cruise Control Speed N09720 P230 YES...Enable Hot Ambient Automatic N09500 P02 NO....Cruise Control Auto Resume N09520 P04 NO....Auto Engine Brake in Cruise N09480 P26 1400..Max PTO Speed N09580 P32 5.....Idle Shtdwn Time N09680 P33 NO....Idle Shtdwn Override N09560 P520 YES...Enable Idle Shutdown Park Br N09600 P233 YES...Enable Impending Shutdown Wa N09780 P47 80....High Ambient Temperature Thr N09740 P46 40....Low Ambient Temperature Thre N09200 N205 120...Standard Maximum Speed Limit N09620 P234 60....Timer For Impending Shutdown N09360 N203 252...Reserve Speed Function Reset N09640 P516 35....Engine Load Threshold N09400 N206 10....Maximum Active Distance (N20 N09420 N201 0.....Reserve Speed Limit Offset (N09760 P56 60....Intermediate Ambient Tempera N09380 N202 0.....Maximum Cycle Distance (N202 N09220 N207 0.....Expiration Distance (N207) N09540 N209 0.....Expiration Distance (N209)	0
1000151	S	PremierSpec	0
1000306	S	T300: 4x2 truck w/hydraulic brakes.	0

Sales Code	Std/ Opt	Description	Weight
1000684		Effective VSL Setting NA	0
1000857	O	Engine Idle Shutdown Timer Enabled	0
1000859	O	Enable EIST Ambient Temp Overrule	0
1000891		Eff EIST NA Expiration Miles	0
1006800	S	Delete air compressor for hydraulic brakes.	0
1031130	S	Air Cleaner: Dry-type firewall mounted w/filter restriction indicator.	0
1105261	S	Fan Hub: Horton On/Off for PX-7	0
1121200	S	Cooling module: 1000 square inches T170/T270/T370/T470. Includes metal surge tank on T170/T270/T370.	0
1247137	S	Exhaust: 2017 EPA Horizontal Under Rail DPF/SCR for PX-7 w/ Horizontal Tailpipe Below RH Rail, BOC.	0
1321109	S	Fuel Filter:PACCAR Standard Service Interval Fuel/Water Separator. 2017 and Later Emissions	0
1321200	O	Run Aid:None *For Fuel Filter	0
1321300	S	Start Aid:None *For Fuel Filter	0
1816160	S	Alternator: 160 amp brush type T3	0
1821220	S	Batteries: 2 PACCAR GP31 threaded post (700-730) 1400-1460 CCA dual purpose.	0
1836107	S	Starter: PACCAR 90P47 12V with PACCAR PX-7	0
Transmission & Clutch			
2050121	S	Transmission: Eaton Fuller FS5406A 6-spd synchro. *Torque Limit: 560 pound-feet.	0
2240001	S	Clutch: ceramic to 605 lb-ft 14 in. Fuller. Includes manual adjusting clutch cover, extended grease fitting for clutch bearing and cross shaft, and synthetic lubricant for the transmission.	0
2406419	O	Driveline: 2 Dana SPL100 1 centerbearing light duty.	-24
Front Axle & Equipment			
2500881	S	Dana Spicer D800F Front Axle rated 8K 3-1/2in. drop, hydraulic brakes.	0
2603007	S	Front brakes included w/ front hub package for hydraulic brakes only. Brakes included w/ front hub package hydraulic brakes only.	0
2702998	S	Front Brake: 8,000 lb. hydraulic brake package 2x66mm. disc brakes, rotors, iron 8-bolt hub pilot hubs, hub caps, oil seals & dust shields. For use w/ 19.5 x 6.75in. wheels.	0

Price Level: January 1, 2019

Deal: HT06 20H3

Printed On: 1/21/2020 10:00:10 AM

Date: January 14, 2020

Quote Number: QUO-493841-C8H1M1

Sales Code	Std/ Opt	Description	Weight
2860007	S	Front Springs: Taperleaf 8K w/ shock absorbers for use on 2010+ T170 chassis only.	0
2895004	S	Single power steering gear: 8K for hydraulic brakes.	0

Rear Axle & Equipment

3001110	S	Single Dana Spicer S14-110 single reduction rear axle for T170 w/ hydraulic brakes. Single rear axle 13.5K capacity rated at 11.5K.	0
3200456	O	Rear Axle Ratio - 4.56.	0
3300001	S	Single rear brakes included w/rear hub package for hydraulic brakes only.	0
3402998	S	18K hydraulic brake package includes 2x66 mm. disc brakes, rotors, iron 8-bolt hub pilot hubs, hub caps, oil seals and dust shields for use w/ 19.5 x 6.75 in. wheels.	0
3485001	S	Bosch Parking Brake 3x12 in. high lever actuated. Axle mounted for medium duty.	0
3495013	S	WABCO 4S/4M anti-lock brake system. T300: w/ hydraulic brakes only. K300 all configurations.	0
3626477	S	Rear suspension: single Reyco 79KB taperleaf 13.5K. Medium-duty. Unladen height: 7.8 in. Laden height: 6.2 in. Not rear air disc brake compatible.	0

Tires & Wheels

4070011	S	Front Tires: Bridgestone R238 245/70R19.5 14PR	0
4270011	S	Rear Tires: Bridgestone R238 245/70R19.5 14PR	0
4900004	O	Rear Tire Quantity: 4	0
5042248	S	Front Wheel: Accuride 50180 19.5x6.75RW steel Steel Armor[™] powder coat, hub-pilot mount. 8-bolt hub pilot mount. 5000lb. maximum rating.	0
5242248	S	Rear Wheel: Accuride 50180 19.5x6.75RW steel Steel Armor powder coat, 8-bolt hub-pilot mount. 5000lb. maximum rating.	0
5853906	O	Powder coat white steel wheel. Use in conjunction with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color.	0
5900004	O	Rear Wheel/Rim Quantity: 4	0

Frame & Equipment

6050605	S	Frame Rails: 9-7/8 x 1/4 in. steel to 308 in. Truck frame weight is 2.10 lb.-in. per pair of rails. Section modulus is 10 cu in, RBM is 1,254,767 lbs. per rail. 120,000 PSI. Heat treated. Frame rail availability may be restricted based upon application, axle/suspension capacity, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application	0
---------	---	---	---

Price Level: January 1, 2019

Deal: HT06 20H3

Printed On: 1/21/2020 10:00:10 AM

Date: January 14, 2020

Quote Number: QUO-493841-C8H1M1

Sales Code	Std/Opt	Description	Weight
		Engineering will advise the dealer of the appropriate material specification for a substitute rail.	
6301210	S	Bumper: Steel painted gray.	0
6319409	S	40.9 in. Bumper setting. Requires a bumper code.	0
6390103	S	Front mudflaps.	0
6404400	S	Battery box: Steel parallel under cab w/ABS cover	0
6409901	S	Battery box location: LH Side.	0
6490122	S	One-piece welded crossmember assembly with 12mm frame fasteners, center and rear frame. Standard crossmember.	0
6742009	S	Square end-of-frame w/o crossmember; non-towing.	0
Fuel Tanks & Equip			
7130045	S	Fuel Tank: 45 US gallon, rectangular steel with step under replacement.	0
7722008	S	Rectangular DEF tank. 7.5 gallons of usable volume. The tank will be located just forward of the under cab component on the side you specified. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	0
7889203	S	DEF to fuel fill ratio 2:1 or greater.	0
7889604	S	DEF tank location is LH.	0
7910045	S	Location: 45 gal fuel tank RH under cab	0
Cab & Equipment			
8024310	S	Cab: Curved Glass Conventional. Cab Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Single electric horn standard. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection (excluding T3 series), short and open check diagnostics. Warning alarm will sound when lights are left on.	0
8090310	S	Hood: Sloped aerodynamic hood includes grill & separate bumper.	0
8108010	S	Cab heater: W/integral defrosters & A/C 45,000 btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control. T660 include filter media.	0
8201201	S	Tilt steering column. Available for T170 Only.	0
8282009	S	Instrument package: Includes speedometer,	0

Sales Code	Std/ Opt	Description	Weight
		tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	
8330014	S	Class 5 interior: Includes cloth headliner & vinyl cab back panel.	0
8412799	S	Dr Seat: Static HB Vinyl With Dual Armrests	0
8480180	S	Rider seat: Kenworth Toolbox Plus IB vinyl. W/dual armrests.	0
8601421	S	Kenworth Radio with AM/FM/WB/USB and Bluetooth	4
8700083	S	Under-dash center console: W/2 cup holders, 1 ashtray, 1 lighter, 1 12V outlet & a storage compartment.	0
8700154	S	Self cancelling turn signal: W/head light dimmer switch .	0
8800200	S	Cab access contoured grabhandles, LH/RH.	0
8832115	S	Daylite Door: LH/RH includes RH peeper window	0
8850210	S	Dual convex mirrors 7-1/2 in. w/ offset mounting, and non-heated.	0
8850300	S	Look-Down, Pass. Door, Stainless 8.5x4.4	0
8862101	S	Mirror: Dual Prutsmann mirror 7 in. x 16 in. polished stainless steel, and non-heated.	0
8869005	S	Mirror brackets 8-1/2 ft load width.	0
8871438	S	Rear Cab Stationary Window 17 in. x 36 in.	0
8879200	S	Manual LH & electric-powered RH door window. Switch located on door.	0
Lights & Instruments			
9010801	S	Headlamps: Halogen Projector Low Beam, Halogen Complex Reflector High Beam	0
9020166	S	Marker Lights: Five cab roof mounted.	0
9030010	S	Turn Signal Lights: Mounted on fender	0
9070138	S	Combination Stop, Tail, Turn & Backup Lights RH & LH.	0
9090845	S	Circuit Breakers: Replacing fuses. Does not apply to any 5-amp fuse box position. Brakers include stop/brake/turn, tail lamp, high & low beams, marker/clearance lamps, horn, fuel heat, gauges, air dryer, HVAC controls, panel lamps. Some circuits will remain fuses.	0



Sales Code	Std/ Opt	Description	Weight
Air Equipment			
Extended Warranty			
9200007	O	Base Warranty - PACCAR PX-7 Engine 36 months / Unlimited miles & km / Unlimited hours.	0
9200022	S	Base Warranty - Standard Service Medium Duty 12 months / Unlimited miles & km	0
Miscellaneous			
9400072	O	Ship to Dealer.	0
9409852	S	GHG Secondary Manufacturer: Does Not Apply	0
Promotions			
Paint			
9700000	O	Paint color number(s). N9702 A - L0006 WHITE N9720 FRAME N0001 BLACK	0
9943050	O	Day Cab Standard Paint	0
9944820	S	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0
9965510	S	Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0
Order Comments			

Total Weight

8,033

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change

Price Level: January 1, 2019

Deal: HT06 20H3

Printed On: 1/21/2020 10:00:10 AM

Date: January 14, 2020

Quote Number: QUO-493841-C8H1M1



without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefor we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information