



CSM - KENWORTH OF SOUTH TEXAS - SAN ANTONIO (F428)
P.O. BOX 200187
SAN ANTONIO, Texas 78220

HGAC
3100 COMMUNICATIONS RD
ST CLOUD, Florida 34769
United States of America

Kristian Martinez
Cell Phone:
Office Phone: 210-662-9333
Email: kristian.martinez@frenchellison.com

Neal Whitty
Office Phone: (713) 499-6693
Email: neal.whitty@h-gac.com

Vehicle Summary

Unit		Chassis	
Model:	T400 Series Conventional.	Fr Axle Load (lbs):	12000
Type:	FULL TRUCK	Rr Axle Load (lbs):	40000
Description 1:	HT06 20H8 T440 TRA	G.C.W. (lbs):	52000
Description 2:	T440, Conventional Cab, SBFA, TRA		
Application		Road Conditions:	
Intended Serv.:	Local pickup & delivery: Vehicles which	Class A (Highway)	90
Commodity:	Other building materials.	Class B (Hwy/Mtn)	10
Body		Class C (Off-Hwy)	0
Type:	Van.	Class D (Off-Road)	0
Length (ft):	10	Maximum Grade:	6
Height (ft):	13	Wheelbase (in):	177
Max Laden Weight (lbs):	4000	Overhang (in):	60
		Fr Axle to BOC (in):	67.4
Trailer		Cab to Axle (in):	109.6
No. of Trailer Axles:	0	Cab to EOF (in):	169.6
Type:		Overall Comb. Length (in):	287
Length (ft):	0	Special Req.	
Height (ft):	0	U.S. Domestic registry, 50-state.	
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	75		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

Sales Code	Std/Opt	Description	Weight
Model			
0000410	S	T400 Series Conventional.	11,518
0070070	O	T440 6x4 Class 8	0
0080050	O	CARB Idle Emissions Reduction Feature for PX-7 and PX-9	0
0090062	O	T440 6x4 Class 8	0
Engine & Equipment			
0129461	S	PACCAR PX-9 260 2017 260@2200 720@1300 Includes turbo exhaust brake, no code is used. Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing. N09260 P14 64....Max Vehicle Speed in Top Gea N09440 P11 NO....Engine Protection Shtdwn N09460 P06 NO....Gear Down Protection N09300 P19 64....Max Cruise Control Speed N09720 P230 YES...Enable Hot Ambient Automatic N09500 P02 NO....Cruise Control Auto Resume N09520 P04 NO....Auto Engine Brake in Cruise N09480 P26 1400..Max PTO Speed N09580 P32 5.....Idle Shtdwn Time N09680 P33 NO....Idle Shtdwn Override N09560 P520 YES...Enable Idle Shutdown Park Br N09600 P233 YES...Enable Impending Shutdown Wa N09780 P47 80....High Ambient Temperature Thr N09740 P46 40....Low Ambient Temperature Thre N09200 N205 120...Standard Maximum Speed Limit N09620 P234 60....Timer For Impending Shutdown N09360 N203 252...Reserve Speed Function Reset N09640 P516 35....Engine Load Threshold N09400 N206 10....Maximum Active Distance (N20 N09420 N201 0.....Reserve Speed Limit Offset (N09760 P56 60....Intermediate Ambient Tempera N09380 N202 0.....Maximum Cycle Distance (N202 N09220 N207 0.....Expiration Distance (N207) N09540 N209 0.....Expiration Distance (N209)	0
1000151	S	PremierSpec	0
1000684		Effective VSL Setting NA	0
1000857	S	Engine Idle Shutdown Timer Enabled	0
1000859	O	Enable EIST Ambient Temp Overrule	0
1000891		Eff EIST NA Expiration Miles	0
1002060	S	Air compressor: Cummins 18.7 CFM For Cummins And	0

Price Level: January 1, 2019

Deal: HT06 20H8 T440 TRA

Printed On: 1/21/2020 10:16:02 AM

Date: January 20, 2020

Quote Number: QUO-494597-W1N6W5

Sales Code	Std/ Opt	Description	Weight
		PACCAR PX engines.	
1051092	S	Engine mount Powercore air cleaner. w/constant torque SS clamps, pop-up air restriction indicator. Pop-up indicator is standard.	0
1105231	S	Fan Hub: Horton On/Off for PX-9 or ISLG	0
1122505	S	Cooling module: 1300 square inches. Includes aluminum radiator core, aluminum charge air cooler, translucent surge tank and washer bottle, silicone hoses, and extended life coolant. Drain valve is not available w/Allison transmissions.	0
1247166	O	Exhaust: 2017 EPA RH Under DPF/SCR w/ RH side of cab vertical tailpipe w/ daycabs, extended daycabs, or modular sleepers.	0
1290124	O	Tailpipe: 5 in. single 24 in. 45 degree curved.	-3
1321145	O	Fuel Filter:Fleetguard FS1003 Fuel/Water Separator for PX-9	0
1321200	O	Run Aid:None *For Fuel Filter	0
1321300	O	Start Aid:None *For Fuel Filter	0
1500029	S	Kenworth Fuel Cooler Required for Cummins engines with a single fuel tank. Required for PACCAR MX-13 engine with a single fuel tank and stationary use: High RPM, low vehicle speed, sustained for longer than 1 hour. Optional for all other applications.	0
1816260	S	Alternator: PACCAR 160 amp, brush type	0
1821220	S	Batteries: 2 PACCAR GP31 threaded post (700-730) 1400-1460 CCA dual purpose.	0
1836106	S	Mitsubishi 105P55 12V Starter with Cummins and PX PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded. Only for Cummins or PX engines.	0
Transmission & Clutch			
2051122	S	Transmission: Fuller FSO8406A 6-speed synchro. *Torque Limit: 860 pound-feet.	0
2240035	S	Clutch: Eaton Fuller 14in. medium-duty manual adjustment 606-1000. Includes manual adjusting clutch cover, extended grease fitting for clutch bearing and cross shaft, and synthetic lubricant for the transmission.	0
2401405	S	Driveline: 2 Dana standard-duty; 1 centerbearing. *Standard duty is 1710 series.	0
2429100	O	Chassis will be fitted w/ LH transmission PTO. (Prevents ECU F/Interfering w/ PTO Only).	0
Front Axle & Equipment			
2512042	S	Meritor MFS12E PLUS 12.5K 3.5in. drop standard	0

Price Level: January 1, 2019

Deal: HT06 20H8 T440 TRA

Printed On: 1/21/2020 10:16:02 AM

Date: January 20, 2020

Quote Number: QUO-494597-W1N6W5

Sales Code	Std/ Opt	Description	Weight
		track	
2621310	O	Front Brakes: 14.6K Bendix ES s-cam 16.5x5 in.	-62
2690002	O	Front Brake Drums: 14.6K 16.5x5 in. cast.	78
2701300	O	Front Hub: aluminum hub pilot 13,200 lbs. 10-Bolt, 11-1/4 in. bolt circle .	0
2741970	S	ConMet PreSet Plus Hub package; front axle.	0
2750001	S	Hubcap: front vented.	0
2765001	O	Front Auto Slack Adjuster.	0
2863012	S	Front Springs: Taperleaf 12K w/ shock absorbers w/ maintenance-free elastomer spring pin bushings. Standard with rubber pins except for C500 which has threaded pins. Not available on W900L.	0
2895121	S	Single power steering gear: 13.2K Sheppard M100P.	0
Rear Axle & Equipment			
3122245	O	Dual Meritor MT40-14X3 Hypoid rear axle rated at 40K. Tandem rear axle.	725
3200411	O	Rear Axle Ratio - 4.11.	0
3334004	O	Dual Rear Brakes 16-1/2x7 in. to 46K; Bendix ES-extended service S-cam.	0
3392005	O	Dual Rear Brake Drums: cast.	0
3407050	O	Dual Rear Hubs: Aluminum hub pilot 46K 11-1/4 in. bolt circle.	0
3441972	O	ConMet PreSet Plus Hub package; dual rear axle.	0
3465002	O	Dual Rear axle automatic slack adjusters.	0
3485207	O	Spring Brake: 3030 long stroke dual 30 square inches travel. Helps keep brakes in adjustment longer.	4
3495226	S	Bendix 4S/4M anti-lock brake system.	0
3500037	O	Interaxle driveline:1 Dana 1710 Series	0
3736418	O	Rear suspension: Tandem Reyco 102 40K. 4-spring multileaf & 52 in. axle spacing. Steel crossmembers & gussets. Unladen Height: 10.8 in. Laden Height: 9.2 in.	500
Tires & Wheels			
4070040	S	Front Tires: Bridgestone R284 Ecopia 295/75R22.5	0
4270040	S	Rear Tires: Bridgestone R284 Ecopia 295/75R22.5 14PR	0

Price Level: January 1, 2019

Deal: HT06 20H8 T440 TRA

Printed On: 1/21/2020 10:16:02 AM

Date: January 20, 2020

Quote Number: QUO-494597-W1N6W5

Sales Code	Std/Opt	Description	Weight
4900008	O	Rear Tire Quantity: 8	0
5042275	O	Front Wheel: Accuride 51408 22.5x8.25 steel Steel Armor[TM] powder coat, hub-pilot mount. 7400lb. maximum rating. 2-hand holes. Air disc brake compatible.	0
5242375	O	Rear Wheel: Accuride 51408 22.5x8.25 steel Steel Armor[TM] powder coat, hub-pilot mount. 7400lb. maximum rating. 2-hand holes. Air disc brake compatible. Code is priced per pair of wheels.	-48
5853906	O	Powder coat white steel wheel. Use in conjunction with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color.	0
5900008	O	Rear Wheel/Rim Quantity: 8	0
Frame & Equipment			
6054400	O	Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to 285 in. to 336 in. Truck frame weight is 2.91 lb.-in. per pair of rails. Section modulus is 14.80, RBM is 1,776,000 in.-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	56
6302460	S	Bumper: Tapered painted steel channel. Requires a bumper setting code.	0
6319050	S	50 in. Bumper setting. Requires a bumper code.	0
6390103	S	Front mudflaps.	0
6390304	S	Brackets, Front Drive: Aluminum up to 15,999 lbs.	0
6405048	S	Battery box module: Short length aluminum parallel under cab, aluminum diamond plate cover w/ step. Up to 2 air tanks may mount to bottom of box. Batteries will be oriented perpendicular on rail.	0
6409901	S	Battery box location: LH Side.	0
6451090	S	T470,C5, T6, T8 non-polished DPF/SCR or CNG cover diamond plate w/ step. For use w/ 2010 or later exhaust systems. For T8, use extended length non-polished battery box on opposite rail to match the length of under cab components. End plates will be painted standard black frame color.	0
6721102	S	Rear mudflap arms: Betts B-25 standard-duty, straight. Includes B1732 mounting brackets as standard.	0
6722000	S	Rear mudflap shields: White plastic antisail w/ Kenworth logo.	0
6742009	S	Square end-of-frame w/o crossmember; non-towing.	0

Sales Code	Std/ Opt	Description	Weight
Fuel Tanks & Equip			
7014056	S	Fuel Tank: 56 US gallon 22in. aluminum BOC replace. Class 8 fuel tank includes an anti-siphon device on the filler neck.	0
7722011	S	Small round DEF tank. 11 gallons of usable volume. The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	0
7889203	S	DEF to fuel fill ratio 2:1 or greater.	0
7889604	S	DEF tank location is LH.	0
7930056	S	Location: 56 gal fuel tank RH behind cab	0
Cab & Equipment			
8024310	S	Cab: Curved Glass Conventional. Cab Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Single electric horn standard. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection (excluding T3 series), short and open check diagnostics. Warning alarm will sound when lights are left on.	0
8090450	S	Hood: Sloped Aerodynamic T440 Hood. Includes hood and mounted grille, split fenders w/ mudflaps, & separate bumper.	0
8108010	S	Cab heater: W/integral defrosters & A/C 45,000 btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control. T660 include filter media.	0
8201013	S	Steering wheel: 18 in. 4-spoke.	0
8201200	S	Adjustable telescoping tilt steering column.	10
8282004	S	KW Driver Information Center: Includes fuel economy, RPM display, trip information, truck information, diagnostics, gear display, alarm clock.	0
8282009	S	Instrument package: Includes speedometer, tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	0
8282107	S	Large flat panel on dash For customer-installed controls. Reduces gauge count by 6.	0
8331140	S	Cab Interior: Summit. T440/T470 Only. Includes	0

Sales Code	Std/ Opt	Description	Weight
		smooth upholstered side & back panels w/stitched accent lines, upholstered door pads, full vinyl headliner, black dash panels & black rubber floor mats.	
8343304	S	Interior color: Slate Gray w/trim Dark Slate Gray	0
8410091	S	Driver seat: Kenworth Air cushion Plus HB cloth. Standard features includes 7 in. fore and aft slide adjustment w/isolator, 6-23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide w/ 2-position tilt and 2-position front cushion extension. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted and includes a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	0
8480090	S	Rider seat: Kenworth Toolbox Plus HB cloth. Standard features include fixed base and backrest, tool box seat base w/ door, and dual armrests. Seat cushion is 19.5 inches. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted with a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	0
8490110	S	Seat color: Dark Slate Gray.	0
8700168	S	Non-self cancelling turn signal: W/column-mounted headlight dimmer switch & intermittent wiper control.	0
8700186	S	Electric LH & RH door locks.	0
8800200	S	Cab access contoured grabhandles, LH/RH.	0
8800400	S	Grabhandle: LH inside door frame above dash.	0
8800401	S	Grabhandle: RH inside door frame above dash.	0
8832115	S	Daylite Door: LH/RH includes RH peeper window	0
8841411	S	Single air horn under cab.	0
8850300	S	Look-Down, Pass. Door, Stainless 8.5x4.4	0
8862101	S	Mirror: Dual Prutsman mirror 7 in. x 16 in. polished stainless steel, and non-heated.	0
8869005	S	Mirror brackets 8-1/2 ft load width.	0
8871438	S	Rear Cab Stationary Window 17 in. x 36 in.	0
8879200	S	Manual LH & electric-powered RH door window. Switch located on door.	0
8890100	S	One-piece windshield, w/ curved glass.	0
Lights & Instruments			
9010801	S	Headlamps: Halogen Projector Low Beam, Halogen Complex Reflector High Beam	0

Sales Code	Std/ Opt	Description	Weight
9020164	S	Marker Lights: with small round base, Five cab roof mounted.	0
9030010	S	Turn Signal Lights: Mounted on fender	0
9070138	S	Combination Stop, Tail, Turn & Backup Lights RH & LH.	0
9090039	S	Marker Lights: Interrupter Switch. Included in Turn Signal For All Models Except T3. The T3 Switch Is In The Dash.	0
9090049	S	Omit Brake Light with Engine Brake. Can only be selected when chassis also has engine brake. Cannot be used with options to delete engine brake.	0
Air Equipment			
9101215	S	Air Dryer Bendix AD-IS heated Puraguard	0
9108001	S	Moisture ejection valve w/ pull cable drain.	0
9140020	S	Nylon air tubing in frame & cab, excluding hoses subject to excessive heat or flexing.	0
Extended Warranty			
9200008	O	Base Warranty - PACCAR PX-9 Engine 24 months / 250,000 miles / 402,336 km / 6250 hours.	0
9200021	O	Base Warranty - Standard Service Heavy Duty 12 months / 100,000 miles / 160,000 km.	0
Miscellaneous			
9400072	O	Ship to Dealer.	0
9409852	O	GHG Secondary Manufacturer: Does Not Apply	0
Promotions			
Paint			
9700000	O	Paint color number(s). N9702 A - L0006 WHITE N9770 BUMPER L0006 WHITE N9720 FRAME N0001 BLACK	0
9943001	S	Bumper Painted Color A	0
9943050	O	Day Cab Standard Paint	0
9944820	O	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0



Sales Code	Std/ Opt	Description	Weight
9965510	S	Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0

Order Comments

Total Weight

12,778

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information