

**HM300-5 ARTICULATED DUMP TRUCK**

F.O.B. U.S STOCKING AREA  
(CE) CONSTRUCTION EQUIPMENT

**Standard Equipment for Base Machine****Engine and Related Components**

Alternator, 90 amp, 24 volt  
Air cleaner, dry type with double elements,  
    precleaner, dust indicator  
Batteries 2x12 volt, 200 Ah  
Battery disconnect switch  
Electronic priming fuel pump  
Engine, Komatsu SAA6D125E-7, 11.0 L displacement  
    direct injection system, Komatsu variable geometry  
    turbocharger, aftercooled, EPA Tier 4 Final emission  
    certified, diesel  
    Gross HP: 333 HP (248 kW) / 2000 RPM  
    Net HP: 325 HP (242 kW) / 2000 RPM  
Full-automatic F6 R2 Transmission  
    with K-ATOMIC shift control  
    with automatic T/C lock-up  
Hydraulic driven cooling fan, for after-cooler  
Hydraulic driven cooling fan, for radiator  
Komatsu diesel particulate filter (KDPF)  
Selective catalytic reduction (SCR) system  
Starting motor, 7.5 kW  
Two mode engine power system (Economy and Power modes)

**Operator Environment**

ROPS cab w/FOPS, Level 2  
    (73 dBA), with viscous mounts support  
12 volt outlet port  
Air conditioner/heater/defroster, electronically controlled  
Ashtray and 12 volt cigarette lighter  
Cup holder  
Electronic hoist control system  
Floor mat  
Radio AM/FM with auxiliary jack  
Rear window guard  
Seat belt, operator's, 3 point, 3" width lap belt  
    2" width shoulder belt, retractable  
Seat, air suspension, heated, reclining (fabric)  
Seat, passenger's, with 3" seat belt  
Secondary engine stop switch  
Tilt and telescopic steering wheel  
Tilt cab arrangement for easy service  
Window, power type, left side  
Window, sliding, right side  
Windshield washer and wiper (front and rear)

**Lighting System**

Back-up light  
Hazard light system  
Headlights, front  
Stop, tail, and turn signal lights, LED  
Working lights, front and side

**Special Arrangements**

Ambient Temperature Range, -20°C (-4°F)  
through +45°C (+113°F) at maximum standard elevation  
of 2,300 meters (7,546 ft.)

**Monitoring System, LCD display****Main Monitor Display**

Clock  
DEF level gauge  
ECO gauge  
Engine coolant temperature  
Engine power mode  
Fuel consumption  
Fuel level gauge  
Odometer  
Payload display  
Retarder oil temperature  
Service meter reading (hour meter)  
Speedometer  
Tachometer  
Torque converter oil temperature  
Transmission shift lever indicator

**Pilot Lights**

Action level monitor  
Auxiliary steering system  
Brake oil pressure  
Dump body float  
Engine preheat  
Hydraulic fan reverse  
Inter-axle differential lock-up  
KDPF Regeneration  
KTCS  
Message indicator for cautions  
Parking brake  
Retarder  
Seat belt caution  
Shift hold  
Transmission lock-up  
Transmission range indicator  
Turn signal

**Other Standard Equipment**

Anchor points, tie off type (ISO 14567)  
Auxiliary steering system, automatic, electric  
Back-up alarm  
Centralized greasing  
Dump counter for body  
Electric pump for hydraulic tilt cab  
Hand rails for platform and ladder  
Heavy duty transmission guard  
Horn, electric  
Hydropneumatic suspension, front and rear  
Interaxle lockup, wet disc clutch type, controlled by KTCS  
Komatsu Traction Control System (KTCS)  
Komtrax Level 5  
Ladders, LH side  
Payload meter with external display lamp  
Provision for tailgate installation  
Rearview Camera with dedicated in cab monitor  
Rearview mirrors, heated, LH and RH  
Retarder, automatic and manual  
Rims for 23.5 x 25 tires (set of 6)  
Underview mirrors, front

HM300-5

CONSIGNMENT ELIGIBILITY:

SP = In an existing spec pattern  
YES = Eligible for consignment (option may or may not need to be removed if machine is moved)  
YES-CSC= Eligible for consignment - DB MUST remove items and be invoiced for them if machine is moved  
NO = Not eligible for consignment - Build to order machine - Invoiced in 90 days  
N/A = Not Applicable

MANUFACTURING FLEX CODE LEAD TIME (Pending option availability):

A = At Order timing - Changes Require C = 1 week  
Machine Reallocation X = At Order Timing - Must Take if O  
B = 2 weeks

INDIVIDUAL ORDER:

Z= Factory Install Only C = Available Loose. May require combination w/ other options  
A = Factory Install or Loose L = Available but may cause long lead time - Contact CSC  
B = Available Loose (May require replacement parts) K = Factory Install or Loose with Komatsu Approval for machine completion

DESCRIPTION	SALES UNIT CODE	CONSIGNMENT ELIGIBILITY	LEAD TIME	FLEX IDI' CODE 3DI	LIST PRICE US DOLLAR
-------------	--------------------	----------------------------	--------------	-----------------------	-------------------------

BASE MACHINE

HM300-5 BASE MACHINE	HM300-5			\$	798,813
----------------------	---------	--	--	----	---------

DESCRIPTION	SALES UNIT CODE	CONSIGNMENT ELIGIBILITY	LEAD TIME	FLEX IDI' CODE RDI	LIST PRICE US DOLLAR
<b>SPEC ARRANGEMENTS</b>					
<b>SPEC ARRANGEMENT A</b>					
HM300-5 BASE MACHINE	HM300-5			\$	798,813
Body, Non-heated, 22.4 cubic yards (17.1 cubic meters)	4HA17AB-C			\$	35,841
SAE 2:1 heaped, unlined floor, with heating channels					
Rims only for 23.5-25 tubeless tires	2HW1925RZ				IN BASE PRICE
* 23.5R25, XADN PLUS, E3, Michelin	2HW2325RAT			\$	51,878
<i>* Only items that can be changed within spec arrangements</i>					
<b>SPEC ARRANGEMENT B</b>					
HM300-5 BASE MACHINE	HM300-5			\$	798,813
Provision for exhaust heating, includes exhaust piping from SCR to body	4HCBH-N			\$	13,485
Body, Non-heated, 22.4 cubic yards (17.1 cubic meters)	4HA17AB-C			\$	35,841
SAE 2:1 heaped, unlined floor, with heating channels					
Rims only for 23.5-25 tubeless tires	2HW1925RZ				IN BASE PRICE
* 23.5R25, XADN PLUS, E3, Michelin	2HW2325RAT			\$	51,878
<i>* Only items that can be changed within spec arrangements</i>					

## HM300-5

DESCRIPTION	SALES UNIT CODE	CONSIGNMENT ELIGIBILITY	LEAD TIME	FLEX IDI' CODE RDI	LIST PRICE US DOLLAR
<b>OPTIONAL EQUIPMENT</b>					
<b>S1 = Mandatory, only 1 sales code can be selected</b>					
<b>N1 = Optional, only 1 sales code can be selected</b>					
<b>NN = Optional, select sales codes as required</b>					
<b>RIMS (SET OF 6) (S1)</b>					
Rims only for 23.5-25 tubeless tires	2HW1925RZ	SP		A Z	IN BASE PRICE
Rims only for 750/65-25 tubeless tires	2HW2425WZ	YES	Contact CSC	X Z \$	16,149
<i>NOTE: When machine is ordered with Rims only for 750/65-25 tires, 2HW2425WZ, then it is required to order 750/65R25, VLT, E3, Bridgestone tires (2HW3065W2T).</i>					
<b>RADIAL TIRES, TIRES ONLY, TUBELESS (Set of 6) (S1)</b>					
23.5R25, VLT, E3, Bridgestone	2HW2325R4T	YES	Contact CSC	X K \$	43,525
23.5R25, XADN PLUS, E3, Michelin	2HW2325RAT	SP		A K \$	51,878
750/65R25, VLT, E3, Bridgestone	2HW3065W2T	YES	Contact CSC	X K \$	59,686
Handling charge to ship with rims only *	2HWLT	YES	Contact CSC	X Z \$	7,441
<i>* Item must be selected when 2XW1925RZ is ordered and no tires are selected.</i>				Subject to change without notice	
<i>NOTE: Please confirm availability of tires before placing order.</i>					
<i>NOTE: When machine is ordered with Rims only, 2HW1925RZ, and tires are purchased and installed locally by the distributor / customer, the tire valve stem assemblies are not included with the Rims. The valve stem assemblies are the responsibility of the distributor.</i>					
<i>NOTE: When machine is ordered with Rims only, 2HW1925RZ, the DB should plan on receiving the unit with exposed metal rims. The DB is responsible for removing the articulated truck from the transportation trailer and should expect to use cranes(s) to accomplish this.</i>					
<i>NOTE: The Bridgestone low profile tire (2HW3065W2T) includes the fenders for the wider tire. If converting an existing machine from standard tires to low profile tires, reference PSN BT18047 for the installation procedure.</i>					
<b>BODY (S1)</b>					
Body, Non-heated, 22.4 cubic yards (17.1 cubic meters)	4HA17AB-C	SP		A K \$	35,841
SAE 2:1 heaped, unlined floor, with heating channels					
Handling charge for truck ordered less-body	4HA999	NO		X Z \$	5,044
<i>NOTE: Non-heated and heated arrangements share a common vessel body with heating channels installed (4HA17AB-C). Heated arrangement requires ordering provision for exhaust heating (4HCBH-N).</i>					
<i>NOTE: For truck ordered less-body (4HA999), submit a SEST for Komatsu review and approval of final truck application. Trucks will ship with hoist cylinders and hydraulics.</i>					
<b>BODY ATTACHMENTS (NN)</b>					
Provision for exhaust heating, includes exhaust piping from SCR to body	4HCBH-N	SP		A Z \$	13,485
Tailgate, scissors type	4HCTG25A-E	YES		B A \$	22,645

DESCRIPTION	SALES UNIT CODE	CONSIGNMENT ELIGIBILITY	LEAD TIME	FLEX IDI' CODE RDI	LIST PRICE US DOLLAR
<b>OPTIONAL EQUIPMENT</b>					
<b>S1 = Mandatory, only 1 sales code can be selected</b>					
<b>N1 = Optional, only 1 sales code can be selected</b>					
<b>NN = Optional, select sales codes as required</b>					
<b>FIELD INSTALLTION ATTACHMENTS (NN)</b>					
Spare rim, 19" for 23.5 x 25 Tire (1 rim only)	SHW1925RZ	N/A	18 WKS	X C \$	4,249
Spare rim, 24" for 30/65 x 25 Tire (1 rim only)	SHW2425WZ	N/A	18 WKS	X C \$	4,930
KOMTRAX Iridium Field Kit (S/N 11136 and after)	6HP11RRC-A	N/A	Contact CSC	X B \$	3,715
Body Heat Conversion Field Kit	7HB990013B	N/A	Contact CSC	X B \$	9,298

*NOTE: KOMTRAX Iridium field kit (6HP11RRC-A) satellite based system is to replace the standard cellular based system.  
It is intended for machines (S/N 11136 and after) operating in remote areas with confirmed, no cellular communication to a machine.  
Reference BT20003 for installation instructions.*

*NOTE: 7HB990013B body heat conversion kit is intended for bodies with existing heating channels  
(includes all exhaust components from SCR to body)*

Field Installed Attachments are not eligible for consignment. The kits arrive separately from the machine and should not be installed on a consignment machine without approval from KAC.

KOMATSU ADVANTAGE EXTENDED COVERAGE is available for this machine.

For other coverage options and current price quotations, visit the ADVANTAGE

Extended Coverage location on Komatsu America International eb site at :

<https://WWW.komatsuamerica.net/>

EFFECTIVE JANUARY 1, 2025

Subject to change without notice

Printed in the United States

HM300-5

Page 5

**ALLIED MANUFACTURER ATTACHMENTS  
FIELD INSTALLATION****HM300-5***ALLIED ATTACHMENTS ARE NOT AVAILABLE FOR CONSIGNMENT**WARRANTY FOR ALLIED ATTACHMENTS IS PROVIDED BY THE INDIVIDUAL ATTACHMENT MANUFACTURER*

DESCRIPTION	SALES UNIT CODE	ADDITIONAL COMMENTS	LEAD TIME	FOB POINT	LIST PRICE US DOLLAR
-------------	--------------------	------------------------	--------------	--------------	-------------------------

**AUTO LUBE SYSTEM - GRACO****ONE STOP SHOP INSTALLED**

G3 Auto Lube System	HM300-5LUBOSS	Auto lube system with G3 pump/ reservoir & GLC 2200 in cab controller	Contact	KAC Stock	\$ 24,112
OSS Installed		OSS Installed	Customer Support	Yard	

**FIELD INSTALLED KITS**

G3 Auto Lube System	HM300-5LUB	Auto lube system with G3 pump/ reservoir & GLC 2200 in cab controller	2 Weeks	Anoka, MN	\$ 15,035
FIK		Field installed kit			

**NOTE 1:** For installation assistance, warranty or technical support contact:

GRACO INC.

TEL: (800) 533-9655 x4

FAX: (800) 533-9656

Field Installed Attachments are not eligible for consignment. The kits arrive separately from the machine and should not be installed on a consignment machine without approval from KAC.

DESCRIPTION	SALES UNIT CODE	ADDITIONAL COMMENTS	FOB POINT	LIST PRICE US DOLLAR
-------------	--------------------	------------------------	--------------	-------------------------

**HM400-5 ARTICULATED DUMP TRUCK**

F.O.B. U.S STOCKING AREA

(CE) CONSTRUCTION EQUIPMENT

**Standard Equipment for Base Machine****Engine and Related Components**

Alternator, 90 amp, 24 volt  
Air cleaner, dry type with double elements,  
precleaner, dust indicator  
Batteries 2x12 volt, 200 Ah  
Battery disconnect switch  
Electronic priming fuel pump  
Engine, Komatsu SAA6D140E-7, 15.2 L displacement  
direct injection system, Komatsu variable geometry  
turbocharger, aftercooled, EPA Tier 4 Final emission  
certified, diesel  
Gross HP: 473 HP (353 kW) / 2000 RPM  
Net HP: 469 HP (350 kW) / 2000 RPM  
Full-automatic F6 R2 Transmission  
with K-ATOMIC shift control  
with automatic T/C lock-up  
Hydraulic driven cooling fan, for after-cooler  
Hydraulic driven cooling fan, for radiator  
Komatsu diesel particulate filter (KDPF)  
Selective catalytic reduction (SCR) system  
Starting motor, 11.0 kW  
Two mode engine power system (Economy and Power modes)

**Operator Environment**

ROPS cab w/FOPS, Level 2  
(76 dBA), with viscous mounts support  
12 volt outlet port  
Air conditioner/heater/defroster, electronically controlled  
Ashtray and 12 volt cigarette lighter  
Cup holder  
Electronic hoist control system  
Floor mat  
Radio AM/FM with auxiliary jack  
Rear window guard  
Seat belt, operator's, 3 point, 3" width lap belt,  
2" width shoulder belt, retractable  
Seat, air suspension, heated, reclining (fabric)  
Seat, passenger's, with 3" seat belt  
Secondary engine stop switch  
Tilt and telescopic steering wheel  
Tilt cab arrangement for easy service  
Window, power type, left side  
Window, sliding, right side  
Windshield washer and wiper (front and rear)

**Lighting System**

Back-up light  
Hazard light system  
Headlights, front  
Stop, tail, and turn signal lights, LED  
Working lights, front and side

**Special Arrangements**

Ambient Temperature Range, -20°C (-4°F)  
through +45°C (+113°F) at maximum standard elevation  
of 2,300 meters (7,546 ft.)

**Monitoring System, LCD display****Main Monitor Display**

Clock  
DEF level gauge  
ECO gauge  
Engine coolant temperature  
Engine power mode  
Fuel consumption  
Fuel level gauge  
Odometer  
Payload display  
Retarder oil temperature  
Service meter reading (hour meter)  
Speedometer  
Tachometer  
Torque converter oil temperature  
Transmission shift lever indicator

**Pilot Lights**

Action level monitor  
Auxiliary steering system  
Brake oil pressure  
Dump body float  
Engine preheat  
Hydraulic fan reverse  
Inter-axle differential lock-up  
KDPF Regeneration  
KTCS  
Message indicator for cautions  
Parking brake  
Retarder  
Seat belt caution  
Shift hold  
Transmission lock-up  
Transmission range indicator  
Turn signal

**Other Standard Equipment**

Anchor points, tie off type (ISO 14567)  
Auxiliary steering system, automatic, electric  
Back-up alarm  
Centralized greasing  
Dump counter for body  
Electric pump for hydraulic tilt cab  
Hand rails for platform and ladder  
Heavy duty transmission guard  
Horn, electric  
Hydropneumatic suspension, front and rear  
Interaxle lockup, wet disc clutch type, controlled by KTCS  
Komatsu Traction Control System (KTCS)  
Komtrax Level 5  
Ladders, LH side  
Payload meter with external display lamp  
Provision for tailgate installation  
Rearview Camera with dedicated in cab monitor  
Rearview mirrors, heated, LH and RH  
Retarder, automatic and manual  
Rims for 29.5 x 25 tires (set of 6)  
Underview mirrors, front

HM400-5

CONSIGNMENT ELIGIBILITY:

SP = In an existing spec pattern  
YES = Eligible for consignment (option may or may not need to be removed if machine is moved)  
YES-CSC= Eligible for  
NO = Not eligible for consignment - Build to order machine - Invoiced in 90 days  
N/A = Not Applicable

MANUFACTURING FLEX CODE LEAD TIME (Pending option availability):

A = At Order timing - Changes Require      C = 1 week  
Machine Reallocation      X = At Order Timing - Must Take if Ordered  
B = 2 weeks

INDIVIUDUAL ORDER:

Z= Factory Install Only      C = Available Loose. May require combination w/ other options  
A = Factory Install or Loose      L = Available but may cause long lead time - Contact CSC  
B = Available Loose      K = Factory Install or Loose with Komatsu Approval for  
(May require replacement parts)      machine completion

DESCRIPTION	SALES UNIT CODE	CONSIGNMENT ELIGIBILITY	LEAD TIME	FLEX CODE	INDIV. ORDER	LIST PRICE US DOLLAR
-------------	--------------------	----------------------------	--------------	--------------	-----------------	-------------------------

BASE MACHINE

HM400-5 BASE MACHINE	HM400-5					\$ 1,128,723
----------------------	---------	--	--	--	--	--------------

DESCRIPTION	SALES UNIT CODE	CONSIGNMENT ELIGIBILITY	LEAD TIME	FLEX CODE	INDIV. ORDER	LIST PRICE US DOLLAR
-------------	--------------------	----------------------------	--------------	--------------	-----------------	-------------------------

**SPEC ARRANGEMENTS****SPEC ARRANGEMENT A**

HM400-5 BASE MACHINE	HM400-5					\$ 1,128,723
Body, Non-heated, 31.4 cubic yards (24 cubic meters)	4HA24AA-C					\$ 47,810
SAE 2:1 heaped, unlined floor, with heating channels						
Rims only for 29.5-25 tubeless tires (5-piece)	2HW2525RY					IN BASE
* 29.5R25, XADN Plus, E3, Michelin	2HW2925RET					\$ 98,573

*\* Only items that can be changed within spec arrangements*

**SPEC ARRANGEMENT B**

HM400-5 BASE MACHINE	HM400-5					\$ 1,128,723
Provision for exhaust heating, includes exhaust piping from SCR to body	4HCBH-M					\$ 18,090
Body, Non-heated, 31.4 cubic yards (24 cubic meters)	4HA24AA-C					\$ 47,810
SAE 2:1 heaped, unlined floor, with heating channels						
Rims only for 29.5-25 tubeless tires (5-piece)	2HW2525RY					IN BASE
* 29.5R25, XADN Plus, E3, Michelin	2HW2925RET					\$ 98,573

*\* Only items that can be changed within spec arrangements*

**HM400-5**

DESCRIPTION	SALES UNIT CODE	CONSIGNMENT ELIGIBILITY	LEAD TIME	FLEX CODE	INDIV. ORDER	LIST PRICE US DOLLAR
-------------	--------------------	----------------------------	--------------	--------------	-----------------	-------------------------

**OPTIONAL EQUIPMENT**

**S1 = Mandatory, only 1 sales code can be selected**

**N1 = Optional, only 1 sales code can be selected**

**NN = Optional, select sales codes as required**

**RIMS (SET OF 6) (S1)**

Rims only for 29.5-25 tubeless tires (5-piece)	2HW2525RY	SP		X	Z	IN BASE
Rims only for 875/65-R29 tubeless tires	2HW2729WZ	NO	18 Weeks	X	Z	\$ 33,709

**RADIAL TIRES, TIRES ONLY, TUBELESS (Set of 6) (S1)**

29.5R25 VLT, E3, Bridgestone	2HW2925R3T	YES		A	K	\$ 92,908
29.5R25 XADN Plus, E3, Michelin	2HW2925RET	SP		A	K	\$ 98,573
875/65R29 CRXAD, E3, Michelin	2HW8765W2T	YES	18 Weeks	X	Z	\$ 122,824
Handling charge to ship with rims only*	2HWLT					\$ 9,560

\* Item must be selected when 2HW2525RY or 2HW2729WZ is ordered and no tires are selected.

Note: Please confirm availability of tires before placing order.

Note: When machine is ordered with Rims only (2HW2525RY or 2HW2729WZ) and tires are purchased and installed locally by the distributor / customer, the tire valve stem assemblies are not included with the rims. The valve stem assemblies are the responsibility of the distributor.

Note: When machine is ordered with Rims only (2HW2525RY or 2HW2729WZ) the DB should plan on receiving the unit with exposed metal rims. The DB is responsible for removing the articulated truck from the transportation trailer and should expect to use cranes to accomplish this.

Note: Rims only (2HW2525RY or 2HW2729WZ) orders are not available from CMO-sourced machines.

**BODY (S1)**

Body, Non-heated, 31.4 cubic yards (24 cubic meters)	4HA24AA-C	SP		A	K	\$ 47,810
SAE 2:1 heaped, unlined floor, with heating channels						
Handling charge for truck ordered less-body	4HA999	NO		X	Z	\$ 5,044

NOTE: Non-heated and heated arrangements share a common vessel body with heating channels installed (4HA24AA-C). Heated arrangement requires ordering provision for exhaust heating (4HCBH-M).

NOTE: For truck ordered less-body (4HA999), submit a SEST for Komatsu review and approval of final truck application. Trucks will ship with hoist cylinders and hydraulics.

**BODY ATTACHMENTS (NN)**

Provision for exhaust heating, includes exhaust piping from SCR to body	4HCBH-M	SP		A	Z	\$ 18,090
Tailgate, scissors type	4HCTG25A-F	YES		B	A	\$ 34,064

**HM400-5**

DESCRIPTION	SALES UNIT CODE	CONSIGNMENT ELIGIBILITY	LEAD TIME	FLEX CODE	INDIV. ORDER	LIST PRICE US DOLLAR
<b>OPTIONAL EQUIPMENT</b>						
S1 = Mandatory, only 1 sales code can be selected						
N1 = Optional, only 1 sales code can be selected						
NN = Optional, select sales codes as required						
<b>FIELD INSTALLTION ATTACHMENTS (NN)</b>						
Spare Rim, for 29.5 x 25 Tire (single rim)	7HB997025A	N/A	18 Weeks	X	B	\$ 4,115
KOMTRAX Iridium Field Kit (S/N 11637 and after)	6HP11RRC-A	N/A	Contact CSC	X	B	\$ 3,938
Body Heat Conversion Field Kit (Channeled Body)	7HB990013A	N/A	Contact CSC	X	B	\$ 12,084
Body Heat Conversion Field Kit	7HB992026C	N/A	Contact CSC	X	B	\$ 12,346

NOTE: KOMTRAX Iridium field kit (6HP11RRC-A) satellite based system is to replace the standard cellular based system.  
It is intended for machines (S/N 11637 and after) operating in remote areas with confirmed, no cellular communication to a machine.  
Reference BT20003 for installation instructions.

NOTE: Body heat conversion kits are available for vessels with heating channels and no heating channels

7HB990013A body heat conversion kit is intended for bodies with existing heating channels  
(includes all exhaust components from SCR to body)

7HB992026C body heat conversion kit is intended for bodies with no existing channels  
(includes all exhaust components from SCR to body and body channels)

Field Installed Attachments are not eligible for consignment. The kits arrive separately from the machine and should not be installed on a consignment machine without approval from KAC.

KOMATSU ADVANTAGE EXTENDED COVERAGE is available for this machine.

For other coverage options and current price quotations, visit the ADVANTAGE

Extended Coverage location on Komatsu America International web site at:

<https://www.komatsuamerica.net/>

EFFECTIVE JANUARY 1, 2025

Subject to change without notice

Printed in the United States

HM400-5

Page 5

**ALLIED MANUFACTURER ATTACHMENTS  
FIELD INSTALLATION****HM400-5***ALLIED ATTACHMENTS ARE NOT AVAILABLE FOR CONSIGNMENT**WARRANTY FOR ALLIED ATTACHMENTS IS PROVIDED BY THE INDIVIDUAL ATTACHMENT MANUFACTURER*

DESCRIPTION	SALES UNIT CODE	ADDITIONAL COMMENTS	LEAD TIME	FOB POINT	LIST PRICE US DOLLAR
-------------	--------------------	------------------------	--------------	--------------	-------------------------

**AUTO LUBE SYSTEM - GRACO****ONE STOP SHOP INSTALLED**

G3 Auto Lube System	HM400-5LUBOSS	Auto lube system with G3 pump/ reservoir & GLC 2200 in cab controller	Contact	KAC Stock	\$ 25,730
OSS Installed		OSS Installed	Customer Support	Yard	

**FIELD INSTALLED KITS**

G3 Auto Lube System	HM400-5LUB	Auto lube system with G3 pump/ reservoir & GLC 2200 in cab controller	2 Weeks	Anoka, MN	\$ 16,044
FIK		Field installed kit			

**NOTE 1:** For installation assistance, warranty or technical support contact:

GRACO INC.

TEL: (800) 533-9655 x4

FAX: (800) 533-9656

Field Installed Attachments are not eligible for consignment. The kits arrive separately from the machine and should not be installed on a consignment machine without approval from KAC.

EFFECTIVE JANUARY 1, 2025

Subject to change without notice

Printed in the United States

HM400-5

Page 6

DESCRIPTION	SALES UNIT CODE	ADDITIONAL COMMENTS	FOB POINT	LIST PRICE US DOLLAR
-------------	--------------------	------------------------	--------------	-------------------------