

TAKEUCHI®

2025 MACHINE PRICE LIST

519 Bonnie Valentine Way, Pendergrass, GA 30567

e-mail sales@takeuchi-us.com
www.takeuchi-us.com

Prices and specifications
subject to change without notice

Prices are F.O.B. Pendergrass, GA
Effective 1 January 2025
Revised 07/01/2025



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725
www.takeuchi-us.com

TB210R

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 2,535 lbs.	ROPS/TOPS 2 post foldable canopy
Width: 29.5" / 40.2"	Hydraulically retractable track frame
Maximum Dig Depth: 5' 9.1"	Adjustable width dozer blade with 2 pin-on extensions
Bucket Digging Force: 2,518 lbs.	Pilot operated joystick controls with safety lock out
Horsepower / RPM: 11.7 / 2,200	Pattern change valve
Travel Speed: 1.2 / 2.3 mph	Two-way auxiliary hydraulic circuit routed to the end of the arm
Auxiliary Flow: 5.9 gpm	Adjustable seat with 2" retractable seat belt
Boom swing: Left 85° / Right 85°	Two speed travel
7.1" wide rubber tracks	Travel alarm
	Boom mounted work light
	Horn
	Cast iron, wrap around counterweight

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB210R	TB210R Equipped with ROPS/TOPS 2-post foldable canopy, Rubber tracks, Travel alarm, Auxiliary hydraulics	\$29,229

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB00708	8" Bucket with teeth, .8 cu. ft. capacity	\$430.92
BTB00712	12" Bucket with teeth, 1.1 cu. ft. capacity	\$498.18

FIELD INSTALLED OPTIONS

0333400003	3" Non Retractable seat belt in lieu of standard 2"	\$174.11
------------	---	-----------------



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB216

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 3,900 lbs.	ROPS/TOPS/OPG 4 post canopy
Width: 38.6" / 51.2"	LCD gauge panel with multi-functional operator information center
Maximum Dig Depth: 7' 10"	Hydraulically retractable track frame
Bucket Digging Force: 4,250 lbs.	Travel alarm
Horsepower / RPM: 15 / 2,400	Two-speed travel with automatic down shift
Travel Speed: 1.4 / 2.6 mph	Pattern selector valve
Auxiliary Flow: 8.9 gpm	Pilot operated joystick controls with safety lock out
Boom swing: Left 80°/ Right 50°	Cast iron, wrap around counterweight
9" wide rubber tracks	Adjustable suspension seat with 2" retractable seat belt
Long Arm w/ integrated thumb mount	Two-way auxiliary hydraulic circuit routed to the end of the arm
	Variable displacement axial piston main hydraulic pumps
Electronic engine monitoring system	Adjustable width dozer blade
TFM hardware standard equipment, service included through the standard warranty period (sn 216101378 ~)	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB216R	TB216 Equipped with ROPS/TOPS/OPG canopy, Rubber tracks	\$38,413

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB01608	8" Pin-On Bucket with teeth, 1.1 cu. ft. capacity	\$551.30
BTB01612	12" Pin-On Bucket with teeth, 1.5 cu. ft. capacity	\$688.90
BTB01618	18" Pin-On Bucket with teeth, 2.4 cu. ft. capacity	\$808.76
BTB01624	24" Pin-On Bucket with teeth, 3.2 cu. ft. capacity	\$852.15
BQC01600	Quick Coupler	\$1,073.88
BQC01612	12" Quick Coupler Bucket with teeth, 1.5 cu. ft. capacity	\$688.90
BQC01618	18" Quick Coupler Bucket with teeth, 2.4 cu. ft. capacity	\$808.76
BQC01624	24" Quick Coupler Bucket with teeth, 3.2 cu. ft. capacity	\$852.15
BQC01624D	24" Quick Coupler Ditch Bucket, 3.0 cu. ft. capacity	\$1,045.70
ATH216I	INSTALLED Hydraulic thumb (Only compatible w/ 12" or larger Buckets)	\$2,493.18

FIELD INSTALLED OPTIONS

1914199048	3" Non-retractable seat belt in lieu of standard 2"	\$72.63
ATH216K	Hydraulic thumb (Only compatible with 12" and larger buckets)	\$2,243.18



519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

TB216H

Hybrid Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 4,277 lbs.	LCD gauge panel with multi-functional operator information center
Width: 38.6" / 51.2"	Hydraulically retractable track frame
Maximum Dig Depth: 7' 10"	Travel alarm
Bucket Digging Force: 4,250 lbs.	Two-speed travel with automatic down shift
Horsepower / RPM: 15 / 2,400 (diesel)	Pattern selector valve
14.2 / 2,400 (electric)	Pilot operated joystick controls with safety lock out
Travel Speed: 1.4 / 2.6 mph	Cast iron, wrap around counterweight
Auxiliary Flow: 8.9 gpm	Adjustable suspension seat with 2" retractable seat belt
Boom swing: Left 80°/ Right 50°	Two-way auxiliary hydraulic circuit routed to the end of the arm
9" wide rubber tracks	Variable displacement axial piston main hydraulic pumps
Long Arm w/ integrated thumb mount	Adjustable width dozer blade
ROPS/TOPS/OPG 4 post canopy	Electronic engine monitoring system
TFM hardware standard equipment, service included through the standard warranty period (sn 216101378 ~)	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB216RH	TB216 Equipped with ROPS/TOPS/OPG canopy, Rubber tracks, diesel engine/electric motor	\$61,719

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB01608	8" Pin-On Bucket with teeth, 1.1 cu. ft. capacity	\$551.30
BTB01612	12" Pin-On Bucket with teeth, 1.5 cu. ft. capacity	\$688.90
BTB01618	18" Pin-On Bucket with teeth, 2.4 cu. ft. capacity	\$808.76
BTB01624	24" Pin-On Bucket with teeth, 3.2 cu. ft. capacity	\$852.15
BQC01600	Quick Coupler	\$1,073.88
BQC01612	12" Quick Coupler Bucket with teeth, 1.5 cu. ft. capacity	\$688.90
BQC01618	18" Quick Coupler Bucket with teeth, 2.4 cu. ft. capacity	\$808.76
BQC01624	24" Quick Coupler Bucket with teeth, 3.2 cu. ft. capacity	\$852.15
BQC01624D	24" Quick Coupler Ditch Bucket, 3.0 cu. ft. capacity	\$1,045.70
ATH216I	INSTALLED Hydraulic thumb (Only compatible w/ 12" or larger Buckets)	\$2,493.18

FIELD INSTALLED OPTIONS

1914199048	3" Non-retractable seat belt in lieu of standard 2"	\$72.63
ATH216K	Hydraulic thumb (Only compatible with 12" and larger buckets)	\$2,243.18
TP-84-MTF-0252-01	8/4 PLUG-CONNECTOR 25' Cable	\$979.00
TP-84-MTF-0502-01	8/4 PLUG-CONNECTOR 50' Cable	\$1,155.00

** All TB216H's purchased for use in Canada must have a CSA (Canadian Standards Association) inspection on the electrical components prior to retail sale or rental. Canadian Dealer's and Direct Accounts are responsible for scheduling this inspection and any associated costs/fees. Inspection services are available throughout Canada. If you have questions concerning CSA inspections you may go to their website: <https://www.csagroup.org> or contact the CSA Group (Product Evaluation) at 888.273.3335. **



519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

TB20e

Battery Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 4,255 lb	High resolution multifunction color monitor
Width: 38.6" / 51.2"	Hydraulically retractable track frame
Maximum Dig Depth: 7' 10"	Travel alarm
Bucket Digging Force: 4,226 lb	Two-speed travel with automatic down shift
Lithium Ion Battery 24.7 kWh	Pattern selector via monitor panel
Travel Speed: 1.3 / 2.5 mph	EH joystick controls with safety lock out
Auxiliary Flow: 9.0 gpm	Cast iron, wrap around counterweight
Boom swing: Left 78°/ Right 49°	Adjustable suspension seat with 2" retractable seat belt
9" wide rubber tracks	Two-way auxiliary hydraulic circuit routed to the end of the arm
Long Arm w/ integrated thumb mount	Two Motor-linked fixed displacement gear pumps
Electronic monitoring system	Adjustable width dozer blade
ROPS/TOPS/OPG 4 post canopy	
TFM hardware standard equipment, service included through the standard warranty period (sn 120000010~)	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB20e	TB20e Battery Excavator Equipped with ROPS/TOPS/OPG canopy, Rubber tracks	\$81,370

NOTE: Unit does not come with a charge cable, see below for a basic cable or one can be made locally

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB01608	8" Pin-On Bucket with teeth, 1.1 cu. ft. capacity	\$551.30
BTB01612	12" Pin-On Bucket with teeth, 1.5 cu. ft. capacity	\$688.90
BTB01618	18" Pin-On Bucket with teeth, 2.4 cu. ft. capacity	\$808.76
BTB01624	24" Pin-On Bucket with teeth, 3.2 cu. ft. capacity	\$852.15
BQC01600	Quick Coupler	\$1,073.88
BQC01612	12" Quick Coupler Bucket with teeth, 1.5 cu. ft. capacity	\$688.90
BQC01618	18" Quick Coupler Bucket with teeth, 2.4 cu. ft. capacity	\$808.76
BQC01624	24" Quick Coupler Bucket with teeth, 3.2 cu. ft. capacity	\$852.15
BQC01624D	24" Quick Coupler Ditch Bucket, 3.0 cu. ft. capacity	\$1,045.70
ATH216I	INSTALLED Hydraulic thumb (Only compatible w/ 12" or larger Buckets)	\$2,493.18

FIELD INSTALLED OPTIONS

1914199048	3" Non-retractable seat belt in lieu of standard 2"	\$72.63
ATH216K	Hydraulic thumb (Only compatible with 12" and larger buckets)	\$2,243.18
TB20ECHR	480V Quick Charger	\$6,400.00
TP-103-PPT-0252-01	Charging Cable 25' with 110v plug	\$518.82

NOTE: TB20E is not available for Canada customers currently.



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB225

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 4,993 lbs.	ROPS/FOPS/OPG Level 1
Width: 3' 7.3" / 4' 11"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 8' 5.5"	Suspension seat with fore/aft, tilt, and weight adjustments
Bucket Digging Force: 4,339 lbs.	Pilot operated joystick controls with pattern change valve
Horsepower / RPM: 19.6 / 2,400	EPA Tier 4 Final Engine
Travel Speed: 1.6 / 2.6 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 9.96 gpm	High capacity radiator and hydraulic oil cooler
Boom Swing: Left 75° / Right 55°	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode
Track Width: 9.8"	Safety features include: Travel alarm, retractable seat belt control lockout, pilot accumulator, and lights
Automatic load sensing two speed travel	Variable displacement axial piston pump
Reinforced arm w/ Integrated thumb mount	Auto Idle
Backfill blade with extensions	
TFM hardware standard equipment, service included through the standard warranty period	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB225R	TB225 Canopy Equipped with Rubber	\$45,291

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB12512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	\$778.05
BTB12518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	\$884.93
BTB12524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	\$999.50
BQC12500	Quick Coupler	\$1,073.88
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	\$778.05
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	\$807.98
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	\$884.93
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	\$999.50
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	\$1,503.44
ATH225I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	\$2,407.68

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
ATH225K	Hydraulic thumb (Only compatible with 13" and larger buckets)	\$2,157.68



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB230

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 6,360 lbs.	TOPS/ROPS/OPG 4 post canopy
Width: 4' 9.5"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 9' 3.6"	High back adjustable suspension seat
Bucket Digging Force: 6,471 lbs.	Pilot operated joystick control with pattern change valve
Horsepower / RPM: 24.4 / 2,400	EPA Final Tier 4 compliant engine with engine monitoring system
Travel Speed: 1.8 / 3.2 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 13.4 gpm	High capacity radiator and hydraulic oil cooler
Boom Swing: Left 79° / Right 58°	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system,
Track Width: 11.8"	proportional slide switch, one-way mode and continuous detent mode
	Safety features include: Travel alarm, retractable seat belt
Two speed travel with automatic shift down	control lockout, pilot accumulator, and lights
Reinforced arm w/ Integrated thumb mount	Variable displacement axial piston pump
Heavy duty dozer blade with float	Auto Idle
TFM hardware standard equipment, service included through the standard warranty period (sn 13000923 ~)	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB230R	TB230 Canopy Equipped with Rubber Tracks	\$49,752
TB230S	TB230 Canopy Equipped with Steel Tracks	\$50,697
TB230RA (w/Angle Blade)	TB230 Canopy (Rubber Track) with Angle Blade *Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$53,098
TB230SA (w/Angle Blade)	TB230 Canopy (Steel Track) with Angle Blade *	\$54,043

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB12512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	\$778.05
BTB12518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	\$884.93
BTB12524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	\$999.50
BQC12500	Quick Coupler	\$1,073.88
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	\$778.05
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	\$807.98
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	\$884.93
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	\$999.50
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	\$1,503.44
ATH230I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	\$2,407.68

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
ATH230K	Hydraulic thumb (Only compatible with 13" and larger buckets)	\$2,157.68

Prices are F.O.B. Pendergrass, GA
Effective 1 January 2025
Revised 07-01-2025



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB235-2

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 7,418 lbs.	TOPS/ROPS/OPG 4 post canopy
Width: 5' 2.2"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 10' 7.8"	High back adjustable suspension seat
Bucket Digging Force: 9,127 lbs.	Pilot operated joystick control with pattern change valve
Horsepower / RPM: 24.4 / 2,400	EPA Final Tier 4 compliant engine and engine monitoring system
Travel Speed: 1.7 / 2.8 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 15.8 gpm	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system,
Boom Swing: Left 70° / Right 55°	proportional slide switch, one-way mode and continuous detent mode
Track width: 11.8"	Safety features include: travel alarm, retractable seat belt,
	control lockout, pilot accumulator, and lights
Two speed travel with automatic shift down	Variable displacement axial piston pump
Reinforced arm w/ Integrated thumb mount	Auto Idle
Heavy duty dozer blade with float	
TFM hardware standard equipment, service included through the standard warranty period	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB235-2R	TB235-2 Canopy Equipped with Rubber Tracks	\$56,098
TB235-2RA (w/Angle Blade)	TB235-2 Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$59,747

TB235-2CR	TB235-2 Cab Equipped with Rubber TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet	\$64,719
TB235-2CRA (w/ Angle Blade)	TB235-2 Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$68,368

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB13512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	\$778.05
BTB13518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	\$884.93
BTB13524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	\$999.50
BQC13500	Quick Coupler	\$1,073.88
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	\$778.05
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	\$807.98
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	\$884.93
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	\$999.50
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	\$1,503.44
ATH235-2I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	\$2,407.68

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
ATH235-2K	Hydraulic thumb (Only compatible with 13" and larger buckets)	\$2,157.68



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB335R

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 7,970 lbs.	TOPS/ROPS/OPG 4 post canopy
Width: 5' 8.5"	Multifunction color display panel, 4.3" (Canopy) 7" (Cab)
Maximum Dig Depth: 10' 6.2"	High back adjustable suspension seat
Bucket Digging Force: 9,127 lbs.	Pilot operated joystick control with pattern change valve
Horsepower / RPM: 24.4 / 2,300	EPA Final Tier 4 compliant engine and engine monitoring system
Travel Speed: 1.9 / 2.5 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 17.0 gpm	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system,
Boom Swing: Left 70o/ Right 55o	proportional slide switch, one-way mode and continuous detent mode
Track width: 11.8"	Safety features include: travel alarm, retractable seat belt,
	control lockout, pilot accumulator, and LED work lights
Two speed travel with automatic shift down	Variable displacement axial piston pump
Reinforced arm w/ Integrated thumb mount	Auto Idle
Heavy duty dozer blade with float	
TFM hardware standard equipment, service included through the standard warranty period	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB335R-R	TB335R Canopy Equipped with Rubber Tracks Four post TOPS/ROPS/OPG canopy, 12v power outlet, 1st aux circuit only	\$59,463
TB335R-RA (w/Angle Blade)	TB335R Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$63,333
TB335R-CR	TB335R Cab Equipped with Rubber TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet, 1st and 3rd aux circuits	\$68,603
TB335R-CRA (w/ Angle Blade)	TB335R Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$72,470

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB13512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	\$778.05
BTB13518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	\$884.93
BTB13524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	\$999.50
BQC13500	Quick Coupler	\$1,073.88
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	\$778.05
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	\$807.98
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	\$884.93
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	\$999.50
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	\$1,503.44
ATH235-2I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	\$2,407.68

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
ATH235-2K	Hydraulic thumb (Only compatible with 13" and larger buckets)	\$2,157.68



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725
www.takeuchi-us.com

TB240

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 8,570 lbs.	TOPS/ROPS/OPG 4 post canopy
Width: 5' 8.5"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 11' 4.4"	High back adjustable suspension seat
Bucket Digging Force: 9,959 lbs.	Pilot operated joystick control with pattern change valve
Horsepower / RPM: 35.8 / 2,200	EPA Final Tier 4 compliant engine with DPF and engine monitoring system
Travel Speed: 1.8 / 3.3 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 17.1 gpm	Side by side industrial type radiator and hydraulic oil cooler
Boom Swing: Left 76° / Right 58°	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode
Track width: 13.8"	Safety features include: Travel alarm, retractable seat belt control lockout, pilot accumulator, and lights
Two speed travel with automatic shift down	Variable displacement axial piston pump
Reinforced arm w/ Integrated thumb mount	Auto Idle
Heavy duty dozer blade with float	
TFM hardware standard equipment, service included through the standard warranty period (Canopy: sn 124001379~ / Cab: sn 124001483-	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB240R	TB240 Canopy Equipped with Rubber Tracks	\$63,562
TB240S	TB240 Canopy Equipped with Steel Tracks	\$64,498
TB240RA (w/Angle Blade)	TB240 Canopy (Rubber Tracks) with Angle Blade *Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$67,177
TB240SA (w/Angle Blade)	TB240 Canopy (Steel Tracks) with Angle Blade *	\$68,101
<hr/>		
TB240CR	TB240 Cab Equipped with Rubber Tracks ** TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet	\$72,404
TB240CS	TB240 Cab Equipped with Steel Tracks **	\$73,340
TB240CRA (w/ Angle Blade)	TB240 Cab (Rubber Tracks) with Angle Blade ***Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$76,019
TB240CSA (w/ Angle Blade)	TB240 Cab (Steel Tracks) with Angle Blade	\$76,954

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB13512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	\$778.05
BTB13518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	\$884.93
BTB13524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	\$999.50
BQC13500	Quick Coupler	\$1,073.88
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	\$778.05
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	\$807.98
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	\$884.93
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	\$999.50
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	\$1,503.44
ATH240I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	\$2,407.68

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
ATH240K	Hydraulic thumb (Only compatible with 13" and larger buckets)	\$2,157.68



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725
www.takeuchi-us.com

TB250-2

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 10,737 lbs. Width: 6' 0" Maximum Dig Depth: 12' 4.8" Bucket Digging Force: 10,430 lbs. Horsepower / RPM: 39 / 2,400 Travel Speed: 1.6 / 2.6 mph Auxiliary Flow: 24 gpm Track width: 15.7"	TOPS/ROPS/OPG 4 post canopy Color gauge panel with multi-function operator information center High back adjustable suspension seat Pilot operated joystick control with pattern change valve EPA Final Tier 4 compliant engine with DPF and engine monitoring system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door Side by side industrial type radiator and hydraulic oil cooler Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode Safety features include: Travel alarm, retractable seat belt, control lockout, pilot accumulator, and lights Variable displacement axial piston pump Auto Idle
Two speed travel with automatic shift down Reinforced arm w/ Integrated thumb mount Heavy duty dozer blade with float TFM hardware standard equipment, service included through the standard warranty period	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB250-2R	TB250-2 Canopy Equipped with Rubber Tracks	\$76,765
TB250-2S	TB250-2 Canopy Equipped with Steel Tracks	\$77,946
TB250-2RA (w/Angle Blade)	TB250-2 Canopy (Rubber Track) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$80,425
TB250-2SA (w/Angle Blade)	TB250-2 Canopy (Steel Track) with Angle Blade	\$81,607
TB250-2CR	TB250-2 Cab Equipped with Rubber Tracks TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet	\$83,851
TB250-2CS	TB250-2 Cab Equipped with Steel Tracks	\$85,032
TB250-2CRA (w/ Angle Blade)	TB250-2 Cab (Rubber Track) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$87,512
TB250-2CSA (w/ Angle Blade)	TB250-2 Cab (Steel Track) with Angle Blade	\$88,692

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB14512	12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity	\$1,131.17
BTB14518	18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity	\$1,254.00
BTB14524	24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity	\$1,354.32
BTB14536	36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity	\$1,680.36
BQC14500	Quick Coupler	\$1,094.40
BQC14512	12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity	\$1,120.39
BQC14518	18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity	\$1,185.60
BQC14524	24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity	\$1,280.45
BQC14536	36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity	\$1,588.70
BQC14536D	36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity	\$1,521.00
ATH250-2I	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,548.58

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
ATH250-2K	Hydraulic Thumb (Only compatible with 18" and larger buckets)	\$2,298.58

Prices are F.O.B. Pendergrass, GA
Effective 1 January 2025
Revised 07-01-2025

Prices and specifications
subject to change without notice

P-8
Prices are in US Dollar



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB350R

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 10,980 lbs.	TOPS/ROPS/OPG 4 post canopy
Width: 6' 6.7"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 11' 8.8"	High back adjustable suspension seat
Bucket Digging Force: 10,431 lb	Pilot operated joystick control with pattern change valve
Horsepower / RPM: 41.7 / 2,000	EPA Final Tier 4 compliant engine with DPF and engine monitoring system
Travel Speed: 1.7 / 3.1 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 24.6 gpm	Side by side industrial type radiator and hydraulic oil cooler
Track width: 15.7"	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode
Two speed travel with automatic shift down	Safety features include: Travel alarm, retractable seat belt, control lockout, pilot accumulator, and lights
Reinforced arm w/ Integrated thumb mount	Variable displacement axial piston pump
Heavy duty dozer blade with float	Auto Idle
TFM hardware standard equipment, service included through the standard warranty period	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB350R-R	TB350R- Canopy Equipped with Rubber Tracks Four Post TOPS/ROPS/OPG Canopy, 12V Power Outlet, 1st Aux Circuit Only	\$81,371
TB350R-RA (w/Angle Blade)	TB350R- Canopy (Above Equipped) Rubber Track) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$85,251
TB350R-CR	TB350R- Cab Equipped with Rubber Tracks TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet	\$88,882
TB350R-CRA (w/ Angle Blade)	TB350R- Cab (Above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$92,763

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB14512	12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity	\$1,131.17
BTB14518	18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity	\$1,254.00
BTB14524	24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity	\$1,354.32
BTB14536	36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity	\$1,680.36
BQC14500	Quick Coupler	\$1,094.40
BQC14512	12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity	\$1,120.39
BQC14518	18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity	\$1,185.60
BQC14524	24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity	\$1,280.45
BQC14536	36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity	\$1,588.70
BQC14536D	36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity	\$1,521.00
ATH250-2I	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,548.58

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
ATH250-2K	Hydraulic Thumb (Only compatible with 18" and larger buckets)	\$2,298.58



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB260

Compact Excavator

STANDARD EQUIPMENT		
Operating Weight: 12,125 lbs. Width: 6' 6.7" Maximum Dig Depth: 12' 9.4" Bucket Digging Force: 12,756 lbs. Horsepower / RPM: 47.6 / 2,400 Travel Speed: 1.7 / 3.0 mph Primary Aux Flow: 27.0 gpm Second Aux Flow: 11.6 gpm Boom Swing: Left 78° / Right 55° Track Width: 15.7" Two speed travel with automatic shift down Reinforced arm w/ Integrated thumb mount Heavy duty dozer blade with float Auto Idle	TOPS/ROPS/OPG 4 post canopy Color gauge panel with multi-function operator information center Adjustable high back suspension seat Pilot operated joystick control with pattern change valve Proportional slide switch control auxiliary hydraulics EPA Final Tier 4 Turbocharged engine with DPF and engine monitoring system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door Side by side radiator and hydraulic cooler Variable Displacement axial piston pump Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch controls Primary auxiliary continuous mode and one-way mode Safety features include: Travel alarm, retractable seat belt, control lockout, pilot accumulator, mirrors and lights	
TFM hardware standard equipment, service included through the standard warranty period (Canopy: sn 1261001302~ / Cab: sn 1261001605~)		

BASE MACHINE WITH STANDARD EQUIPMENT		
Factory Code	Description	Suggested List Price
TB260R	TB260 Equipped with ROPS/TOPS/FOPS canopy, Rubber Tracks	\$85,601
TB260S	TB260 Equipped with ROPS/TOPS/FOPS canopy, Steel Tracks	\$86,782
TB260RA (w/Angle Blade)	TB260 Canopy (Rubber Track) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$89,251
TB260SA (w/Angle Blade)	TB260 Canopy (Steel Track) with Angle Blade	\$90,432
TB260L (w/ Segmented Rubber Tracks)	TB260 Canopy (above Equipped with Segmented Rubber Tracks)	\$91,683
TB260LA (w/ Angle Blade & Segmented Rubber Tracks)	TB260 Canopy (above Equipped with Segmented Rubber Tracks) w/ Angle Blade , Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$95,333
TB260CR	TB260 Cab Equipped with Rubber Tracks TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 12v power outlet	\$93,630
TB260CS	TB260 Cab Equipped with Steel Tracks	\$94,810
TB260CRA (w/Angle Blade)	TB260 Cab (Rubber Track) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$97,278
TB260CSA (w/Angle Blade)	TB260 Cab (Steel Track) with Angle Blade	\$98,460
TB260CL (w/ Segmented Rubber Tracks)	TB260 Cab (above Equipped Cab with Segmented Rubber Tracks)	\$99,711
TB260CLA (w/ Angle Blade & Segmented Rubber Tracks)	TB260 Cab (above Equipped Cab with Segmented Rubber Tracks) w/ Angle Blade , Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$103,362
BASE MACHINE PRICE DOES NOT INCLUDE BUCKET		

ATTACHMENTS		
Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Thumb System		
AQC-PH260I	INSTALLED	Hydraulic Pin Grabber Coupler (TB260) - Includes set of dead pins & hoses (Installed)
AQC-PH260	Field Installed Kit	Hydraulic Pin Grabber Coupler (TB260) - Includes set of dead pins & hoses
ABE-260-PO12T		12" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)
ABE-260-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)
ABE-260-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)
ABE-260-PO36T		36" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)
ATE-260I	INSTALLED	Hydraulic Thumb (2-line) (Only compatible w/ 18" or larger Buckets)
ATE-260K	Field Installed Kit	Hydraulic Thumb (2-line) (Only compatible w/ 18" or larger Buckets)
DPK-260		Bucket Pin Kit (includes Hardware)
Tag Branded Pin on Buckets, Manual Coupler		
BTB26012		12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity
BTB26018		18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity
BTB26024		24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity
BTB26036		36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity
BQC26000		Quick Coupler
BQC14512		12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity
BQC14518		18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity
BQC14524		24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity
BQC14536		36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity
BQC14536D		36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity
ATH260I	INSTALLED	Hydraulic thumb (Only compatible w/ 18" or larger Buckets) *
ATH260K	Field Installed Kit	Hydraulic Thumb (Only compatible with 18" and larger buckets)

FIELD INSTALLED OPTIONS		
1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

TB257FR

Zero Swing Excavator

STANDARD EQUIPMENT

Operating Weight: 12,675 lbs. Width: 6' 6.7" Maximum Dig Depth: 12' 9.4" Bucket Digging Force: 10,431 lbs. Horsepower / RPM: 52.3 / 2,400 Travel Speed: 1.6 / 3.0 mph Primary Aux Flow: 27.7 gpm Second Aux Flow: 11.8 gpm Boom Swing: Left 30°/ Right 16° Track Width: 15.7" Automatic Load Sensing Two Speed Travel Reinforced arm w/ Integrated thumb mount Heavy duty backfill blade with float Auto Idle TFM hardware standard equipment, service included through the standard warranty period	ROPS/TOPS/OPG Level 1, 4 Post Canopy Multifunction display Deluxe High Back Suspension Seat Pilot operated joystick controls with pattern change valve Proportional slide switch control auxiliary hydraulic: EPA Tier 4 Final, Turbocharged engine with DOC/DPF exhaust aftertreatment system Self priming fuel system with ground level fuel fill, sight gauge and lockable door Side by side radiator and hydraulic cooler Variable Displacement axial piston pump Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch controls, third auxiliary circuit for hydraulic quick couple Primary auxiliary with detent and one way mode Safety features include: Travel alarm, retractable seat belt, boom holding valve with lift alarm control lockout, pilot accumulator, mirrors and LED working lights
--	--

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB257FRR	TB257FR Equipped with ROPS/TOPS/FOPS canopy, Rubber Tracks	\$87,837
TB257FRS	TB257FR Equipped with ROPS/TOPS/FOPS canopy, Steel Tracks	\$89,019

TB257FRCR	TB257FR Cab Equipped with Rubber Tracks TOPS/ROPS/OPG enclosed cab with air conditioner/heater/defrost slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio 12v power outlet	\$96,457
TB257FRCS	TB257FR Cab Equipped same as above with Steel Tracks	\$97,639

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Hydraulic Thumb

AQC-PH257I	INSTALLED	Hydraulic Pin Grabber Coupler (TB257FR) (Installed)	\$4,713.56
AQC-PH257	Field Installed Kit	Hydraulic Pin Grabber Coupler (TB257FR) - Includes pins & hose	\$4,463.56
ABE-145-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,260.00
ABE-145-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,360.80
ATE-145I	INSTALLED	Hydraulic Thumb (2-tine) (Only compatible w/ 18" or larger Buckets)	\$2,848.75
ATE-145K	Field Installed Kit	Hydraulic Thumb (2-tine) (Only compatible w/ 18" or larger Buckets)	\$2,598.75
DPK-260		Bucket Pin Kit (includes Hardware)	\$363.00

Tag Manual Coupler / Pin on Buckets / Hydraulic Thumb

BTB14512		12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity	\$1,131.17
BTB14518		18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity	\$1,254.00
BTB14524		24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity	\$1,354.32
BTB14536		36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity	\$1,680.36
BQC14500		Quick Coupler	\$1,094.40
BQC14512		12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity	\$1,120.39
BQC14518		18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity	\$1,185.60
BQC14524		24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity	\$1,280.45
BQC14536		36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity	\$1,588.70
BQC14536D		36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity	\$1,521.00
ATH250-2I	INSTALLED	Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,548.58
ATH250-2K	Field Installed Kit	Hydraulic Thumb (2-tine) (Only compatible with 18" and larger buckets)	\$2,298.58

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
------------	---	---------



519 Bonnie Valentine Way, Pendergrass, GA 30561
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB370

Excavator

STANDARD EQUIPMENT

Operating Weight: 14,850 lbs. Width: 6' 10.7" Maximum Dig Depth: 13' 4.7" Bucket Digging Force: 14,613 lbs. Net Horsepower / RPM: 56.9 / 2,000 Travel Speed: 1.6 / 2.9 mph Auxiliary Flow: 31.7 gpm Second Aux Flow: 12.3 gpm Boom Swing: Left 79° / Right 51° Track Width: 15.7" Automatic load sensing two speed travel Reinforced arm w/ Integrated thumb mount Heavy duty backfill blade with float Auto Idle	ROPS/OPG Level 1 climate control, jog dial, windshield wiper and washer, skylight, sunshade, radio with Bluetooth 8" Color touch screen multifunction display Deluxe high back suspension seat Pilot operated joystick controls EPA Tier 4 Final, Turbocharged engine with DOC/DPF exhaust aftertreatment system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door Side by side radiator and hydraulic cooler Closed center, load sensing hydraulic system Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch controls, third auxiliary circuit for hydraulic quick coupler Primary auxiliary with detent and one way mode. Safety features include: travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding, valve with lift alarm, mirrors and, rear view camera, LED working lights
TFM hardware standard equipment, service included through the standard warranty period	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB370CR	TB370 Cab Equipped with 15.7" Rubber Tracks	\$119,915
TB370CS	TB370 Cab Equipped with 15.7" Steel Tracks	\$121,118
TB370CRA	(w/ Angle Blade) TB370 Cab with Rubber Tracks and Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards	\$125,479
TB370CSA	(w/ Angle Blade) TB370 Cab with Steel Tracks and Angle Blade (same as above)	\$126,683
TB370CL	TB370 Cab Equipped with Segmented 15.7" Rubber Tracks	\$126,262
TB370CLA	(w/ Angle Blade) TB370 Cab with Segmented Rubber Tracks and Angle Blade (same as above)	\$131,825

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Hydraulic Thumb			
AQC-PH290I	INSTALLED	Hydraulic Pin Grabber Coupler (TB370) - Includes set of dead pins & hoses(Installed)	\$5,196.95
AQC-PH290	Field Installed Kit	Hydraulic Pin Grabber Coupler (TB370) - Includes set of dead pins & hoses	\$4,946.95
ABE-370-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,549.80
ABE-370-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,644.30
ABE-370-PO36T		36" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$2,009.70
ATE-370I	INSTALLED	Hydraulic Thumb (4-tine) (Only compatible w/ 18" or larger Buckets)	\$3,437.80
ATE-370K	Field Installed Kit	Hydraulic Thumb (4-tine) (Only compatible w/ 18" or larger Buckets)	\$3,187.80
DPK-290		Bucket Pin Kit (includes Hardware)	\$387.20

Tag Manual Coupler / Pin on Buckets / Hydraulic Thumb

BTB07018		18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,329.70
BTB07024		24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,514.21
BTB07036		36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,894.40
BQC07000		Quick Coupler	\$1,350.33
BQC07018		18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,280.45
BQC07024		24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,382.54
BQC07036		36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,729.67
BQC07036D		36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,699.43
ATH290I	INSTALLED	Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$3,498.66
ATH290K	Field Installed Kit	Hydraulic thumb (Only compatible with 18" and larger buckets)	\$3,248.66

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
------------	---	---------



TB290

Excavator

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 18,630 lbs.	ROPS/OPG enclosed cab w/ air conditioner/heat, windshield wiper,
Width: 7' 7"	12v power outlet, and AM/FM/MP3 radio
Maximum Dig Depth: 15'	Color 5.7" gauge panel with multi-function operator information center
Bucket Digging Force: 16,565 lbs.	10-way adjustable high back suspension seat
Net Horsepower / RPM: 69.2 / 2,000	Pilot operated joystick control with pattern change valve
Travel Speed: 1.6 / 3.1 mph	EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system
Auxiliary Flow: 31.7 gpm	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable doo
Second Aux Flow: 14.5 gpm	Side by side radiator and hydraulic cooler
Boom Swing: Left 70°/ Right 60°	Load sensing variable displacement hydraulic system
Track Width: 17.7" Rubber / 21.7" Steel	Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow
Two speed travel with automatic shift down	control system and proportional slide switch
Reinforced arm w/ Integrated thumb mount	Primary auxiliary continuous mode and one-way mode
Heavy duty dozer blade with float	Safety features include: large skylight with sun shade,
Automatic track tensioner	travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding
Auto Idle	valve with lift alarm, mirrors, rear view camera, and lights
TFM hardware standard equipment, service included through the standard warranty period (sn 185102670 ~	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB290CR	TB290 Cab Equipped with Rubber Tracks	\$139,077
TB290CS	TB290 Cab Equipped with Steel Tracks	\$140,291
TB290CRA (w/ Angle Blade)	TB290 Cab (Rubber Tracks) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards	\$146,583
TB290CSA	TB290 Cab (Steel Tracks) with Angle Blade	\$147,798
TB290CL (w/ Segmented Rubber Tracks)	TB290 Cab (above Equipped except with Segmented Rubber Tracks)	\$146,321
TB290CLA (w/ Angle Blade & Segmented Rubber Tracks)	TB290 Cab (above Equipped except with Segmented Rubber Tracks) with Angle Blade , Angle Blade features 25 degree left and right angle, cylinder protective guards	\$153,827

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Hydraulic Thumb			
AQC-PH290I	INSTALLED	Hydraulic Pin Grabber Coupler (TB370) - Includes set of dead pins & hoses (Installed)	\$5,196.95
AQC-PH290	Field Installed	Hydraulic Pin Grabber Coupler (TB370) - Includes set of dead pins & hoses	\$4,946.95
ABE-290-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,549.80
ABE-290-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,644.30
ABE-290-PO36T		36" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$2,009.70
ATE-290I	INSTALLED	Hydraulic Thumb (4-tine) (Only compatible w/ 18" or larger Buckets	\$3,437.80
ATE-290K	Field Installed	Hydraulic Thumb (4-tine) (Only compatible w/ 18" or larger Buckets	\$3,187.80
DPK-290		Bucket Pin Kit (includes Hardware)	\$387.20

Tag Manual Coupler / Pin on Buckets / Hydraulic Thumb			
BTB07018		18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,329.70
BTB07024		24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,514.21
BTB07036		36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,894.40
BQC07000		Quick Coupler	\$1,350.33
BQC07018		18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,280.45
BQC07024		24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,382.54
BQC07036		36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,729.67
BQC07036D		36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,699.43
ATH290I	INSTALLED	Hydraulic thumb (Only compatible w/ 18" or larger Buckets	\$3,498.66
ATH290K	Field Installed	Hydraulic thumb (Only compatible with 18" and larger buckets	\$3,248.66

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
------------	---	---------



TB280FR

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

Zero Swing Excavator

STANDARD EQUIPMENT

Operating Weight: 18,810 lbs.	ROPS/OPG enclosed cab w/ air conditioner/heat, windshield wiper, 12v power outlet and AM/FM/MP3 radio
Width: 7' 7"	Tilt-up operator's platform
Maximum Dig Depth: 14' 11"	Color 5.7" gauge panel with multi-function operator information center
Bucket Digging Force: 16,335 lbs.	10-way adjustable high back suspension seat
Horsepower / RPM: 69.2 / 2,000	Pilot operated joystick control with pattern change valve
Travel Speed: 1.7 / 3.2 mph	EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system
Auxiliary Flow: 39 gpm	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Second Aux Flow: 15 gpm	Side by side radiator and hydraulic cooler
Boom swing: Left 30°/ Right 15°	Variable displacement axial piston main hydraulic pump
Track Width: 17.7"	Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch
Side-to-Side (STS) offset boom system	Primary auxiliary continuous mode and one-way mode
Two speed travel with automatic shift down	Safety features include: large skylight with sun shade
Reinforced arm	travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding valve with lift alarm, mirrors and lights
Heavy duty dozer blade with float	
Auto idle	
TFM hardware standard equipment, service included through the standard warranty period (sn 178500473 ~	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB280FRCR	TB280FR Cab Equipped with Rubber Tracks	\$143,455
TB280FRCS	TB280FR Cab Equipped with Steel Tracks	\$144,670
TB280FRCL (w/ Segmented Rubber Tracks)	TB280FR Cab Equipped with Segmented Rubber Tracks	\$150,699

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Hydraulic Thumb

AQC-PH290I	INSTALLED	Hydraulic Pin Grabber Coupler (TB370) - Includes set of dead pins & hoses (Installed)	\$5,196.95
AQC-PH290	Field Installed Kit	Hydraulic Pin Grabber Coupler (TB370) - Includes set of dead pins & hose:	\$4,946.95
ABE-290-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,549.80
ABE-290-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,644.30
ABE-290-PO36T *		36" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$2,009.70
ATE-290I	INSTALLED	Hydraulic Thumb (4-tine) (Only compatible w/ 18" or larger Buckets)	\$3,437.80
ATE-290K	Field Installed Kit	Hydraulic Thumb (4-tine) (Only compatible w/ 18" or larger Buckets)	\$3,187.80
DPK-290		Bucket Pin Kit (includes Hardware)	\$387.20

Tag Manual Coupler / Pin on Buckets / Hydraulic Thumb

BTB07018		18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,329.70
BTB07024		24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,514.21
BTB07036 *		36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,894.40
BQC07000		Quick Coupler	\$1,350.33
BQC07018		18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,280.45
BQC07024		24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,382.54
BQC07036 *		36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,729.67
BQC07036D *		36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,699.43
ATH280FRI	INSTALLED	Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$3,498.66
ATH280FRK	Field Installed Kit	Hydraulic thumb (Only compatible with 18" and larger buckets)	\$3,248.66

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2" belt	\$91.00
------------	--	---------

* **NOTE:** The Zero Swing front radius feature is only available for the standard bucket attachment (30" or smaller)



519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB395W

Wheel Excavator

STANDARD EQUIPMENT

Operating Weight: 26425 lbs.	ROPS/OPG enclosed cab w/ air conditioner/heat, windshield wiper,
Width: 15' 3.5"	24v power outlet, and AM/FM/MP3 radio
Maximum Dig Depth: 13'5.2"	Color 8" gauge panel with multi-function control panel & jog dial contro
Bucket Digging Force: 13241 lbf	Air suspension seat with heat
Net Horsepower / RPM: 114 / 2,200	Pilot operated joystick control with pattern change valve
Travel Speed: (1) 3.5/ 9.7 and (2) 6.5/18.1 mph	EPA Final Tier 4 turbocharged engine with DOC+DPF+SCR exhaust after treatment
Auxiliary Flow: 31.7 gpm	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable doo
Second Aux Flow: 14.5 gpm	Side by side radiator and hydraulic cooler
Boom Swing: Left 68°/ Right 59°	Load sensing variable displacement hydraulic system
Two speed travel with automatic shift down	Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow
Reinforced arm w/ Integrated thumb mount	control system and proportional slide switch
2-piece variable angle boom	Third auxiallry for Quick Hitch
Heavy duty box frame dozer blade	Primary auxiliary continuous mode and one-way mode
Hydraulic Outriggers	Safety features include: large skylight with sun shade,
Mud Guards	travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding
Auto Idle	valve with lift alarm, mirrors, rear view camera, and lights
LED Light Package; Right Cover, Boom,Front Cab, and Rear Cab	
270 degree view monitor	
TFM hardware standard equipment, service included through the standard warranty perioo	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB395W-2S	TB395W Cab Equipped with Tires and 2 wheel steer	\$203,940
TB395W-4S	TB395W Cab Equipped with Tires and 4 wheel steer	\$210,120

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Hydraulic Thumb			
AQC-PH290I	INSTALLED	Hydraulic Pin Grabber Coupler (TB370) - Includes set of dead pins & hoses(Installed)	\$5,196.95
AQC-PH290	Field Installed	Hydraulic Pin Grabber Coupler (TB370) - Includes set of dead pins & hoses	\$4,946.95
ABE-290-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,549.80
ABE-290-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$1,644.30
ABE-290-PO36T		36" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$2,009.70
ATE-290I	INSTALLED	Hydraulic Thumb (4-tine) (Only compatible w/ 18" or larger Buckets	\$3,437.80
ATE-290K	Field Installed	Hydraulic Thumb (4-tine) (Only compatible w/ 18" or larger Buckets	\$3,187.80
DPK-290		Bucket Pin Kit (includes Hardware)	\$387.20

Tag Manual Coupler / Pin on Buckets / Hydraulic Thumb

BTB07018		18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,329.70
BTB07024		24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,514.21
BTB07036		36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,894.40
BQC07000		Quick Coupler	\$1,350.33
BQC07018		18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,280.45
BQC07024		24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,382.54
BQC07036		36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,729.67
BQC07036D		36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,699.43
ATH290I	INSTALLED	Hydraulic thumb (Only compatible w/ 18" or larger Buckets'	\$3,498.66
ATH290K	Field Installed	Hydraulic thumb (Only compatible with 18" and larger buckets	\$3,248.66

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
------------	---	----------------



TB2150

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

Excavator

STANDARD EQUIPMENT

Operating Weight: 34,480 lbs. (Rubber)	ROPS/OPG Level 2 cab
Dozer Blade Width: 8' 6"	Factory installed cab with automatic climate control, AM/FM/MP3 radio, wipe
Maximum Dig Depth: 18'	Two speed travel with automatic shift down
Bucket Digging Force: 22,190 lbs.	Travel alarm
Tail Swing Radius: 6' 6.7"	Arm & Boom holding valve with lift alarm
Horsepower / RPM: 114 / 2,000	Pattern change valve
EPA Final Tier 4 Compliant	Pilot operated joystick controls with safety lock out
Travel Speed: 1.9 / 3.4 mph	Wrap around counterweight with towers
Auxiliary Flow: (Primary) 59.0 gpm	Adjustable air suspension seat with retractable seat belt
Auxiliary Flow: (Secondary) 14.5 gpm	Primary and Secondary two-way auxiliary hydraulic circuits routed to the end of the arm
Boom Swing: Left 77° / Right 53°	Proportional thumb wheel control of both auxiliary hydraulic circuits
24" Wide Steel Tracks	Electrohydraulic push button controls of auxiliary hydraulic circuit (Primary Only)
Optional: 20" Rubber Track	Variable displacement axial piston main hydraulic pump
Optional: 20" Segmented Rubber Tracks	Multi function color monitor pane
	Heavy duty dozer blade with Floa

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB2150CR	TB2150 Equipped with CAB OPG, Rubber Tracks, Dozer blade with float Auto Air Conditioner/Heat, Defroster, Windshield wiper and washer Control pattern selector valve, Travel alarm, Cab light, Auxiliary hydraulics (primary and secondary), Slide back front window, AM/FM/MP3 radio Air Suspension seat, Engine monitoring system	\$213,243
TB2150CS	TB2150 Equipped with CAB OPG, Steel Tracks, Dozer blade with float	\$215,408
TB2150CL (w/ Segmented Rubber Tracks)	TB2150 Cab (above Equipped except with Segmented Rubber Tracks)	\$224,439

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Hydraulic Thumb			
AQC-PH2150I	INSTALLED	Hydraulic Pin Grabber Coupler (TB2150) - Includes set of dead pins & hoses (Installed)	\$7,000.00
AQC-PH2150	Field Installed Kit	Hydraulic Pin Grabber Coupler (B2150) - Includes set of dead pins & hose:	\$6,750.00
ABE-2150-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$3,590.46
ABE-2150-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$3,864.60
ABE-2150-PO36T		36" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$4,787.28
ATE-2150LI	INSTALLED	Hyd Thumb LONG (4-tine) (Only compatible w/ 18" or larger Buckets)(for Hyd Coupler	\$8,283.03
ATE-2150LK	Field Installed Kit	Hyd Thumb LONG (4-tine) (Only compatible w/ 18" or larger Buckets)(for Hyd Coupler	\$8,033.03
ATE-2150I	INSTALLED	Hyd Thumb SHORT (4-tine) (Only compatible w/ 18" or larger Buckets)(for Pin on Bucket only	\$8,283.03
ATE-2150	Field Installed Kit	Hyd Thumb SHORT (4-tine) (Only compatible w/ 18" or larger Buckets)(for Pin on Bucket only	\$8,033.03

Tag Manual Coupler / Pin on Buckets / Hydraulic Thumb

BTB114018		18" Pin-On Bucket (Capacity 0.41) (875 lbs)	\$3,598.70
BTB114024		24" Pin-On Bucket (Capacity 0.57) (1025 lbs)	\$3,864.60
BTB114030		30" Pin-On Bucket (Capacity 0.73) (1110 lbs)	\$4,437.74
BTB114036		36" Pin-On Bucket (Capacity 0.89) (1295 lbs)	\$4,798.26
BTB114042D		42" Pin-On Ditching Bucket (Capacity 0.50) (695 lbs)	\$3,395.83
BTB114048D		48" Pin-On Ditching Bucket (Capacity 0.60) (800 lbs)	\$3,655.41
BTB114054D		54" Pin-On Ditching Bucket (Capacity 0.70) (900 lbs)	\$3,925.02
BTB114060D		60" Pin-On Ditching Bucket (Capacity 0.80) (970 lbs)	\$4,562.28
BTH1140I	INSTALLED	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs	\$9,424.84
BTH1140K	Field Installed Kit	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs	\$9,174.84
BTH1140LI	INSTALLED	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler	\$9,424.84
BTH1140LK	Field Installed Kit	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler	\$9,174.84

FIELD INSTALLED OPTIONS

K1573400001	3" Retractable seat belt in lieu of standard 2'	\$121.39
TB1140BKTPINS	Bucket Pin Kit (includes Hardware)	\$482.00

Prices and specifications
subject to change without notice

P-16-A
Prices are in US Dollar

Prices are F.O.B. Pendergrass,GA
Effective 1 January 2025
Revised 07-01-2025



TB2150R

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725
www.takeuchi-us.com

Fixed Boom Excavator

STANDARD EQUIPMENT

Operating Weight: 34,215 lbs. (Rubber)	ROPS/OPG Level 2 cab
Dozer Blade Width: 8' 6"	Factory installed cab with automatic climate control, AM/FM/MP3 radio, wipe
Maximum Dig Depth: 19' 9.4"	Two speed travel with automatic shift down
Bucket Digging Force: 22,256 lbs.	Travel alarm
Tail Swing Radius: 5' 7"	Arm & Boom holding valve with lift alarm
Horsepower / RPM: 114 / 2,000	Pattern change valve
EPA Final Tier 4 Compliant	Pilot operated joystick controls with safety lock out
Travel Speed: 1.9 / 3.4 mph	Wrap around counterweight
Auxiliary Flow: (Primary) 59.0 gpm	Adjustable air suspension seat with retractable seat belt
Auxiliary Flow: (Secondary) 14.5 gpm	Primary and Secondary two-way auxiliary hydraulic circuits routed to the end of the arm
20" Rubber Track	Proportional thumb wheel control of 1st and 2nd auxiliary hydraulic circuit
Optional: 20" Segmented Rubber Track	Electrohydraulic push button controls of primary auxiliary hydraulic circuit
Optional: 24" Steel Tracks	Variable displacement axial piston main hydraulic pump
Optional: 28" Wide Steel Tracks	Multi function color monitor pane
	Heavy duty dozer blade with float

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB2150R-CR	TB2150R Equipped with CAB OPG, Rubber Tracks, Dozer Blade with Float Auto Air Conditioner/Heat, Defroster, Windshield Wiper and Washer Control Pattern Selector Valve, Travel Alarm, Cab Light, Auxiliary Hydraulics (primary and secondary), Slide Back Front Window, AM/FM/MP3 Radio Air Suspension Seat, Engine Monitoring System	\$207,908
TB2150R-CSS	TB2150R Equipped with CAB OPG, 24" Steel Tracks, Dozer blade with float	\$210,010
TB2150R-CWS	TB2150R Equipped with CAB OPG, 28" Steel Tracks, Dozer blade with float	\$212,930
TB2150R-CL (w/ Segmented Rubber Tracks)	TB2150R Cab (above Equipped except with 20" Segmented Rubber Tracks)	\$219,354

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

Takeuchi Hydraulic Pin Grabber Coupler / Bucket / Hydraulic Thumb			
AQC-PH2150I	INSTALLED	Hydraulic Pin Grabber Coupler (TB2150) - Includes set of dead pins & hoses (Installed)	\$7,000.00
AQC-PH2150	Field Installed Kit	Hydraulic Pin Grabber Coupler (B2150) - Includes set of dead pins & hose:	\$6,750.00
ABE-2150-PO18T		18" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$3,590.46
ABE-2150-PO24T		24" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$3,864.60
ABE-2150-PO36T		36" Pin-On Bucket with Teeth (for Hyd Pin Grabber Coupler)	\$4,787.28
ATE-2150LI	INSTALLED	Hyd Thumb LONG (4-tine) (Only compatible w/ 18" or larger Buckets)(for Hyd Coupler	\$8,283.03
ATE-2150LK	Field Installed Kit	Hyd Thumb LONG (4-tine) (Only compatible w/ 18" or larger Buckets)(for Hyd Coupler	\$8,033.03
ATE-2150I	INSTALLED	Hyd Thumb SHORT (4-tine) (Only compatible w/ 18" or larger Buckets)(for Pin on Bucket only	\$8,283.03
ATE-2150	Field Installed Kit	Hyd Thumb SHORT (4-tine) (Only compatible w/ 18" or larger Buckets)(for Pin on Bucket only	\$8,033.03

Tag Manual Coupler / Pin on Buckets / Hydraulic Thumb			
BTB114018		18" Pin-On Bucket (Capacity 0.41) (875 lbs)	\$3,598.70
BTB114024		24" Pin-On Bucket (Capacity 0.57) (1025 lbs)	\$3,864.60
BTB114030		30" Pin-On Bucket (Capacity 0.73) (1110 lbs)	\$4,437.74
BTB114036		36" Pin-On Bucket (Capacity 0.89) (1295 lbs)	\$4,798.26
BTB114042D		42" Pin-On Ditching Bucket (Capacity 0.50) (695 lbs)	\$3,395.83
BTB114048D		48" Pin-On Ditching Bucket (Capacity 0.60) (800 lbs)	\$3,655.41
BTB114054D		54" Pin-On Ditching Bucket (Capacity 0.70) (900 lbs)	\$3,925.02
BTB114060D		60" Pin-On Ditching Bucket (Capacity 0.80) (970 lbs)	\$4,562.28
BTH1140I	INSTALLED	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs	\$9,424.84
BTH1140K	Field Installed Kit	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs	\$9,174.84
BTH1140LI	INSTALLED	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler	\$9,424.84
BTH1140LK	Field Installed Kit	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler	\$9,174.84

FIELD INSTALLED OPTIONS

K1573400001	3" Retractable seat belt in lieu of standard 2'	\$121.39
TB1140BKTPINS	Bucket Pin Kit (includes Hardware)	\$482.00

Prices and specifications
subject to change without notice

P-16-B
Prices are in US Dollar

Prices are F.O.B. Pendergrass,GA
Effective 1 January 2025
Revised 07-01-2025



TL6

Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 7485 lbs.	Radial boom design
Overall Width Without Bucket: 5' 0.2"	ROPS/FOPS tilt-up operators compartment w/ rearview mirrors
Tipping Load (SAE 732) 5,269 lbs.	Back-up alarm, Top and rear windows
Rated Operating Capacity (ROC)(SAE J818): 1,841 lbs	Automatic fuel bleed system
Bucket Digging Force: 5,930 lbs.	Pilot operated joystick controls
Horsepower / RPM: 65.2 / 2700	Universal quick attach mounting bracket
Travel Speed: 4 / 6mph	Suspension seat with retractable seatbelt
Auxiliary Flow: 17.8 gpm	One and two way auxiliary hydraulics
Ground Pressure: 4.8 psi	Electronic engine monitoring system
Maximum Lift Height to Bucket Pin: 9' 6.4"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Reach Fully Raised: 1' 10"	Proportional slide switch control auxiliary hydraulics with detent function
Canopy/Cab height: 6' 5"	Hydraulic self-leveling bucket
	Flat face, pressure releasing Hydraulic Couplers
	Standard 14-pin connector with push button control
	Dual element air cleaner
	Push button boom float with detent
	Foot Throttle

EPA Final Tier 4 Turbocharged Engine with DPF

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL6R	TL6 with ROPS/FOPS Canopy, Rubber tracks	\$58,544
TL6CR	TL6 with ROPS/FOPS Cab with Air Conditioning/Heat Defroster, Rubber Tracks, Hydraulic quick attach, Swing out door, AM/FM/MP3 Radio	\$65,328

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

ATTACHMENTS

ABLU-60S-047	60" HD smooth dirt bucket with bolt-on edge, 12.7 cubic feet capacity	\$2,283.59
ABLU-60T-047	60" HD dirt bucket with 7 teeth, 12.7 cubic feet capacity	\$2,404.03
BTL867	67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity	\$2,420.99
BTL867T	67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity	\$2,349.06
TDZR84	7' six way dozer blade	\$9,893.66
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	\$1,227.87

FIELD INSTALLED OPTIONS

K28843001	Counter Weight Kit (332 lbs)(ROC: 2041 lbs)	\$1,851.70
1914199948	3" Retractable seat belt in lieu of standard 2'	\$91.00
K28843005	TL6 hydraulic quick attach coupler kit (for Canopy unit)	\$1,800.15



TL8R2

Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 8,807 lbs.	Radial lift design
Overall Width Without Bucket:(15.7" Tracks) 65.5"	ROPS/FOPS tilt-up operators compartment w/ rear view camera
Tipping Load (SAE 732) 6,041 lbs.	Back-up alarm, Top and rear windows
Rated Operating Capacity (ROC)(SAE J818): 2,116 lbs	Automatic fuel bleed system
Bucket Digging Force: 6,204 lbs.	Pilot operated joystick controls
Horsepower / RPM: 73.2 / 2,600	Universal quick attach mounting bracket
Travel Speed: 4.7 / 7 mph	Deluxe high back suspension seat with retractable seatbel
Auxiliary Flow: 19.1 gpm	One and two way auxiliary hydraulics
Ground Pressure: 4.5 psi	Electronic engine monitoring system
Maximum Lift Height to Bucket Pin: 10' 1.2"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Reach Fully Raised: 2' 4.3"	Proportional slide switch control auxiliary hydraulics with detent function
Canopy/Cab height: 7' 3.8"	Hydraulic self-leveling bucket
	Flat face, pressure releasing Hydraulic Couplers
	Standard 14-pin connector with push button control
	Dual element air cleaner with standard pre-cleaner
	Push button boom float with detent
	Foot Throttle

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL8R2-R	TL8R2 with ROPS/FOPS Canopy, 15" Rubber tracks	\$68,755
TL8R2-CR	TL8R2 with ROPS/FOPS Cab with Air Conditioning/Heat Defroster, 15" Rubber Tracks, Hydraulic quick attach,AM/FM/MP3 Radio, Roll up door	\$76,286

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

ATTACHMENTS

BTL867	67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity	\$2,420.99
BTL867T	67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity	\$2,349.06
ABLU-72S-057	72" Low Profile Bucket - Smooth with Bolt on Cutting Edge	\$2,485.76
ABLU-72T-057	72" Low Profile Bucket -Tooth	\$2,442.45
BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	\$2,808.70
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	\$2,817.79
TDZR84	7' six way dozer blade	\$9,893.66
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	\$1,227.87

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2'	\$91.00
K48834204	3-point 2" seat belt kit in lieu of standard 2'	\$150.00
K28843001	Counter Weight Kit (332 lbs)(ROC: 2314 lbs)	\$1,851.70
K48800115	Level 2 Roof Guard Kit	\$888.25
K48887001	Hydraulic quick attach coupler kit (for Canopy unit)	\$1,998.87



TL8R2

Track Loader

HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel: 706-693-3600 Fax: 706-693-3725

www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 9,182 lbs.	Radial lift design
Overall Width Without Bucket: (15.7" Tracks) 65.5"	ROPS/FOPS tilt-up operators compartment w/ rear view camera
Tipping Load (SAE 732) 6,041 lbs.	Back-up alarm, Top and rear windows
Rated Operating Capacity (ROC)(SAE J818): 2,116 lbs	Automatic fuel bleed system
Bucket Digging Force: 6,204 lbs.	Pilot operated joystick controls
Horsepower / RPM: 73.2 / 2,600	Universal quick attach mounting bracket
Travel Speed: 4.7 / 7 mph	Deluxe high back suspension seat with retractable seatbelt
Auxiliary Flow: 19.1 gpm STD / 33.8 gpm HF	One and two way auxiliary hydraulics
Ground Pressure: 4.5 psi	Electronic engine monitoring system
Maximum Lift Height to Bucket Pin: 10' 1.2"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Reach Fully Raised: 2' 4.3"	Proportional slide switch control auxiliary hydraulics with detent function
Cab height: 7' 6.1"	Hydraulic self-leveling bucket
1/2" Lexan roll up door	Flat face, pressure releasing Hydraulic Couplers
EPA Final Tier 4 turbocharged engine with DPF	Standard 14-pin connector with push button control
	Dual element air cleaner with standard pre-cleaner
	Push button boom float with detent
	Foot Throttle

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL8R2-CRH	TL8R2 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, Rubber Tracks, Hydraulic quick attach, Lexan Roll up door and HIGH FLOW auxiliary hydraulics (33 gpm) AM/FM/MP3 Radio, 2-speed auto-shift with creep mode	\$79,809

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

ATTACHMENTS

BTL867	67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity	\$2,420.99
BTL867T	67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity	\$2,349.06
ABLU-72S-057	72" Low Profile Bucket - Smooth with Bolt on Cutting Edge	\$2,485.76
ABLU-72T-057	72" Low Profile Bucket -Tooth	\$2,442.45
BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	\$2,808.70
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	\$2,817.79
TDZR84	7' six way dozer blade	\$9,893.66
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	\$1,227.87

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
K48834204	3-point 2" seat belt kit in lieu of standard 2"	\$150.00
K28843001	Counter Weight Kit (332 lbs)(ROC: 2314 lbs)	\$1,851.70
K48800115	Level 2 Roof Guard Kit	\$888.25

Prices are F.O.B. Pendergrass, GA

Effective 1 January 2025

Revised 07-01-2025

Prices and specifications
subject to change without notice

P-18-B
Prices are in US Dollar



TL10V2

Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 9,950 lbs.	Vertical boom design
Overall Width Without Bucket: 5' 8.5"	Tilt-up operators compartment
Tipping Load (SAE 732) 7,205 lbs.	Electronic dial type throttle and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 2,522 lbs	Back-up alarm
Bucket Digging Force: 6,520 lbs.	Top and rear windows
Horsepower / RPM: 74.3 / 2,600	Automatic fuel bleed system
Travel Speed: 4.8 / 7.0	Pilot operated joystick controls
Auxiliary Flow: 18.8 gpm	Universal quick attach mounting bracket
Ground Pressure: 4.9 PSI	Deluxe high back suspension seat with retractable seatbelt
Maximum Lift Height to Bucket Pin: 10' 4.8"	One and two way auxiliary hydraulics
Reach Fully Raised: 3' 1.4"	Electronic engine monitoring system
Canopy/Cab height: 7' 5.4"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Selectable working modes	Proportional thumb wheel control auxiliary hydraulics with detent function
Front & rear LED working lights	Hydraulic self-leveling bucket
ROPS/FOPS Level 1 operator protection	Flat face, pressure relieving Hydraulic Couplers
Multi function color monitor	Standard 14-pin connector with push button control
Active power control power management system	Dual element air cleaner
	Push button boom float with detent

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL10V2--R	TL10 with ROPS/FOPS Canopy, 15.7" Rubber tracks	\$79,079
TL10V2-RR (w/ RC)	TL10R (above Equipped) with Ride Control*	\$79,930
TL10V2-RP (w/ PC)	TL10R (above Equipped) with Pattern Control*	\$80,234
TL10V2-RRP (w/ RC & PC)	TL10R (above Equipped) with Ride Control & Pattern Control*	\$81,084

TL10V2-CR	TL10 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 15.7" Rubber Tracks, Hydraulic quick attach, Roll up door, AM/FM/MP3 Radio	\$86,854
TL10V2-CRR (w/ RC)	TL10CR (above Equipped) with Ride Control*	\$87,703
TL10V2-CRP (w/ PC)	TL10CR (above Equipped) with Pattern Control*	\$88,007
TL10V2-CRRP (w/ RC & PC)	TL10CR (above Equipped) with Ride Control & Pattern Control*	\$88,858

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	\$2,808.70
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	\$2,817.79
TDZR84	7' six way dozer blade	\$9,893.66
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	\$1,227.87

FIELD INSTALLED OPTIONS

K28843001	Counter Weight Kit (332 lbs)(ROC: 2314 lbs)	\$1,851.70
19141-99948	3" retractable seat belt in lieu of standard 2"	\$91.00
K48847001	Hydraulic quick attach coupler kit (for Canopy unit)	\$1,998.87



TL10V2

Track Loader

HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 10,270 lbs.	Vertical boom design
Overall Width Without Bucket: 5' 8.5"	Tilt-up operators compartment
Tipping Load (SAE 732) 7,205 lbs.	Electronic dial type throttle and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 2,522 lbs	Back-up alarm
Bucket Digging Force: 6,520 lbs.	Top and rear windows
Horsepower / RPM: 74.3 / 2,600	Automatic fuel bleed system
Travel Speed: 4.8 / 7.0	Pilot operated joystick controls
Auxiliary Flow (SP1): 18.8 gpm STD / 32.8 gpm HF	Universal quick attach mounting bracket
Ground Pressure: 5.1 PSI	Deluxe high back suspension seat with retractable seatbelt
Maximum Lift Height to Bucket Pin: 10' 4.8"	One and two way auxiliary hydraulics
Reach Fully Raised: 3' 1.4"	Electronic engine monitoring system
Cab height: 7' 6.9"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Front & rear LED working lights	Proportional thumb wheel control auxiliary hydraulics with detent function
ROPS / FOPS Level 2 operator protection	Hydraulic self-leveling bucket
Multi function color monitor	Flat face, pressure relieving Hydraulic Couplers
	Standard 14-pin connector with push button control
	Dual element air cleaner
	Push button boom float with detent

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL10V2-CRH	TL10 with Cab with Air Conditioning/Heat, Defroster, 15.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door, AM/FM/MP3 Radio, HIGH FLOW Auxiliary Hydraulics	\$90,560
TL10V2-CRHR (w/ RC)	TL10CRH (above Equipped) with Ride Control*	\$91,409
TL10V2-CRHP (w/ PC)	TL10CRH (above Equipped) with Pattern Control*	\$91,713
TL10V2-CRHRP (w/ RC & PC)	TL10CRH (above Equipped) with Ride Control & Pattern Control*	\$92,563

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	\$2,808.70
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	\$2,817.79
TDZR84	7' six way dozer blade	\$9,893.66
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	\$1,227.87

FIELD INSTALLED OPTIONS

19141-99948	3" retractable seat belt in lieu of standard 2"	\$91.00
K28843001	Counter Weight Kit (332 lbs)(ROC: 2718 lbs)	\$1,851.70



TL11R3

Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 11,650 lbs.	Radial boom design
Overall Width Without Bucket: 6' 0"	Tilt-up operators compartment
Tipping Load (SAE 732) 7,825 lbs.	Electronic dial type throttle and foot throttle (accel./ decel.)
Rated Operating Capacity (ROC)(SAE J818): 2,735 lbs	Back-up alarm
Bucket Digging Force: 7,958 lbs.	Top and rear windows
Horsepower / RPM: 107.3 / 2,400	Automatic fuel bleed system
Travel Speed: 4.8 / 7.5 mph	EH operated joystick controls
Auxiliary Flow: 23.1 gpm	Universal quick attach mounting bracket
Ground Pressure: 4.71 psi	Deluxe high back suspension seat with retractable seatbelt
Maximum Lift Height to Bucket Pin: 10' 6"	One and two way auxiliary hydraulics
Reach Fully Raised: 2' 11.2"	Electronic engine monitoring system
Canopy/Cab height: 7' 7.7"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Active power control power management system	Proportional thumb wheel control auxiliary hydraulics with detent function
Front & rear LED working lights	Hydraulic self-leveling bucket (up only)
ROPS/FOPS Level 1 operator protection	Flat face, pressure relieving Hydraulic Couplers
Multi function touchscreen monitor	Standard 14-pin connector with push button control
Selectable working modes	Dual element air cleaner
	Push button boom float with detent

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL11R3-R	TL11R3 with Canopy, 17.7" Rubber tracks	\$98,777
TL11R3-RR (w/ RC)	TL11R3 (above Equipped) with Ride Control	\$99,653
TL11R3-CR	TL11R3 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door, AM/FM/MP3 Radio	\$106,811
TL11R3-CRR (w/ RC)	TL11R3 (above Equipped) with Ride Control	\$107,687
TL11R3-CRHR (w/ RC)	TL11R3 with Cab with Air Conditioning/Heat, Defroster, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door, AM/FM/MP3 Radio, HIGH FLOW Auxiliary Hydraulics, RIDE CONTROL	\$112,888

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$3,125.37
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	\$3,115.18
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity	\$3,538.41
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth	\$3,468.31
TDZR96	8' six way dozer blade	\$10,281.16
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	\$1,227.87

FIELD INSTALLED OPTIONS

19141-99948	3" retractable seat belt in lieu of standard 2"	\$91.00
1914100145	3-point 2" seat belt kit in lieu of standard 2"	\$288.86
K48867001	Hydraulic quick attach coupler kit (for Canopy unit)	\$2,198.76



TL12R2

Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 12,300 lbs.	Radial boom design
Overall Width Without Bucket: 6' 5.2"	Tilt-up operators compartment
Tipping Load (SAE 732) 8,629 lbs.	Electronic dial type throttle and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 2,975 lbs	Back-up alarm
Bucket Digging Force: 8,210 lbs.	Top and rear windows
Horsepower / RPM: 111.3 / 2,400	Automatic fuel bleed system
Travel Speed: 5.0 / 7.8 mph	Pilot operated joystick controls
Auxiliary Flow: 23.2 gpm	Universal quick attach mounting bracket
Ground Pressure: 4.58 psi	Deluxe high back suspension seat with retractable seatbelt
Maximum Lift Height to Bucket Pin: 10' 6"	One and two way auxiliary hydraulics
Reach Fully Raised: 3' 1.8"	Electronic engine monitoring system
Canopy/Cab height: 7' 7"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Active power control power management system	Proportional thumb wheel control auxiliary hydraulics with detent function
Front & rear LED working lights	Hydraulic self-leveling bucket
ROPS/FOPS Level 1 operator protection	Flat face, pressure relieving Hydraulic Couplers
Multi function color monitor	Standard 14-pin connector with push button control
Selectable working modes	Dual element air cleaner
	Push button boom float with detent

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12R2-R	TL12 with Canopy, 17.7" Rubber tracks	\$97,786
TL12R2-RR (w/ RC)	TL12R (above Equipped) with Ride Control*	\$98,637
TL12R2-RP (w/ PC)	TL12R (above Equipped) with Pattern Control*	\$98,940
TL12R2-RRP (w/ RC & PC)	TL12R (above Equipped) with Ride Control & Pattern Control*	\$99,792

TL12R2-CR	TL12 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door, AM/FM/MP3 Radio	\$105,744
TL12R2-CRR (w/ RC)	TL12CR (above Equipped) with Ride Control*	\$106,594
TL12R2-CRP (w/ PC)	TL12CR (above Equipped) with Pattern Control*	\$106,898
TL12R2-CRRP (w/ RC & PC)	TL12CR (above Equipped) with Ride Control & Pattern Control*	\$107,747

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$3,125.37
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	\$3,115.18
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity	\$3,538.41
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth	\$3,468.31
TDZR96	8' six way dozer blade	\$10,281.16
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	\$1,227.87

FIELD INSTALLED OPTIONS

19141-99948	3" retractable seat belt in lieu of standard 2"	\$91.00
1914100145	3-point 2" seat belt kit in lieu of standard 2"	\$288.86
K48867001	Hydraulic quick attach coupler kit (for Canopy unit)	\$2,198.76
K28863001	Counter Weight Kit (450 lbs) (ROC: 3,291 lbs)	\$1,875.00
TBK56104	BUMPER KIT (TL12V/R ONLY)	\$4,815.66



TL12R2

Track Loader

HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 12,590 lbs.	Radial boom design
Overall Width Without Bucket: 6' 5.2"	Tilt-up operators compartment
Tipping Load (SAE 732) 8,629 lbs.	Electronic dial type throttle and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 2,975 lbs	Back-up alarm
Bucket Digging Force: 8,210 lbs.	Top and rear windows
Horsepower / RPM: 111.3 / 2,400	Automatic fuel bleed system
Travel Speed: 5.0 / 7.8 mph	Pilot operated joystick controls
Auxiliary Flow (SP1): 23.2 gpm STD / 40.4 gpm HF	Universal quick attach mounting bracket
Auxiliary Flow (SP2): 23.2 gpm	Deluxe high back suspension seat with retractable seatbelt
Ground Pressure: 4.68 psi	One and two way auxiliary hydraulics
Maximum Lift Height to Bucket Pin: 10' 6"	Electronic engine monitoring system
Reach Fully Raised: 3' 1.8"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Cab height: 7' 9.7"	Proportional thumb wheel control auxiliary hydraulics with detent function
Active power control power management system	Hydraulic self-leveling bucket
Front & rear LED working lights	Flat face, pressure relieving Hydraulic Couplers
ROPS / FOPS Level 2 operator protection	Standard 14-pin connector with push button control
Multi function color monitor	Dual element air cleaner
Selectable working modes	Push button boom float with detent
TFM hardware standard equipment, service included through the standard warranty period	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12R2-CRH	TL12 with Cab with Air Conditioning/Heat, Defroster, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door, AM/FM/MP3 Radio, HIGH FLOW Auxiliary Hydraulics	\$109,388
TL12R2-CRHR (w/ RC)	TL12CRH (above Equipped) with Ride Control*	\$110,238
TL12R2-CRHP (w/ PC)	TL12CRH (above Equipped) with Pattern Control*	\$110,542
TL12R2-CRHRP (w/ RC & PC)	TL12CRH (above Equipped) with Ride Control & Pattern Control*	\$111,391

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$3,125.37
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	\$3,115.18
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity	\$3,538.41
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth	\$3,468.31
TDZR96	8' six way dozer blade	\$10,281.16
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	\$1,227.87

FIELD INSTALLED OPTIONS

1914199948	3" retractable seat belt in lieu of standard 2"	\$91.00
1914100145	3-point 2" seat belt kit in lieu of standard 2"	\$288.86
K28863001	Counter Weight Kit (450 lbs) (ROC: 3,291 lbs)	\$1,875.00
TWK56088	BUMPER KIT, hydraulic winch (TL12V/R ONLY)	\$12,096.82
TBK56104	BUMPER KIT (TL12V/R ONLY)	\$4,815.66



TL12V2

Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight (Canopy/Cab): 12,860 lb / 13,190 lb	Vertical boom design
Overall Width Without Bucket: 6' 5.2"	Tilt-up operators compartment
Tipping Load (SAE 732) 11,737 lbs.	Electronic dial type throttle and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 4,107 lbs	Back-up alarm
Bucket Digging Force: 7,874 lbs.	Top and rear window
Horsepower / RPM: 111.3 / 2,400	Automatic fuel bleed system
Travel Speed: 5.0 / 7.8 mph	Pilot operated joystick controls
Auxiliary Flow: 23.2 gpm	Universal quick attach mounting bracket
Ground Pressure (Canopy / Cab): 4.8 psi / 4.9 psi	Deluxe high back suspension seat with retractable seatbelt
Maximum Lift Height to Bucket Pin: 10' 10"	One and two way auxiliary hydraulics
Reach Fully Raised: 3' 0.4"	Electronic engine monitoring system
Canopy/Cab height: 7' 7.7"	Electrohydraulic push button controls of auxiliary hydraulic circuit
ROPS/FOPS Level 1 operators protection	Proportional slide switch control auxiliary hydraulics with detent function
Front & rear LED working lights	Hydraulic self-leveling bucket
Selectable working modes	Flat face, pressure relieving hydraulic couplers
Active power control power management system	Standard 14-pin connector with push button control
Multi function color monitor	Dual element air cleaner
	Push button boom float with detent

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12V2-R	TL12V with Canopy, 17.7" Rubber tracks	\$101,431
TL12V2-RR (w/ RC)	TL12VR (above Equipped) with Ride Control*	\$102,281
TL12V2-RP (w/ PC)	TL12VR (above Equipped) with Pattern Control*	\$102,585
TL12V2-RRP (w/ RC & PC)	TL12VR (above Equipped) with Ride Control & Pattern Control*	\$103,436

TL12V2-CR	TL12V with ROPS/FOPS Cab, Air Conditioning/Heat, Defroster, AM/FM/MP3 Radio, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door	\$109,388
TL12V2-CRR (w/ RC)	TL12VCR (above Equipped) with Ride Control*	\$110,238
TL12V2-CRP (w/ PC)	TL12VCR (above Equipped) with Pattern Control*	\$110,542
TL12V2-CRRP (w/ RC & PC)	TL12VCR (above Equipped) with Ride Control & Pattern Control*	\$111,391

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$3,125.37
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	\$3,115.18
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity	\$3,538.41
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth - 27 cu.ft. capacity	\$3,468.31
TDZR96	8' six way dozer blade	\$10,281.16
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	\$1,227.87

FIELD INSTALLED OPTIONS

1914199948	3" retractable seat belt in lieu of standard 2"	\$91.00
1914100145	3-point 2" seat belt kit in lieu of standard 2"	\$288.86
K48857001	Hydraulic quick attach coupler kit (for Canopy unit)	\$2,298.70
K28863001	Counter Weight Kit (450 lbs) (ROC: 4,815 lbs)	\$1,875.00
TBK56104	BUMPER KIT (TL12V/R ONLY)	\$4,815.66

Prices and specifications
subject to change without notice

P-22-A
Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
Effective 1 January 2025
Revised 07-01-2025



TL12V2

Track Loader

HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel: 706-693-3600 Fax: 706-693-3725

www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 13,190 lbs.	Vertical boom design
Overall Width Without Bucket: 6' 5.2"	ROPS/FOPS tilt-up operators compartment
Tipping Load (SAE 732) 11,737 lbs.	Electronic dial type throttle and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 4,107 lbs	Back-up alarm
Bucket Digging Force: 7,874 lbs.	Top and rear window
Horsepower / RPM: 111.3 / 2,400	Automatic fuel bleed system
Travel Speed: 5.0 / 7.8 mph	Pilot operated joystick controls
Auxiliary Flow (Std / High Flow): 23.2 gpm / 40.4 gpm	Universal quick attach mounting bracket
Ground Pressure: 4.9 psi	Deluxe high back suspension seat with retractable seatbelt
Maximum Lift Height to Bucket Pin: 10' 10"	One and two way auxiliary hydraulics
Reach Fully Raised: 3' 0.4"	Electronic engine monitoring system
Cab height: 7' 9.7"	Electrohydraulic push button controls of auxiliary hydraulic circuit
ROPS/FOPS Level 2 operators protection	Proportional slide switch control auxiliary hydraulics with detent function
Front & rear LED working lights	Hydraulic self-leveling bucket
Selectable working modes	Flat face, pressure relieving hydraulic couplers
Active power control power management system	Standard 14-pin connector with push button control
Multi function color monitor	Dual element air cleaner
	Push button boom float with detent

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12V2-CRH	TL12 with Cab with Air Conditioning/Heat, Defroster, AM/FM/MP3 Radio, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door HIGH FLOW Auxiliary Hydraulics	\$113,032
TL12V2-CRHR (w/ RC)	TL12VCRH (above Equipped) with Ride Control*	\$113,882
TL12V2-CRHP (w/ PC)	TL12VCRH (above Equipped) with Pattern Control*	\$114,186
TL12V2-CRHRP (w/ RC & PC)	TL12VCRH (above Equipped) with Ride Control & Pattern Control*	\$115,036

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$3,125.37
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	\$3,115.18
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity	\$3,538.41
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth - 27 cu.ft. capacity	\$3,468.31
TDZR96	8' six way dozer blade	\$10,281.16
TPFWT4855	HD 48" pallet forks and frame (Rated 5500 lb)	\$1,227.87

FIELD INSTALLED OPTIONS

1914199948	3" retractable seat belt in lieu of standard 2"	\$91.00
1914100145	3-point 2" seat belt kit in lieu of standard 2"	\$288.86
K28863001	Counter Weight Kit (450 lbs) (ROC: 4,815 lbs)	\$1,875.00
TWK56088	BUMPER KIT, hydraulic winch (TL12V/R HF ONLY)	\$12,096.82
TBK56104	BUMPER KIT (TL12V/R ONLY)	\$4,815.66



TCR50-2

Dump Carrier

519 Bonnie Valentine Way, Pendergrass, GA 30567

Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight 14,440 lb	Travel Alarm
Dump Body Capacity - Heaped 2.68 cu yd - Struck 1.50 cu yd	Beacon Lamp Switch
Maximum Loading Weight 8,157 lb	Rear View Monitor
Travel Speed 4.3 mph / 5.9 mph	Double Flanged Track Rollers
Gradeability 30°	2-Speed Travel with Automatic Shift
Ground Pressure Full 6.1 psi Empty 3.9 psi	High Torque Planetary Final Drive
Travel Traction Force 8,115 lbf	450 mm Rubber Crawlers
EU Stage V / EPA Tier 4 Compliant	Hydraulic Joystick Controls
Turbocharged	Hydraulic Tank w/ Fluid Sight Gauge
DOC+DPF+SCR Exhaust Aftertreatment	Air Breather, Hydraulic Tank
Automatic Fuel Bleed System	180 Degree Turning Dump
Double Element Air Cleaner	ROPS/FOPS (TOP Guard, Level II)
Automatic Deceleration	Deluxe High Back Adjustable Suspension Seat with Head Rest
High Capacity Fuel Tank	12V Power Outlet
Engine Auto Stop	2" Retractable Seat Belt
Parking Brake	3" Seat Belt Optional
5.7" Color Multi-Informational Display	Cab with Front / Rear Windshield
Sealed Rocker Switches	Wiper and Washer, Skylight with
12-volt System with 80 amp Alternator	Sunshade, Radio with Bluetooth
	Air Conditioner

LED Light Package 2; Forward Facing, Front and Rear Cab

TFM hardware standard equipment, service included through the standard warranty period

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TCR50-2CR	TCR50 Dump Carrier with Cab and dump bed	\$132,870

FIELD INSTALLED OPTIONS

19141-99948	3" retractable seat belt in lieu of standard 2"	\$91.00
-------------	---	----------------



TW60

Wheel Loader

SERIES 2

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 10,692 lbs	ROPS / FOPS Level 1 Cab
Tip Load, Straight: 6,724 lbs	Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost
Bucket Breakout Force: 5,822 lbs	LCD Gauge panel with multi-function operator information center
Lift Arm Breakout Force: 6,675 lb	Suspension Seat
HP / RPM: 61 / 2300	Single control handle for direction (F/R) and loader functions
Travel Speed (Max): 12.4 mph	EPA Final Tier 4 Yanmar turbocharged, intercooled engine 4TNV86CHT-M
Auxiliary Flow: 15.8 gpm	100% Front and rear differential lock
Maximum Height to Bucket Pin: 10" 3.2"	Universal skid steer hydraulic coupler
Height: 8' 1.4'	Bucket float
Articulation: 40 / 40	Bucket level indicator
Reach Fully Raised: 26.4"	Mechanical bucket positioning
	Safety features include: back up alarm, lights, retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights), front driving lights, front and rear hazard and directional indicators

ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TW60C2	TW60-2 Cab	\$96,663
TW60C2HS	TW60 Cab with High Speed Road Gear (17 mph max speed)	\$98,000

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES

TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

BTW65TIREHD	Heavy Duty Construction Tire Assy for TW602 / TW65 / TW80 (4 x Tire Assy)	\$5,280.00
-------------	---	-------------------

ATTACHMENTS

BTW60-276	Bucket (76" General Purpose) (1.11 cu. Yd) (SSL Hookup) for TW60-2	\$3,620.93
BTW60-276A	Blade, bolt-on (76") (For BTW60-276)	\$753.84
BTW60-2PF	48" Fork Assy for TW60-2 (Rated 6,000 lbs) (SSL Hookup)	\$2,792.71

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
------------	---	----------------



TW80

Wheel Loader

SERIES 3

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 12,700 lbs	Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost
Tip Load, Straight: 10,065 lbs	LCD Gauge panel with multi-function operator information center with diagnostics and anti-theft capabilities
Bucket Breakout Force: 13,690 lbs	Deluxe suspension seat
Lift Arm Breakout Force: 11,802 lb	Pilot operator loader joystick control
HP / RPM: 73 / 2200	EPA Final Tier 4 turbocharged engine with DOC and engine monitoring system
Travel Speed (Max): 12.4 mph	Side by side radiator and hydraulic oil cooler
Auxiliary Flow: 16.4 gpm	Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick
Maximum Height to Bucket Pin: 11' 1"	100% Front and rear differential lock
Height: 8' 11.5"	Euro style attachment mount with hydraulic coupler
Articulation: 40 /40	Bucket float
Reach Fully Raised: 29"	Mechanical bucket positioning
ROPS / FOPS Cab	Safety features include: back up alarm, lights, retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights), front driving lights, front and rear hazard and directional indicators

ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TW80C3HS	TW80 Cab, High Speed Road Gear (24.8 mph max speed), & Ride Control	\$114,707
TW80C3HH	TW80 Cab, High Flow Auxiliary Hydraulics (26 gpm), High Speed Road Gear (24.8 mph max speed), & Ride Control (Requires 90 + days)	\$120,270

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES

TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

BTW65TIREHD	Heavy Duty Construction Tire Assy for TW65 / TW80 (4 x Tire Assy)	\$5,280.00
-------------	---	-------------------

ATTACHMENTS

BTW8082	81.5" General Purpose Bucket (1.3 cu. Yd) for TW80	\$3,303.72
BTW8082A	82" Bolt-on Blade for BTW8082	\$836.00
BTWPF48	48" Combo Fork Assy for all TW's (Rated 8000 lb)	\$3,146.40
BTWUNIADP	Combo Hitch to Universal SSL Adapter TW50/60/65/80	\$2,630.89

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
TWFASTERKIT	TW Series Coupler Kit	\$211.82
TWCOUPLERKIT	TW Series Coupler Kit for HIGH FLOW UNITS ONLY	\$230.00



TW95

Wheel Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 17,417 lbs	Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost
Tip Load, Straight: 14,388 lbs	LCD Gauge panel with multi-function operator information center with diagnostics and anti-theft capabilities
Bucket Breakout Force: 16,186 lbs	Deluxe suspension seat
Lift Arm Breakout Force: 18,434 lbs	Pilot operator loader joystick control
HP / RPM: 114 / 2200	EPA Final Tier 4 turbocharged engine with DOC/SCR exhaust after treatment system
Travel Speed (Max): 24.8 mph	Side by side radiator and hydraulic oil cooler
Auxiliary Flow: 26.4 gpm	Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick
Maximum Height to Bucket Pin: 11' 10.9"	100% Front and rear differential lock
Height: 9' 7.4"	Euro style attachment mount with hydraulic coupler
Articulation: 40 /40	Bucket float
Reach Fully Raised: 32.3"	Return to dig
ROPS / FOPS Level 2 Cab	Safety features include: back up alarm, lights, retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights), front driving lights, front and rear hazard and directional indicators

ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TW95C2HS	TW95 Cab, High Speed Road Gear, & Ride Control	\$169,360

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES

TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

BTW95TIREHDSET	Heavy Duty Radial Tire Assy for TW95 500/70R24 (Set of 4)	\$12,452.00
----------------	---	--------------------

ATTACHMENTS

BTW95952YDW-BOCE	Bucket (95" General Purpose) (W/BOCE) (2.00 cu. Yd) for TW95	\$6,686.10
BTW9595W-BOCE	Bucket (95" Light Material) (W/BOCE) (2.75 cu. Yd) for TW95	\$7,433.37
BTW9595T	Bucket (95" Light Material) (8 tooth) (2.62 cu. Yd) for TW95	\$8,196.37
BTW95PF	48" Fork Assy for TW95 (Rated 12,500 lbs)	\$4,300.08

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91.00
------------	---	----------------



P3-Power Protection Plan + TFM*

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725
www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.
* All P3 Extended warranties include the TFM monitoring service for models equipped with the TFM monitoring device.

		3YR/3000HR			4YR/4000HR			5YR/5000HR		
Models	Details	Powertrain	Powertrain & Hydraulic	Full Machine	Powertrain	Powertrain & Hydraulic	Full Machine	Powertrain	Powertrain & Hydraulic	Full Machine
TB20E	Item Number List Price	EW20EP31 \$2,016.00	EW20EPH31 \$3,360.00	EW20EFM31 \$4,200.00	EW20EP41 \$4,704.00	EW20EPH41 \$7,224.00	EW20EFM41 \$9,038.40	EW20EP51 \$5,376.00	EW20EPH51 \$8,232.00	EW20EFM51 \$10,315.00
TB210	Item Number List Price	EW210P31 \$529.00	EW210PH31 \$882.00	EW210FM31 \$1,105.00	EW210P41 \$1,235.00	EW210PH41 \$1,896.00	EW210FM41 \$2,373.00	EW210P51 \$1,411.00	EW210PH51 \$2,161.00	EW210FM51 \$2,708.00
TB216	Item Number List Price	EW216P31 \$729.00	EW216PH31 \$1,215.00	EW216FM31 \$1,519.00	EW216P41 \$1,701.00	EW216PH41 \$2,613.00	EW216FM41 \$3,269.00	EW216P51 \$1,944.00	EW216PH51 \$2,977.00	EW216FM51 \$3,731.00
TB216H	Item Number List Price	EW216HP31 \$1,217.00	EW216HPH31 \$2,029.00	EW216HFM31 \$2,536.00	EW216HP41 \$2,840.00	EW216HPH41 \$4,362.00	EW216HFM41 \$5,457.00	EW216HP51 \$3,246.00	EW216HPH51 \$4,970.00	EW216HFM51 \$6,228.00
TB225	Item Number List Price	EW225P31 \$914.00	EW225PH31 \$1,523.00	EW225FM31 \$1,903.00	EW225P41 \$2,132.00	EW225PH41 \$3,273.00	EW225FM41 \$4,096.00	EW225P51 \$2,436.00	EW225PH51 \$3,730.00	EW225FM51 \$4,674.00
TB230	Item Number List Price	EW230P31 \$980.00	EW230PH31 \$1,634.00	EW230FM31 \$2,042.00	EW230P41 \$2,287.00	EW230PH41 \$3,512.00	EW230FM41 \$4,394.00	EW230P51 \$2,614.00	EW230PH51 \$4,002.00	EW230FM51 \$5,015.00
TB235-2	Item Number List Price	EW235P31 \$1,171.00	EW235PH31 \$1,951.00	EW235FM31 \$2,439.00	EW235P41 \$2,732.00	EW235PH41 \$4,195.00	EW235FM41 \$5,249.00	EW235P51 \$3,122.00	EW235PH51 \$4,781.00	EW235FM51 \$5,991.00
TB335R	Item Number List Price	EW335P31 \$1,591.00	EW335PH31 \$2,651.00	EW335FM31 \$3,314.00	EW335P41 \$3,712.00	EW335PH41 \$5,700.00	EW335FM41 \$7,132.00	EW335P51 \$4,242.00	EW335PH51 \$6,496.00	EW335FM51 \$8,139.00
TB350R	Item Number List Price	EW350P31 \$2,016.00	EW350PH31 \$3,360.00	EW350FM31 \$4,200.00	EW350P41 \$4,704.00	EW350PH41 \$7,224.00	EW350FM41 \$9,038.40	EW350P51 \$5,376.00	EW350PH51 \$8,232.00	EW350FM51 \$10,315.20
TB240	Item Number List Price	EW240P31 \$1,168.00	EW240PH31 \$1,946.00	EW240FM31 \$2,433.00	EW240P41 \$2,725.00	EW240PH41 \$4,185.00	EW240FM41 \$5,236.00	EW240P51 \$3,114.00	EW240PH51 \$4,769.00	EW240FM51 \$5,976.00
TB250-2	Item Number List Price	EW250/2P31 \$1,431.00	EW250/2PH31 \$2,386.00	EW250/2FM31 \$2,982.00	EW250/2P41 \$3,340.00	EW250/2PH41 \$5,129.00	EW250/2FM41 \$6,417.00	EW250/2P51 \$3,817.00	EW250/2PH51 \$5,845.00	EW250/2FM51 \$7,324.00
TB257FR	Item Number List Price	EW257P31 \$1,857.00	EW257PH31 \$3,095.00	EW257M31 \$3,869.00	EW257P41 \$4,334.00	EW257PH41 \$6,655.00	EW257M41 \$8,327.00	EW257P51 \$4,953.00	EW257PH51 \$7,584.00	EW257FM51 \$9,503.00
TB260	Item Number List Price	EW260P31 \$1,588.00	EW260PH31 \$2,646.00	EW260FM31 \$3,308.00	EW260P41 \$3,704.00	EW260PH41 \$5,689.00	EW260FM41 \$7,118.00	EW260P51 \$4,234.00	EW260PH51 \$6,483.00	EW260FM51 \$8,123.00
TB280FR	Item Number List Price	EW280P31 \$2,643.00	EW280PH31 \$4,405.00	EW280FM31 \$5,506.00	EW280P41 \$6,167.00	EW280PH41 \$9,471.00	EW280FM41 \$11,849.00	EW280P51 \$7,048.00	EW280PH51 \$10,792.00	EW280FM51 \$13,523.00
TB290	Item Number List Price	EW290P31 \$2,492.00	EW290PH31 \$4,154.00	EW290FM31 \$5,192.00	EW290P41 \$5,815.00	EW290PH41 \$9,931.00	EW290FM41 \$11,174.00	EW290P51 \$6,646.00	EW290PH51 \$10,177.00	EW290FM51 \$12,762.00
TB370	Item Number List Price	EW370P31 \$2,621.00	EW370PH31 \$4,368.00	EW370FM31 \$5,460.00	EW370P41 \$6,115.00	EW370PH41 \$9,381.00	EW370FM41 \$11,750.00	EW370P51 \$8,989.00	EW370PH51 \$10,702.00	EW370FM51 \$13,410.00
TB2150	Item Number List Price	EW2150P31 \$4,057.00	EW2150PH31 \$6,762.00	EW2150FM31 \$8,453.00	EW2150P41 \$9,467.00	EW2150PH41 \$14,538.00	EW2150FM41 \$18,190.00	EW2150P51 \$10,819.00	EW2150PH51 \$16,667.00	EW2150FM51 \$20,759.00
TB395W-2S	Item Number List Price	EW395W2P31 \$4,990.00	EW395W2PH31 \$8,316.00	EW395W2FM31 \$10,395.00	EW395W2P21 \$11,642.00	EW395W2PH21 \$17,879.00	EW395W2FM21 \$22,370.00	EW395W2P51 \$13,306.00	EW395W2PH51 \$20,374.00	EW395W2FM51 \$25,530.00
TB395W-4S	Item Number List Price	EW395W4P31 \$5,141.00	EW395W4PH31 \$8,568.00	EW395W4FM31 \$10,710.00	EW395W4P41 \$11,995.00	EW395W4PH41 \$18,421.00	EW395W4FM41 \$23,048.00	EW395W4P51 \$13,709.00	EW395W4PH51 \$20,992.00	EW395W4FM51 \$26,340.00

PLEASE NOTE:

TFM Monitoring is included with all P3 Extended Warranties purchased for the duration of the extended warranty period, provided the Takeuchi Model is equipped with a TFM Monitoring Device.



P3-Power Protection Plan + TFM*

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725
www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

* All P3 Extended warranties include the TFM monitoring service for models equipped with the TFM monitoring device.

Models	Details	3YR/3000HR			4YR/4000HR			5YR/5000HR		
		Powertrain	Powertrain & Hydraulic	Full Machine	Powertrain	Powertrain & Hydraulic	Full Machine	Powertrain	Powertrain & Hydraulic	Full Machine
TL6	Item Number	EWL6P31	EWL6PH31	EWL6FM31	EWL6P41	EWL6PH41	EWL6FM41	EWL6P51	EWL6PH51	EWL6FM51
	List Price	\$985.00	\$1,642.00	\$2,053.00	\$2,299.00	\$3,531.00	\$4,418.00	\$2,628.00	\$4,023.00	\$5,042.00
TL8R2	Item Number	EWL8/2P31	EWL8/2PH31	EWL8/2FM31	EWL8/2P41	EWL8/2PH41	EWL8/2FM41	EWL8/2P51	EWL8/2PH51	EWL8/2FM51
	List Price	\$1,285.00	\$2,142.00	\$2,678.00	\$2,999.00	\$4,605.00	\$5,762.00	\$3,427.00	\$5,248.00	\$6,576.00
TL8R2-H	Item Number	EWL8/2HP31	EWL8/2HPPH31	EWL8/2HFM31	EWL8/2HP41	EWL8/2HPPH41	EWL8/2HFM41	EWL8/2HP51	EWL8/2HPPH51	EWL8/2HFM51
	List Price	\$1,436.00	\$2,394.00	\$2,993.00	\$3,352.00	\$5,147.00	\$6,440.00	\$3,830.00	\$5,865.00	\$7,350.00
TL10V2	Item Number	EWL10VP31	EWL10VPPH31	EWL10VFM31	EWL10VP41	EWL10VPPH41	EWL10VFM41	EWL10VP51	EWL10VPPH51	EWL10VFM51
	List Price	\$1,739.00	\$2,898.00	\$3,623.00	\$4,057.00	\$6,231.00	\$7,796.00	\$4,637.00	\$7,100.00	\$8,897.00
TL11R3	Item Number	EWL12HP31	EWL12HPPH31	EWL12HFM31	EWL12HP41	EWL12HPPH41	EWL12HFM41	EWL12HP51	EWL12HPPH51	EWL12HFM51
	List Price	\$2,029.00	\$3,381.00	\$4,226.00	\$4,733.00	\$7,269.00	\$9,095.00	\$5,410.00	\$8,283.00	\$10,380.00
TL12V2/R2	Item Number	EWL12VP31	EWL12VPPH31	EWL12VFM31	EWL12VP41	EWL12VPPH41	EWL12VFM41	EWL12VP51	EWL12VPPH51	EWL12VFM51
	List Price	\$2,260.00	\$3,767.00	\$4,709.00	\$5,274.00	\$8,100.00	\$10,134.00	\$6,028.00	\$9,230.00	\$11,566.00
TCR50	Item Number	EWCR50P31	EWCR50PH31	EWCR50FM31	EWCR50P41	EWCR50PH41	EWCR50FM41	EWCR50P51	EWCR50PH51	EWCR50FM51
	List Price	\$3,251.00	\$5,418.00	\$6,773.00	\$7,585.00	\$11,649.00	\$14,574.00	\$8,669.00	\$13,274.00	\$16,633.00

PLEASE NOTE:

TFM Monitoring is included with all P3 Extended Warranties purchased for the duration of the extended warranty period, provided the Takeuchi Model is equipped with a TFM Monitoring Device.



P3-Power Protection Plan

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

		3YR/3000HR			4YR/4000HR			5YR/5000HR		
<i>Models</i>	<i>Details</i>	<i>Powertrain</i>	<i>Powertrain & Hydraulic</i>	<i>Full Machine</i>	<i>Powertrain</i>	<i>Powertrain & Hydraulic</i>	<i>Full Machine</i>	<i>Powertrain</i>	<i>Powertrain & Hydraulic</i>	<i>Full Machine</i>
TW60 Series II	Item Number	EW60/2P32	EW60/2PH32	EW60/2FM32	EW60/2P42	EW60/2PH42	EW60/2FM42	EW60/2P52	EW60/2PH52	EW60/2FM52
	List Price	1768	2946	3683	4125	6335	7926	4714	7218	9045
TW80 Series II/III	Item Number	EW80P32	EW80PH32	EW80FM32	EW80P42	EW80PH42	EW80FM42	EW80P52	EW80PH52	EW80FM52
	List Price	1825	3041	3801	4257	6538	8180	4866	7450	9336
TW95	Item Number	EW95P32	EW95PH32	EW95FM32	EW95P42	EW95PH42	EW95FM42	EW95P52	EW95PH52	EW95FM52
	List Price	2956	4927	6158	6897	10592	13253	7883	12070	15125

PLEASE NOTE:

TFM Monitoring is included with all P3 Extended Warranties purchased for the duration of the extended warranty period, provided the Takeuchi Model is equipped with a TFM Monitoring Device.