

**DynaLock Corporation**

705 Emmett Street

Bristol, CT 06010

**Phone:** 860.582.4761 • **Fax:** 860.585.0338**Email:** [info@dynalock.com](mailto:info@dynalock.com) • **Website:** [www.dynalock.com](http://www.dynalock.com)**6451 Series Exit Sensor Bar**

The non-latching 6451 Exit Sensor Bar offers immediate “no prior knowledge” egress by pushing on the bar at any point, with 15 Lbs. or less pressure.

A light touch is all that is required to activate one or both internal optical sensors designed to detect an exit attempt. A built-in mechanical switch is also included as a redundant back-up release.

Dual sensors, fail-safe electronics and successful testing in excess of one million cycles offer the user unparalleled reliability and low maintenance costs.

Installation is simple. Complicated tune-in procedure and frequent call-backs for readjustment are not required.

**Releases an electric lock when activated by any means including:**

- Touch
- Shopping Carts
- Gurneys
- Wheelchairs
- Any other device

All models for doors with 5/8” or less frame stop. Actual bar length is 2” less than width of door x 2-3/8”H x 2-7/16”D Distance between mounting holes is 2-3/4” less than width of door.

Results 1 - 3 of 3

<u>Item #</u>	<u>Series</u>	<u>Bar Length</u>	<u>Holding Force</u>	<u>Maximum Current Draw</u>	<u>Terminations</u>
<a href="#"><u>66451-36-US28</u></a>	Exit Sensor Bar	36 in	15 lb	100 mA	Removable Terminal Block
<a href="#"><u>66451-42-US28</u></a>	Exit Sensor Bar	42 in	15 lb	100 mA	Removable Terminal Block
<a href="#"><u>66451-48-US28</u></a>	Exit Sensor Bar	48 in	15 lb	100 mA	Removable Terminal Block

Results 1 - 3 of 3