


PART NUMBER 659216

UL Listed and Rated Type CL2P or CMP Siamese Cable



CABLE SPECIFICATIONS

DESCRIPTION	Siamese Type RG 59/U Plenum, 20 AWG Solid Bare Copper Center Conductor with a 95% Bare Copper Braid with 18/2 Non-Shielded Tinned Copper Plenum, UL Listed Type CL2P/CMP, C(UL)
CONDUCTOR	Coax: 20 AWG Solid Bare Copper; Twisted Pair: 18 (16/30 Tinned Copper)
COLOR CODE	Black-White
SHIELD	Coax: 95% Bare Copper Braid; Twisted Pair: N/A
JACKET	Coax: Plenum Rated PVC; Twisted Pair: Plenum Rated PVC
JACKET COLOR	White Jacket
MARKING	CLOSED CIRCUIT VIDEO SURVEILLANCE CAMERA CABLE CAMERA / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 CL2P OR CMP 2/C #18 + 1/C 20 AWG 75 C. (UL) C(UL) FT-6 CCTVP SIAMESE
OVERALL DIAMETER	Coax: .174" Nom.; Twisted Pair: .138" Nom.; Jacket: .354" x .204" Nom.
CABLE WEIGHT	46 Lbs/Mft.
CAPACITANCE	Coax: 17.3 pF/ft. Nom.
IMPEDANCE	Coax: 75 Ohms
TEMPERATURE RATING	75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	Power Limited Circuit Cable, Class 2, UL Type CL2P/CMP, C(UL)



All specifications referenced are nominal measurements unless otherwise noted.