

SEALMASTER EQUIPMENT CATALOG SM10-20

<u>PRODUCT #</u>	<u>DESCRIPTION</u>	<u>RETAIL PRICE</u>	<u>DISCOUNTED PRICE</u>
Spray Applicator			
E1000	SP300 Dual	\$62,355.00	\$58,212.00
E1005	SP575 Dual	\$69,025.00	\$65,574.00
Spray trailer			
E1120	TR575 Pro Air	\$21,045.00	\$18,403.00
E1132	TR750 Pro Air	\$23,500.00	\$20,971.00
Chip Spreader			
E2330	10' Chip Spreader	\$24,990.00	\$22,594.00
Heated Asphalt Storage Tank			
E1870	10,000 gallon heated tank	\$65,360.00	\$62,092.00
Heated Tack Distributor			
E2220	TR300 Tack Distributor	\$15,430.00	\$13,255.00
E2260	TR575 Tack Distributor	\$17,870.00	\$15,018.00
Crack Sealing Trailers			
E2728XD	CrackPro 125 gravity melter	\$26,110.00	\$23,936.00
E2745HH	CrackPro 125 Heated Hose	\$53,530.00	\$50,854.00
E2747HH	CrackPro 125 Heated Hose/Air	\$70,350.00	\$66,832.00
E2755HH	CrackPro 260 Heated Hose	\$60,905.00	\$57,794.00
E2765HH	CrackPro 260 Heated Hose/Air	\$77,845.00	\$73,953.00
E2755DP	CrackPro 260 Heated Hose/Dual Pumps	\$74,815.00	\$71,074.00
E2776	CRACKPRO 300 MASTIC MACHINE	\$67,055.00	\$63,702.00



Shown with water option

SP 300 DUAL SPRAY / SQUEEGEE MACHINE

A 320-GALLON CAPACITY MACHINE THAT DOES IT ALL - SPRAY BAR, SPRAY WAND, AND SQUEEGEE APPLICATION

Shown with hydraulic spraybar option

DESIGNED TO MIX AND APPLY PAVEMENT SEALERS WITH OR WITHOUT SAND

SP 300 DUAL™ Features:

- Kubota gasoline engine
- SandPumper II 2" material pump. Shifts to neutral when wand or spray bar is shut off
- Round tank design with true, full-sweep agitation and rubber wiper blades
- 75-foot hose and spray wand
- Rear wheel direct drive
- Power steering for ease of maneuvering
- Quick change floating squeegee assembly with rear-angling squeegee (windrow feature) and front box squeegee
- Emergency brake



SPECIFICATIONS:

Height	65"
Width.....	63"
Length.....	140"
Wheel Base	60"
Squeegee width.....	93"
Spray width.....	108"
Weight.....	3,880 lbs.
Material Tank Capacity.....	320 gallons
Water Tank Capacity Option.....	28 gallons
Engine.....	49 HP Kubota gasoline
Steering.....	Power
Drivetrain.....	Hydrostat Direct Drive

PRODUCT #	DESCRIPTION	WEIGHT
E1000	SP 300 Dual	3,880 lbs.
E9000	Blocking / Bracing Charge	400 lbs.
<i>Options:</i>		
P50402	28 Gallon Water System	
P50246D	Hydraulically Activated Spray bar	

* Call for pricing

STANDARD FEATURES:

							
Rear Wheel Direct-Drive	Power Steering	Hydraulic Shift for Angling the Squeegee	User-Friendly Control Panel	Hydraulically Driven Dual Diaphragm Material Pump	Gasoline Engine Standard	Dual Easy-Open Butterfly Sealer Discharge Valves	1-Gallon Basket Strainer Reduces Tip Clogging



SP 575 DUAL SPRAY / SQUEEGEE MACHINE

A 575-GALLON CAPACITY MACHINE THAT DOES IT ALL - SPRAY BAR, SPRAY WAND, AND SQUEEGEE APPLICATION

DESIGNED TO MIX AND APPLY PAVEMENT SEALERS WITH OR WITHOUT SAND

SP 575 Dual Features:

- Round tank design with true, full-sweep agitation and rubber wiper blades
- SandPumper II 2" material pump. Shifts to neutral when wand or spray bar is shut off
- Quick change floating squeegee assembly with rear-angling squeegee (windrow feature) and front box squeegee
- All wheel drive for added traction and easier trailer loading
- Spray bar, spray wand
- Power steering for ease of maneuvering
- Easy-open, butterfly sealer discharge valves
- Emergency brake

SPECIFICATIONS:

Height	74"
Width	65"
Length	14"
Wheel Base	60"
Squeegee width	104"
Weight	4,760 lbs.
Material Tank Capacity	575 gallons
Water Tank Capacity Option	28 gallons
Engine	49 HP Kubota gasoline

PRODUCT #	DESCRIPTION	WEIGHT
E1005	SP 575 Dual	4,760 lbs.
E9000	Blocking / Bracing Charge	400 lbs.
Optional Features:		
P50402	28 Gallon Water System	
P50246D	Hydraulically Activated Spraybar	

* Call for pricing

STANDARD FEATURES:

							
Rear Wheel Direct-Drive	Power Steering	Hydraulic Shift for Angling the Squeegee	User-Friendly Control Panel	Hydraulically Driven Dual Diaphragm Material Pump	Gasoline Engine Standard	Dual Easy-Open Butterfly Sealer Discharge Valves	1-Gallon Basket Strainer Reduces Tip Clogging




TR 575 & 750 SPRAYMASTER™ WITH PRO-AIR SYSTEM

TRAILER MOUNTED SEALCOAT SPRAY
SYSTEM APPLICATORS

**DESIGNED TO MIX AND APPLY PAVEMENT
SEALER WITH OR WITHOUT SAND**

TR 575 & 750 Features:

- Dependable, low-maintenance air-driven dual diaphragm pump. Shifts to neutral automatically when wand or spray bar is shut off. Sprays sand-filled pavement sealers.
- 575 or 750-gallon tank with hydraulically controlled, full-sweep agitator with rubber wiper blades
- 75-foot hose and spray wand - Spray bar is optional
- Two 6,000 lb. axles
- Running lights and brake lights
- Safety break-away braking system
- One-gallon basket strainer



TR 575 SPECIFICATIONS:

Height	73"
Width	75"
Length with Spray Bar	18'
Length with Storage Deck	20'
Spray Bar Width	88"
Axles	2 - 6,000 lbs.
Tongue Weight Empty	380 lbs.
Engine	GX390 Honda
Material Pump:	
Type	Dual Diaphragm
Inlet / Outlet	1 1/2"
Air Compressor:	
Engine	GX390 Honda
SCFM	30.0

TR 750 SPECIFICATIONS:

Height	81"
Width	75"
Length with Spray Bar	18'
Length with Storage Deck	20'
Spray Bar Width	88"
Axles	2 - 6,000 lbs.
Tongue Weight Empty	390 lbs.
Engine	GX390 Honda
Material Pump:	
Type	Dual Diaphragm
Inlet / Outlet	1 1/2"
Air Compressor:	
Engine	GX390 Honda
SCFM	30.0

PRODUCT #	DESCRIPTION	WEIGHT
E1120	TR 575 Pro-Air	3,100 lbs.
E1120XD	TR 575 Pro-Air Extended Deck	3,900 lbs.
E1132	TR 750 Pro-Air	3,900 lbs.
E1132XD	TR 750 Pro-Air Extended Deck	4,200 lbs.
Optional Features:		
P50246M	Manual spray bar [includes seat and mounting components]	
P50247L	Lever - Manual spray bar	
P50330	50 Gallon water tank, mounting kit and pump	
P50331	Hydraulically driven SandPumper II material pump system	
P50246D	Hydraulically operated spray bar (SandPumper II only)	
P50280B	Water Cooler	
P50281B	Night Work Lights	
P50336	Electric Hose Reel: returns spray hose automatically	
P50337	Hand Operated Hose Reel	
T1145	Brush Water Box 40"	
P50405	2" Air Diaphragm Pump	
E9000	Blocking / Bracing Charge [if required]	400 lbs.

* Call for pricing



R-1 AGGREGATE CHIP SPREADER

IDEAL FOR TAR AND CHIP /
CHIP SEAL APPLICATIONS

The R-1 is a tow-behind aggregate spreader that is ideal for tar and chip operations on roadways. The R-1 distributes aggregate to precise depths with clean-cut edges. It features an open-type spiral agitator to convey material to outer ends of hopper.

**SPREAD WIDTH CAN BE ALTERED WITH
OPTIONAL 12" AND 24" BLOCK-OFF PLATES**

R-1 Aggregate Chip Spreader Features:

- Auger control lever
- Material auger
- Feed gate control lever
- Drive wheels
- Hitch height adjustment
- Quick attachment receiving hitch



Shown with optional 10'
operator platform

PRODUCT #	DESCRIPTION	WEIGHT
E2330	10' spread width, 1.41 cu. yd. capacity	2,420 lbs.
Optional Features:		
PE2380	10' Operator Platform	
PE2460	Truck Hitch - 1 supplied with each spreader	
PE2470	12" Block-Off Plates - to alter width of spread	
PE2480	24" Block-Off Plates - to alter width of spread	
PE2490	Tailgate Hook - (2 required) Two tailgate hooks supplied with each spreader	
E2500	R-1 Trailer System - For towing aggregate spreader	
E9000	Blocking / Bracing Charge (if required)	400 lbs.

* Call for pricing



HEATED ASPHALT STORAGE TANKS

IDEAL FOR PAVING GRADE ASPHALTS, ROOFING ASPHALTS & ASPHALT EMULSIONS

TANKS CAN BE CUSTOMIZED TO MEET SPECIFIC REQUIREMENTS OR SIZES

Heated Asphalt Storage Tank Features:

- 1/4" plate steel construction
- 4" thick mineral wool insulation
- Foam glass block insulation on tank bottom
- Ribbed steel panel outer skin (covers insulation)
- Thermostatically controlled electric heat (all voltages and phases available) - Heater coil system also available
- Liquid level scale



Liquid Level Scale



Heater Control

OPTIONAL FEATURES:




Turbine Agitator



Material Pump

PRODUCT #	DESCRIPTION
E1870	10,000 Gallon
<i>Optional Features:</i>	
P50277B	Material Pump - 80 GPM
P50278B	Propeller Blade Agitation

* Call for pricing




TR 300 HEATED ASPHALT DISTRIBUTOR

HEAT AND SPRAY ASPHALT EMULSIONS, CUTBACKS, REJUVENATORS, PRIMERS, & MORE

TR 300 Features:

- 300 Gallon capacity
- Electric brakes with safety break-away system
- Easy access basket strainer reduces tip clogging
- Positive displacement material pump
- 5-gallon diesel wash down system
- 300,000 BTU vapor heat system with safety shut-off
- Lock down lid with breather vent
- 50-ft. hose and spray wand
- Requires LP gas cylinder - Not included



PRODUCT #	DESCRIPTION	WEIGHT
E2220	TR 300 - Heated Asphalt Distributor	1,805 lbs.
Options:		
P50246M	Manual Spray Bar (includes seat and mounting components) - 10 ft spray width	
P50247L	Lever - Manual Spray Bar	
P50344	2" Pump - Hydraulic Drive w GX240 Honda	
E9000	Blocking / Bracing Charge (if required)	400 lbs.

* Call for pricing

SPECIFICATIONS:

Height	66"
Width	72"
Length	177"
Weight	1,805 lbs.
Tongue Weight Empty	180 lbs.
Axle	6,000 lbs.
Engine	GX160 Honda
Burner System	300,000 BTU vapor heat system with safety shut off
Material Pump	Positive displacement with pressure relief valve 15 GPM

STANDARD FEATURES:



Electric Brakes with Safety Break-Away System



Easy Access Basket Strainer Reduces Tip Clogging



Positive Displacement Material Pump



5 Gallon Diesel Wash Down System



300,000 BTU Vapor Heat System with Safety Shut-Off



Lock down lid with breather vent



Shown with
option P50344

TR 575 HEATED ASPHALT DISTRIBUTOR

HEAT AND SPRAY ASPHALT EMULSIONS, CUTBACKS, REJUVENATORS, PRIMERS, & MORE

TR 575 Features:

- 575 gallon capacity
- Electric brakes with safety break-away system
- Easy access basket strainer reduces tip clogging
- Positive displacement material pump
- 5-gallon diesel wash down system
- 300,000 BTU vapor heat system with safety shut-off
- Lock down lid with breather vent
- 50-ft. hose and spray wand
- Requires LP gas cylinder - Not included



PRODUCT #	DESCRIPTION	WEIGHT
E2260	TR 575 - Heated Asphalt Distributor	3,000 lbs.
Options:		
P50246M	Manual Spray Bar [includes seat and mounting components] - 10 ft spray width	
P50247L	Lever - Manual Spray Bar	
P50344	2" Pump - Hydraulic Drive w GX240 Honda	
E9000	Blocking / Bracing Charge [if required]	400 lbs.

* Call for pricing

SPECIFICATIONS:

Height	73"
Width	75"
Length	17'
Weight	3,000 lbs.
Tongue Weight Empty	300 lbs.
Axle	2 - 6,000 lbs.
Engine	GX160 Honda
Burner System	300,000 BTU vapor heat system with safety shut off
Material Pump	Positive displacement with pressure relief valve 15 GPM

STANDARD FEATURES:



Electric Brakes with Safety Break-Away System



Easy Access Basket Strainer Reduces Tip Clogging



Positive Displacement Material Pump




5 Gallon Diesel Wash Down System



300,000 BTU Vapor Heat System with Safety Shut-Off



Lock down lid with breather vent



**CRACK PRO 260
GRAVITY FLOW**




**CRACK PRO 60
GRAVITY FLOW**

CRACK PRO® GRAVITY FLOW

OIL-JACKETED MELTER FOR HOT
POUR CRACK SEALING MATERIALS

Crack Pro 60, 125 & 260 Gravity Flow Features:

- State-Of-The-Art Burner System with Auto Shut Off
- FWD/REV Hydraulic Agitation
- Direct Drive Hydraulic Agitation
- Anti-Splash Material Loading Hatch
- Oil and Material Temperature Gauges
- Automatic Temperature Control
- Low Profile for Operator Safety



**CRACK PRO 125
GRAVITY FLOW**

CRACK PRO 60 GRAVITY FLOW:

PRODUCT #	DESCRIPTION	WEIGHT
E2730D	Crack Pro 60 - Diesel Fuel Burner	1,500 lbs.

CRACK PRO 125 GRAVITY FLOW:

PRODUCT #	DESCRIPTION	WEIGHT
E2728D	Crack Pro 125 - Diesel Fuel Burner	2,640 lbs.
E2728XD	Crack Pro 125 - Diesel Fuel Burner - Extended Deck	3,020 lbs.

CRACK PRO 260 GRAVITY FLOW:

PRODUCT #	DESCRIPTION	WEIGHT
E2736	Crack Pro 260 - Diesel Fuel Burner	3,640 lbs.
E2736XD	Crack Pro 260 - Diesel Fuel Burner - Extended Deck	4,260 lbs.

* Call for pricing

STANDARD FEATURES:




FWD/REV
Hydraulic Agitation
Valve



Direct Drive
Hydraulic
Agitation



Anti-Splash
Material
Loading Hatch



Oil and Material
Temperature
Gauges

SPECIFICATIONS:

Tank Size	CP 60	CP 125	CP 260
Tank Capacity	60 gallon	125 gallon	260 gallon
Heat Transfer Oil	10 gallons	25 gallons	30 gallons
Max. BTU Input	225,000	225,000	372,000
Construction	Oil Jacket	Oil Jacket	Oil Jacket
Temp. Control	Digital	Digital	Digital
Tank Opening	12" x 14"	12" x 14"	16" x 24"
Insulation	1 1/2" ceramic	1 1/2" ceramic	1 1/2" ceramic
Agitation	Full Sweep Hydraulic	Full Sweep Hydraulic	Full Sweep Hydraulic
Heating System	Diesel burner	Diesel burner	Diesel burner
Power Unit	GX240 Honda	GX240 Honda	GX240 Honda
Suspension	2,500 lb. axle	5,400 lb. axle	6,000 lb. axle
Loading Height	54"	57"	59"
Overall Height	66"	71"	75"
Width	64"	78"	94"
Length	122"	136" XD - 192"	162" XD - 216"

CRACK PRO® HEATED HOSE MACHINES

OIL-JACKETED MELTER / APPLICATORS
FOR HOT POUR CRACK SEALING MATERIALS

ALL DIESEL POWER FOR MAXIMUM EFFICIENCY!

Both the burner and the engine are powered by diesel fuel for maximum safety, efficiency, and performance.

Crack Pro Heated Hose Machine Features:

- State-of-the-art heated hose maintains material temperature throughout the application process
- Industry's fastest heat-up and recovery, (ready to apply product within 1 hour).
- The waterproof steel control cabinet houses all safety interlocks, operations and monitoring of the heating systems (hose, material, heat transfer oil), agitation, pump and audible horn for directional control.
- Anti-splash material loading hatch for safer loading
- Insulated with 1.5" ceramic, covered by a 14-gauge steel outer body
- Electro-hydraulic manifold with flow control for pump and mixer speeds
- Liquid cooled kubota diesel engine
- Diesel fired Beckett Burners are electronically controlled with auto shut off, and side mounted for easy maintenance
- Horn button on wand notifies driver to move ahead or back
- Direct-drive FWD/REV full sweep agitation

TR 125 & 260 DA Model Features:

- Direct drive air compressor with 100' x 5/8" reeled hose & wand
- V1505 Kubota diesel engine

PRODUCT #	DESCRIPTION	WEIGHT
E2745HH	TR 125 D	3,700 lbs.
E2747HH	TR 125 DA	4,000 lbs.
E2755HH	TR 260 D	5,000 lbs.
E2765HH	TR 260 DA	5,300 lbs.
E2755DPH	TR 260 Double Pump	5,300 lbs.
P74001	Upgrade to a 22' hose	

* Call for pricing

ALSO AVAILABLE...



TR 260 Double Pump now available!

SPECIFICATIONS:

Tank Capacity	125, 260 gallons
Heat Transfer Oil	25, 30 gallon capacity
Maximum BTU Input	372,000 BTU
Construction	Oil jacket type tank
Temperature Control	Automatic Electronic
Tank Opening	16" x 24" no splash material loading
Insulation	1 1/2" High Temperature Ceramic
Agitation	Full Sweep, Hydraulically Driven, Forward / Reverse
Material Pump	2" Steel Gear, Reversible
Heating System	Bottom fired forced air diesel fuel
Suspension	Torsion type axle with 5 lug tubeless tire
Application Hose	3/4" x 18' electric hose [22' available]
Heated Hose	Eliminates need to flush out hose for cleanup

	CP 125	CP 260
Loading Height	54"	48"
Overall Height	80"	90"
Width	78"	93"
Length	192"	206"
Empty Weight	3,700 lbs.	5,000 lbs.
Empty Weight with conveyor	4,200 lbs.	5,500 lbs.
Height with conveyor	8' 6"	8' 6"

STANDARD FEATURES ON ALL "D" AND "DA" MODELS:



Digital Control Center with protective steel cover



Anti-Splash Material Loading Hatch



Electro-hydraulic manifold



Liquid Cooled Kubota Diesel Engine



Horn button on wand



Diesel fired Beckett Burner



Direct-Drive FWD/REV Full Sweep Agitation

STANDARD FEATURES ON ALL "DA" MODELS:



Direct Drive Air Compressor



100' x 5/8" Reeled Hose & Wand



V1505 Kubota Diesel Engine

CRACK PRO® MASTIC MACHINE

250- & 300-GALLON CAPACITY MODELS

ENGINEERED FOR EFFICIENCY & SAFETY

NEW!

Crack Pro Mastic Machine Features:

- **Diesel** engine and heating system. No propane required.
- **Oil-jacketed kettle with fast heat-up time** [Approximately 2.5 hours from a cold start].
- **Plow-point agitation** for faster heat-up, with forced material discharge.
- Agitation system provides **unmatched power / torque with safety interlocks** to protect the operator and prevent damage to the machine.
- Hydraulic system is **highly efficient and designed to run cool** (lowering maintenance costs), providing power to the torque-mounted, planetary agitation drive system.
- The waterproof steel control cabinet houses the **Crack Pro brand's proven control system.**
 - Burner temperature controllers with improved material temperature accuracy
 - Safety interlocks
 - Forward / reverse agitation switch
 - Work and strobe lights
- Heavy duty, 6-inch adjustable knife discharge valve to cut through the mastic aggregate.
- Heated **discharge chute stays hot without propane or hot oil** and will not catch on fire when idle. The chute is easily removed for use with wheeled and hand-held applicators.
- **Pail-warmer** melts material from metal pails used in application.
- **Large tool heater box** utilizes a diesel-fired burner with automatic shutoff to prevent overheating tools and wasting fuel.
- Adjustable pintle eye to match hitch height, tandem axle, for good, stable towing and operation. Complete with **battery powered break-away and LED light packages.**
- **Low-cost operation** with highly efficient heating and low-horsepower requirements.
 - The 30-gallon fuel tank allows **15 to 25 hours of operation between fill-ups.**
- **Overnight heaters** allow for quicker application the next day.
- **Maintenance is a breeze** with a 600-degree-rated bearing on the rear and a packing gland with internal grease ports for direct lubrication into the gland on the front. This machine was built with maintenance in mind and easy access to all components that require periodic service. (burners, packing glands, grease Zerks, engine, and drive system).



SPECIFICATIONS:

Model	CP 250	CP 300
Tank Capacity	250 gallon	300 gallon
Heat Transfer Oil	35 gallons	42 gallons
Max. BTU Input	372,000	372,000
Construction	Oil Jacket	Oil Jacket
Temp. Control	Digital	Digital
Tank Opening Material	16" x 24"	16" x 24"
Tank Opening Pail Heat	16" x 16" x 16"	16" x 16" x 16"
Insulation	1.5"	1.5"
Agitation Forward Reverse	Plow-point forced discharge	Plow-point forced discharge
Heating System	Diesel burner	Diesel burner
Power Unit Diesel	Kubota D 602	Kubota D 602
Tandem Axle Suspension	6,000 lb. axles	6,000 lb. axles
Loading Height	60"	60"
Overall Height with Light Kit	108"	108"
Width	82"	82"
Length	200"	212"

PRODUCT #	DESCRIPTION	WEIGHT
E2775	250 Gallon	5,660 lbs.
E2776	300 Gallon	5,860 lbs.
PE2680	Arrowboard	

* Call for pricing

STANDARD FEATURES:



Diesel Tool
Box Heater



Heated Adjustable
Locking Chute



Control Box



Tool Rack



Internally lubricated
packing gland with
drip catch pan



250 GALLON CRACK PRO MASTIC MACHINE

NEW!

Shown with
Optional
Arrowboard



Full Light Kit with Work
Area Lighting, Strobe Light,
and optional Arrowboard



Pail Heater

CRACKMASTER MASTIC

The ideal product for large cracks, bridge joints, plug joints, manhole cover areas, utility joints and more. Mastic consists of rubberized asphalt binder and aggregate.

SEE PAGE 23