



Website WWW.KENSTRUCKREPAIR.com

Email Sales@KENSTRUCKREPAIR.com

Truck Repair, Inc.

Office 815•697•2361

Fax 815•697•2522

Interstate-57 Exit 302 ◀ 400 North Oak - P.O. Box 37 ▶ Chebanse, Illinois 60922

**Quote, Specification, Price on
2020 Titan 53ft 2 Axle Thinwall Possum Belly Tipper – Garbage**

Customer application	Garbage – NON SPIF
Base model	53-2-TW-PB (open top)
Style	Possum
Panel configuration	To suit garbage application
Overall length	53 ft
Overall width	102" nominal
Overall height	13' 6" approx. at front & rear
King pin location	36"
Upper coupler	Std. aluminum coupler assembly with 3" drop with Stainless Steel wear plate set @ 48" high
Number of Axles Primary	Two (2)
Axles	SAF-straight spindle – See Note # 1
Axle track	77"
Suspension	SAF CBX 25/30 245 Fusion Beam – See Note # 9
Location of spreads	89.5" from rear
Hub/drum assembly	10 stud duralite-hub pilot/centrifuse drum – See Note # 1
Disc wheel size	14" x 22.5 – 2" offset
Rims	Mill finish alum. super single
Tires	Brand Michelin
	Size 455/55R22.5
	Tread Xone MET
	Ply 20
	Quantity 4
Axle layout	FRONT-Primary-50-Primary-89.5-REAR
Oil seals	SKF
Lubricants	Oil- Std 80W-90
Brakes	ABS 2S/2M Meritor Wabco with roll stability support – See Note #4
	Slack adj. Meritor Auto
	Cam Enclos All axles–c/w dust shields
Lift kits	None
Lift controls	None
Springs	None
Frame width	48" with 10" I-beam
Rear bumper	Steel, flush, underride
Rubber bumpers	Tailgate Rear bumper
Tow hooks	1- tow hook roadside
Tire carrier	None
Floor	2 ½" thinwall – floor transition slope to be approx. 13.5 degree – See Notes #5, #6, #7

Floor crossmembers		N/A
Landing gear		Jost landing gear model A401G3-17-08 (cushion foot) inboard
Top rail		Titan Tapered Top Rail V1
Top cross tube qty		1 pc
Top cross tube type		Spring steel 5/8" x 4" (two piece version)
Rear Door		Extreme – overslung hinge, solid air release, side finger locks, safety chain
Rear Door Seal		Rubber
Front Door		Std. 35w x 37.5h sealed – curbside hinge with flip step
Tarp header		None
Tarp basket		None
Tarp hooks		None
Tarp/Roof		Roll Over Mesh Ratchet Down Tarp System – See Note #11
Mud flaps	Style	Titan black rubber
	Location	Behind rear tire
	Body – color	Natural aluminum
	Run – gear	Titan black
	Hub / drum	Same as running gear
Paint	Rims or Disc	Aluminum
Light package		2-ID markers per sidewall & midturn, 2-4" dia. per side & 3 rect. in lower sill, 1 per side ID clearance lights at front
	Option #1	Use round plastic 4 1/2" on rear, no stainless cover (anti theft ring)
	Option #2	None
Access	Catwalk Frt	None
	Ladder Frt	Split J ladder in middle w/ 10" long standoffs – See Note #8
	Ladder Rear	J ladder middle & two small catwalks
	Steps Frt out	None
	Steps Frt in	None
	Steps Rear	None

Additional specifications:

- 1) a) invert axles
b) Install Meritor tire inflation system
- 2) Air tanks are to be aluminum
- 3) Sidewall wear plates at rear boomerang style
- 4) Haldex long stroke brake chambers
- 5) Install 3/16 alum floor liner on slope and behind slope
- 6) Provide approx. 17" of ground clearance under belly floor.
- 7) Drain holes all 4 corners of belly with plugs
- 8) Two piece J ladder on front wall bottom section of man door and top section on top of front wall.
- 9) Suspensions will have 1.5" air bag spacers.
- 10) No control box required, controls for air suspension dump and air release tailgate on front air/electric plate. The 2" suspension air gauge is in the corner mitre.
- 15) a) Install sideroll tarp with flaps on front & rear. Operates from rear
b) Titan to supply and install roll bar and the tarp fixed bar w/ full length alum pipe.
c) Roll Bar is 1.5" schedule 80, the fixed bar is 3/4" schedule 80
d) Add tarp bar support rod (pipe) to top of tailgate (No standoffs)

Weight estimate: 15,700 lbs +/- 3%

Volume: 166.1 cubic yards

List Price

\$ 90,638.42

No FET Included, FOB Chebanse, IL

Tarp & Installation Included

No state or local tax included

No license or title fees included