



Website [WWW.KENSTRUCKREPAIR.com](http://WWW.KENSTRUCKREPAIR.com)

Email [Sales@KENSTRUCKREPAIR.com](mailto:Sales@KENSTRUCKREPAIR.com)

*Truck Repair, Inc.*

Office 815•697•2361

Fax 815•697•2522

**Interstate-57 Exit 302 ◀ 400 North Oak - P.O. Box 37 ▶ Chebanse, Illinois 60922**

**Quote Specifications & Weight For:  
2020 Titan 48' 2 Axle Thinwall Tipper Trailer  
With Removeable Roof**

Customer Application		Garbage Compactor – Removeable Roof
Base Model		48-2-TW-TP (open top) Removeable Bolt on Roof
Body Style		Straight
Panel Configuration		7-14" + 1-6" to suit compactor application with EHD Panels – See Note #4,5,6, &10
Overall Length		48'
Overall Width		102" Nominal
Overall Height		13' 4" at front
King Pin Location		36"
Upper Coupler		Flat aluminum coupler assembly @ 48" high
Number of Axles	Primary	(2) Two
	Lift	(0) None
Axle		Dexter-straight spindle
Axle Track		77"
Suspension		Reyco 21B FAB w/ inner wear plates
Location of Spreads		See axle layout
Hub & Drum Assembly		10 stud duralite – hub pilot/centrifuse drum
Disc Wheels Size		8.25 x 22.5
Rims		Steel – Std. Duty – Pre-painted White
Tires	Brand	Goodyear
	Size	11R22.5
	Tread	Endurance RSA
	Ply	14
	Quantity	8
Axle Layout		Front-Primary-50- Primary-29.5-Rear
Oil Seals		SKF
Lubricants		Oil Std 80W-90
Brakes	ABS	2S/1M Meritor Wabco
	Slack Adj	Meritor Auto
	Cam Enclos	All Axles – c/w Dust Shields
Lift Kits		None
Lift Controls		None
Springs		3 leaf TRA-3384
Frame Width		48"
Rear Bumper		Aluminum, Offset, Push – See Note #3
Rubber Bumpers		None on Tailgate
		Steel vertical blocks bolter to bumper
Tow Hooks		Tow shackles

Tire Carrier		None
Floor		Sheet aluminum
		Rear 6' – 5/16", 1/4" for the rest of the floor – See Note #8
Floor Cross members		Boxed 18" apart
Landing Gear		Jost Landing Gear Model A401-G3-19 inboard – See Note #2
Top Rail		Titan Tapered, V1
Top Cross Tube Qty		None – Provide spigot for future spring bar
Top Cross Tube Type		None
Rear Door		Compactor, Overslung hinge, Inner van, air release & side finger locks – See Note #1,3
Rear Door Seal		Rubber
Front Door		Standard – 35w x 37.5h Sealed – Curbside hinge with flip step
Tarp Header		None
Tarp Basket (Hoops)		None
Tarp Hook		None
Tarp/Roof		No Tarp – Removable Bolt on Roof – 3 piece – See Note #9
Mud Flaps	Style	Titan Black Rubber
	Location	Front/Rear primary
Paint	Body	Natural Aluminum
	Run – Gear	Titan Black
	Hub/Drum	Same as running gear
	Rims or Disc	Pre-painted White
Std Light Package – plug form		2 mks per sidewall & midturn, 2-4" dia per side & 3-rect in rear light bar, 1 per side ID clearance lights at front
	Option #1	All lights LED
	Option #2	None
Access	Catwalk – front	None
	Ladder – front	None
	Ladder – rear	None
	Steps – front – out	None
	Steps – front – ins	None
	Steps – rear	None

**Additional Specifications:**

- 1) With sidegrabs, vertical position 63 (?)” from ground air out of suspensions.
  - a. Side grab opening 14 3/8” (?) tall
  - b. Door opening to suit bottom of compactor chute which is (?)” from ground
- 2) Hold 34’ 10” approx. from center of landing gear to rear of bumper blocks
- 4) Compactor sidewall wearplates
- 5) Beef up front wall to SHD wherever possible given man door being installed
- 6) Air/Electrical plate roadside front wall, add suspension dump, tailgate release, & air gauge
- 8) Install alum 3/16” wear plate on rear 16’ of floor
- 9) HD rear 1/3 of roof, NGHD remainder
- 10) Add (2) vents 16” L x 12” T per side on sidewall. See approval drawing for locations
- 11) Add eyebrows over lights rear or rear sill with extended shedder (2”)

Estimated volume: 125 cu yds

**List Price**

**\$ 86,999.50**

*No FET Included, FOB Chebanse, IL*

*No sales tax included*

*No license or title fees included*